

# DIAPHRAGM PUMPS

Lightweight and easy to operate, these pumps are designed to provide continuous flow. Great for pumping long distance or even submersible applications, these air operated pumps offer a great solution for clean and dirty liquids particularly waste oils as they are particle tolerant.



**1/2" AIR-OPERATED DIAPHRAGM PUMP  
L-DDP13**

### TECHNICAL SPECIFICATIONS

- Flow rate up to 45LPM
- Suitable for use with waste oil, diesel fuel, engine coolants and water
- Inlet / Outlet: 1/2" BSP (F)
- Maximum air pressure: 116PSI (8BAR)
- Maximum allowable particle size: 1/8"



**3/4" AIR-OPERATED DIAPHRAGM PUMP  
L-DDP19**

### TECHNICAL SPECIFICATIONS

- Flow rate up to 60LPM
- Suitable for use with waste oil, diesel fuel, engine coolants and water
- Inlet / Outlet: 3/4" BSP (F)
- Maximum air pressure: 116PSI (8BAR)
- Maximum allowable particle size: 1/8"



**1" AIR- OPERATED DIAPHRAGM PUMP  
L-DDP25**

### TECHNICAL SPECIFICATIONS

- Flow rate up to 90LPM
- Suitable for use with waste oil, diesel fuel, engine coolants and water
- Inlet / Outlet: 1" BSP (F)
- Maximum air pressure: 116PSI (8BAR)
- Maximum allowable particle size: 1/8"