



**Experience easy.
No setup. No adjustments. No waste.**

BradyPrinter i5300 Industrial Label Printer

Seriously easy. Really.

When you're focused on efficiency, every process counts, including the steps it takes to print. So why not make it easier? With the BradyPrinter i5300 Industrial Label Printer, you get a smoother and more intuitive experience. Set up, store print jobs and print — easily — and let simplicity drive your efficiency.

- **No waste** — prints on the very first label to maximise material use and cut costs
- **Fast setup** — 20-second material changeovers and drop-lock-print technology
- **Precision** — excellent small-font sharpness and print placement on smaller labels
- **Time-saving features** — prints faster and pauses and resumes jobs if interrupted
- **On-printer label storage** — saves 1,000s of labels with overwrite protection to printer
- **Performance-plus construction** — ideal for printing both high-volume and high-mix jobs



BRADY

5300 RSM 18
HOME ←
Supply Jam
2-88509-102-109 REV C
2.000 x 0.315 in
1 / 28

BradyPrinter i5300

2-88509-102-109
2-88509-102-101 REV C
2-88509-102-100 REV C
2-88509-102-100 REV C
2-88509-102-099 REV C
2-88509-102-099 REV C
2-88509-102-098 REV C
2-88509-102-098 REV C
2-88509-102-097 REV C
2-88509-102-097 REV C

High-Temp Self-Extinguishing Tedlar® Wire Wraps (B-437)

- Top-coated polyvinylfluoride label for wire and cable marking where high temperature and self-extinguishing features are required
- Heavy-duty performance with excellent resistance to water, oil and other fluids and meets MIL-M-87958 Standard
- Upper temp limit of up to 135°C – consult technical data sheet for full performance details




Figure 1




Figure 3a




Figure 4



Part No.	For Use with Printers:	Diagram	Reference	Colour	Label width A (mm)	Label height B (mm)	Horiz. repeat C (mm)	Vert. repeat D (mm)	Web width E (mm)	Labels per row	Labels per roll	Rec. ribbon
133776	i3300, i5300, BBP33	Fig. 4	B33-11-437	Matte White	6.4	6.4	6.4	9.5	81.3	12	15000	B30-R4300
133791	i3300, i5300, BBP33	Fig. 1	B33-1-437	Matte White	19.1	6.4	20.3	8.9	85.1	4	5000	B30-R4300
133833	i3300, i5300, BBP33	Fig. 1	B33-2-437	Matte White	22.9	6.4	28.6	8.9	85.1	3	5000	B30-R4300
133888	i3300, i5300, BBP33	Fig. 1	B33-5-437	Matte White	25.4	12.7	27.3	15.2	85.1	3	5000	B30-R4300
133846	i3300, i5300, BBP33	Fig. 1	B33-29-437	Matte White	31.8	9.5	33.0	12.1	69.9	2	5000	B30-R4300
133889	i3300, i5300, BBP33	Fig. 1	B33-5-437YL	Matte Yellow	25.4	12.7	27.3	15.2	85.1	3	5000	B30-R4300
133847	i3300, i5300, BBP33	Fig. 1	B33-29-437YL	Matte Yellow	31.8	9.5	33.0	12.1	69.9	2	5000	B30-R4300
Continuous rolls												
133776	i3300, i5300, BBP33	Fig. 3a	B33-11-437	Matte White	25.4	25.9m	-	-	30.5	1 roll (cont.)		B30-R4300
133791	i3300, i5300, BBP33	Fig. 3a	B33-1-437	Matte White	38.1	25.9m	-	-	48.3	1 roll (cont.)		B30-R4300
133833	i3300, i5300, BBP33	Fig. 3a	B33-2-437	Matte White	50.8	25.9m	-	-	55.9	1 roll (cont.)		B30-R4300
133888	i3300, i5300, BBP33	Fig. 3a	B33-5-437	Matte White	76.2	25.9m	-	-	86.4	1 roll (cont.)		B30-R4300
133846	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3a	B33-29-437	Matte White	101.6	30.5 m	-	-	101.6	1 roll (cont.)		B30-R4300
133889	i3300, i5300, BBP33	Fig. 3a	B33-5-437YL	Matte Yellow	25.4	25.9m	-	-	30.5	1 roll (cont.)		B30-R4300
133847	i3300, i5300, BBP33	Fig. 3a	B33-29-437YL	Matte Yellow	38.1	25.9m	-	-	48.3	1 roll (cont.)		B30-R4300
133991	i3300, i5300, BBP33	Fig. 3a	B33C-2000-437YL	Matte Yellow	50.8	25.9m	-	-	55.9	1 roll (cont.)		B30-R4300
133998	i3300, i5300, BBP33	Fig. 3a	B33C-3000-437YL	Matte Yellow	76.2	25.9m	-	-	86.4	1 roll (cont.)		B30-R4300

High-Temp Flame-Retardant Polyimide Wire Wraps (B-472)

- Top-coated polyimide label for wire and cable marking where high temperature and self-extinguishing features are required
- Heavy-duty performance with excellent resistance to water, oil and other fluids
- Upper temp limit of up to 160°C – consult technical data sheet for full performance details




Figure 1




Figure 3a




Figure 4



Part No.	For Use with Printers:	Diagram	Reference	Colour	Label width A (mm)	Label height B (mm)	Horiz. repeat C (mm)	Vert. repeat D (mm)	Web width E (mm)	Labels per row	Labels per roll	Rec. ribbon
133778	i3300, i5300, BBP33	Fig. 4	B33-11-472	Matte White	6.4	6.4	6.4	9.5	81.3	12	15000	B30-R4300
133796	i3300, i5300, BBP33	Fig. 1	B33-1-472	Matte White	19.1	6.4	20.3	8.9	85.1	4	5000	B30-R4300
133835	i3300, i5300, BBP33	Fig. 1	B33-2-472	Matte White	22.9	6.4	28.6	8.9	85.1	3	5000	B30-R4300
133890	i3300, i5300, BBP33	Fig. 1	B33-5-472	Matte White	25.4	12.7	27.3	15.2	85.1	3	5000	B30-R4300
133849	i3300, i5300, BBP33	Fig. 1	B33-29-472	Matte White	31.8	9.5	33.0	12.1	69.9	2	5000	B30-R4300
133891	i3300, i5300, BBP33	Fig. 1	B33-5-472YL	Matte Yellow	25.4	12.7	27.3	15.2	85.1	3	5000	B30-R4300
133850	i3300, i5300, BBP33	Fig. 1	B33-29-472YL	Matte Yellow	31.8	9.5	33.0	12.1	69.9	2	5000	B30-R4300
Continuous rolls												
133982	i3300, i5300, BBP33	Fig. 3a	B33C-1000-472	Matte White	25.4	25.9m	-	-	30.5	1 roll (cont.)		B30-R4300
133986	i3300, i5300, BBP33	Fig. 3a	B33C-1500-472	Matte White	31.8	25.9m	-	-	48.3	1 roll (cont.)		B30-R4300
133992	i3300, i5300, BBP33	Fig. 3a	B33C-2000-472	Matte White	50.8	25.9m	-	-	55.9	1 roll (cont.)		B30-R4300
133999	i3300, i5300, BBP33	Fig. 3a	B33C-3000-472	Matte White	76.2	25.9m	-	-	86.4	1 roll (cont.)		B30-R4300
133983	i3300, i5300, BBP33	Fig. 3a	B33C-1000-472YL	Matte Yellow	25.4	25.9m	-	-	30.5	1 roll (cont.)		B30-R4300
133987	i3300, i5300, BBP33	Fig. 3a	B33C-1500-472YL	Matte Yellow	31.8	25.9m	-	-	48.3	1 roll (cont.)		B30-R4300
133993	i3300, i5300, BBP33	Fig. 3a	B33C-2000-472YL	Matte Yellow	50.8	25.9m	-	-	55.9	1 roll (cont.)		B30-R4300
134002	i3300, i5300, BBP33	Fig. 3a	B33C-3000-472YL	Matte Yellow	76.2	25.9m	-	-	86.4	1 roll (cont.)		B30-R4300

PermaSleeve® Heat-Shrink Sleeves (B-342)

- Standard military / industrial grade heat-shrinkable wire marker with 3:1 shrink ratio
- Can be used for identification or wire protection
- Fade-resistant and flame-retardant
- Meets SAE-AS-23053/5 and SAE-AS-81531 specs
- Tested per ASTM E162, ASTM E662 and MIL-STD-202





Figure 21

Figure 21-2



Part No.	For Use with Printers:	Diagram	Reference	Colour	For Wire Gauge (approx.)	For Wire Diameters (mm) Min - Max.	Supplied Diameter B (mm)	Recovered Diameter (mm)	Recovered Wall Thickness (mm)	Qty per Row	Qty per Roll	Rec. ribbon
3:1 Shrink ratio, single-side printable, 2" sleeve width (dimension A)												
142926	i3300, i5300, BBP33	Fig. 21	B33-94-2-342	White	28 to 20	0.6 - 2.0	2.4	0.6	0.6 +/- 0.07	1	1000	B30-R4300
143034	i3300, i5300, BBP33	Fig. 21	B33-125-2-342	White	22 to 16	1.2 - 2.8	3.2	1.2	0.5 +/- 0.07	1	1000	B30-R4300
143036	i3300, i5300, BBP33	Fig. 21	B33-187-2-342	White	20 to 10	1.6 - 3.8	4.7	1.6	0.5 +/- 0.07	1	750	B30-R4300
143038	i3300, i5300, BBP33	Fig. 21	B33-250-2-342	White	16 to 8	2.4 - 5.5	6.4	2.4	0.6 +/- 0.07	1	500	B30-R4300
143039	i3300, i5300, BBP33	Fig. 21	B33-375-2-342	White	12 to 4	3.2 - 8.1	9.5	3.1	0.6 +/- 0.07	1	500	B30-R4300
143040	i3300, i5300, BBP33	Fig. 21	B33-500-2-342	White	8 to 1	4.8 - 11.4	12.7	4.7	0.6 +/- 0.07	1	350	B30-R4300
143041	i3300, i5300, BBP33	Fig. 21	B33-750-2-342	White	6 to 4/0	6.4 - 17.8	19.1	6.4	0.6 +/- 0.07	1	250	B30-R4300
143032	i3300, i5300, BBP33	Fig. 21	B33-1000-2-342	White	2 to 0.950 dia	8.5 - 24.1	25.4	9.5	0.9 +/- 0.07	1	250	B30-R4300
142992	i3300, i5300, BBP33	Fig. 21	B33-1500-2-342	White	n/a	12.7 - 35.6	38.1	12.7	0.9 +/- 0.07	1	150	B30-R4300
142932	i3300, i5300, BBP33	Fig. 21	B33-94-2-342YL	Yellow	28 to 20	0.6 - 2.0	2.4	0.6	0.6 +/- 0.07	1	1000	B30-R4300
143035	i3300, i5300, BBP33	Fig. 21	B33-125-2-342YL	Yellow	22 to 16	1.2 - 2.8	3.2	1.2	0.5 +/- 0.07	1	1000	B30-R4300
143037	i3300, i5300, BBP33	Fig. 21	B33-187-2-342YL	Yellow	20 to 10	1.6 - 3.8	4.7	1.6	0.5 +/- 0.07	1	750	B30-R4300
142930	i3300, i5300, BBP33	Fig. 21	B33-250-2-342YL	Yellow	16 to 8	2.4 - 5.5	6.4	2.4	0.6 +/- 0.07	1	500	B30-R4300
142931	i3300, i5300, BBP33	Fig. 21	B33-375-2-342YL	Yellow	12 to 4	3.2 - 8.1	9.5	3.1	0.6 +/- 0.07	1	500	B30-R4300
142927	i3300, i5300, BBP33	Fig. 21	B33-500-2-342YL	Yellow	8 to 1	4.8 - 11.4	12.7	4.7	0.6 +/- 0.07	1	350	B30-R4300
142934	i3300, i5300, BBP33	Fig. 21	B33-750-2-342YL	Yellow	6 to 4/0	6.4 - 17.8	19.1	6.4	0.6 +/- 0.07	1	250	B30-R4300
143033	i3300, i5300, BBP33	Fig. 21	B33-1000-2-342YL	Yellow	2 to 0.950 dia	8.5 - 24.1	25.4	9.5	0.9 +/- 0.07	1	250	B30-R4300
142993	i3300, i5300, BBP33	Fig. 21	B33-1500-2-342YL	Yellow	n/a	12.7 - 35.6	38.1	12.7	0.9 +/- 0.07	1	150	B30-R4300
142991	i3300, i5300, BBP33	Fig. 21	B33-1500-2-342BK	Black	n/a	12.7 - 35.6	38.1	12.7	0.9 +/- 0.07	1	150	B30-R4500-SV
3:1 Shrink ratio, single-side printable, 1" sleeve width in "2-across precut" configuration (dimension A)												
133978	i3300, i5300, BBP33	Fig. 21-2	B33-94-2-342-2	White	28 to 20	0.6 - 2.0	2.4	0.6	0.6 +/- 0.07	2	2000	B30-R4300
133784	i3300, i5300, BBP33	Fig. 21-2	B33-125-2-342-2	White	22 to 16	1.2 - 2.8	3.2	1.2	0.5 +/- 0.07	2	2000	B30-R4300
142944	i3300, i5300, BBP33	Fig. 21-2	B33-187-2-342-2	White	20 to 10	1.6 - 3.8	4.7	1.6	0.5 +/- 0.07	2	1500	B30-R4300
142945	i3300, i5300, BBP33	Fig. 21-2	B33-250-2-342-2	White	16 to 8	2.4 - 5.5	6.4	2.4	0.6 +/- 0.07	2	1000	B30-R4300
142946	i3300, i5300, BBP33	Fig. 21-2	B33-375-2-342-2	White	12 to 4	3.2 - 8.1	9.5	3.1	0.6 +/- 0.07	2	1000	B30-R4300
133879	i3300, i5300, BBP33	Fig. 21-2	B33-500-2-342-2	White	8 to 1	4.8 - 11.4	12.7	3.0	0.6 +/- 0.07	2	700	B30-R4300
141658	i3300, i5300, BBP33	Fig. 21-2	B33-750-2-342-2	White	6 to 4/0	6.4 - 17.8	19.1	6.35	0.9 +/- 0.07	2	500	B30-R4300
133766	i3300, i5300, BBP33	Fig. 21-2	B33-1000-2-342-2	White	2 to 0.950 dia	8.5 - 24.1	25.4	9.5	0.9 +/- 0.07	2	500	B30-R4300
133808	i3300, i5300, BBP33	Fig. 21-2	B33-1500-2-342-2	White	n/a	12.7 - 35.6	38.1	12.7	0.9 +/- 0.07	2	150	B30-R4300
133979	i3300, i5300, BBP33	Fig. 21-2	B33-94-2-342YL-2	Yellow	28 to 20	0.6 - 2.0	2.4	0.6	0.6 +/- 0.07	2	2000	B30-R4300
133785	i3300, i5300, BBP33	Fig. 21-2	B33-125-2-342YL-2	Yellow	22 to 16	1.2 - 2.8	3.2	1.2	0.5 +/- 0.07	2	2000	B30-R4300
145570	i3300, i5300, BBP33	Fig. 21-2	B33-750-2-342YL-2	Yellow	6 to 4/0	6.4 - 17.8	19.1	6.35	0.6 +/- 0.07	2	500	B30-R4300
133880	i3300, i5300, BBP33	Fig. 21-2	B33-500-2-342YL-2	Yellow	8 to 1	4.8 - 11.4	12.7	3.0	0.6 +/- 0.07	2	700	B30-R4300
133767	i3300, i5300, BBP33	Fig. 21-2	B33-1000-2-342YL-2	Yellow	2 to 0.950 dia	8.5 - 24.1	25.4	9.5	0.9 +/- 0.07	2	500	B30-R4300
133809	i3300, i5300, BBP33	Fig. 21-2	B33-1500-2-342YL-2	Yellow	n/a	12.7 - 35.6	38.1	12.7	0.9 +/- 0.07	2	300	B30-R4300

Part No.	For Use with Printers:	Diagram	Reference	Colour	For Wire Gauge (approx.)	For Wire Diameters (mm) Min - Max.	Supplied Diameter B (mm)	Recovered Diameter (mm)	Recovered Wall Thickness (mm)	Qty per Row	Qty per Roll	Rec. ribbon
3:1 Shrink ratio, Double-side printable, 2" sleeve width (dimension A)												
143019	i3300, i5300, BBP33	Fig. 21	B33D-94-2-342	White	28 to 20	0.6 - 2.0	2.4	0.6	0.6 +/- 0.07	1	1000	B30-R4300
143021	i3300, i5300, BBP33	Fig. 21	B33D-125-2-342	White	22 to 16	1.2 - 2.8	3.2	1.2	0.5 +/- 0.07	1	1000	B30-R4300
143023	i3300, i5300, BBP33	Fig. 21	B33D-187-2-342	White	20 to 10	1.6 - 3.8	4.7	1.6	0.5 +/- 0.07	1	750	B30-R4300
143025	i3300, i5300, BBP33	Fig. 21	B33D-250-2-342	White	16 to 8	2.4 - 5.5	6.4	2.4	0.6 +/- 0.07	1	500	B30-R4300
143027	i3300, i5300, BBP33	Fig. 21	B33D-375-2-342	White	12 to 4	3.2 - 8.1	9.5	3.1	0.6 +/- 0.07	1	500	B30-R4300
143029	i3300, i5300, BBP33	Fig. 21	B33D-500-2-342	White	8 to 1	4.8 - 11.4	12.7	4.7	0.6 +/- 0.07	1	350	B30-R4300
143031	i3300, i5300, BBP33	Fig. 21	B33D-750-2-342	White	6 to 4	6.4 - 17.8	19.1	6.4	0.6 +/- 0.07	1	250	B30-R4300
142937	i3300, i5300, BBP33	Fig. 21	B33D-1000-2-342	White	2 to 0.950 dia	8.5 - 24.1	25.4	9.5	0.9 +/- 0.07	1	250	B30-R4300
142989	i3300, i5300, BBP33	Fig. 21	B33D-1500-2-342	White	n/a	12.7 - 35.6	38.1	12.7	0.9 +/- 0.07	1	150	B30-R4300
143020	i3300, i5300, BBP33	Fig. 21	B33D-94-2-342YL	Yellow	28 to 20	0.6 - 2.0	2.4	0.6	0.6 +/- 0.07	1	1000	B30-R4300
143022	i3300, i5300, BBP33	Fig. 21	B33D-125-2-342YL	Yellow	22 to 16	1.2 - 2.8	3.2	1.2	0.5 +/- 0.07	1	1000	B30-R4300
143024	i3300, i5300, BBP33	Fig. 21	B33D-187-2-342YL	Yellow	20 to 10	1.6 - 3.8	4.7	1.6	0.5 +/- 0.07	1	750	B30-R4300
143026	i3300, i5300, BBP33	Fig. 21	B33D-250-2-342YL	Yellow	16 to 8	2.4 - 5.5	6.4	2.4	0.6 +/- 0.07	1	500	B30-R4300
143028	i3300, i5300, BBP33	Fig. 21	B33D-375-2-342YL	Yellow	12 to 4	3.2 - 8.1	9.5	3.1	0.6 +/- 0.07	1	500	B30-R4300
143030	i3300, i5300, BBP33	Fig. 21	B33D-500-2-342YL	Yellow	8 to 1	4.8 - 11.4	12.7	4.7	0.6 +/- 0.07	1	350	B30-R4300
142928	i3300, i5300, BBP33	Fig. 21	B33D-750-2-342YL	Yellow	6 to 4/0	6.4 - 17.8	19.1	6.4	0.6 +/- 0.07	1	250	B30-R4300
142933	i3300, i5300, BBP33	Fig. 21	B33D-1000-2-342YL	Yellow	2 to 0.950 dia	8.5 - 24.1	25.4	9.5	0.9 +/- 0.07	1	250	B30-R4300
142990	i3300, i5300, BBP33	Fig. 21	B33D-1500-2-342YL	Yellow	n/a	12.7 - 35.6	38.1	12.7	0.9 +/- 0.07	1	150	B30-R4300
142935	i3300, i5300, BBP33	Fig. 21	B33D-94-2-342BK	Black	28 to 20	0.6 - 2.0	2.4	0.6	0.6 +/- 0.07	1	1000	B30-R4500-SV
142921	i3300, i5300, BBP33	Fig. 21	B33D-125-2-342BK	Black	22 to 16	1.2 - 2.8	3.2	1.2	0.5 +/- 0.07	1	1000	B30-R4500-SV
142923	i3300, i5300, BBP33	Fig. 21	B33D-187-2-342BK	Black	20 to 10	1.6 - 3.8	4.7	1.6	0.5 +/- 0.07	1	750	B30-R4500-SV
142924	i3300, i5300, BBP33	Fig. 21	B33D-250-2-342BK	Black	16 to 8	2.4 - 5.5	6.4	2.4	0.6 +/- 0.07	1	500	B30-R4500-SV
142922	i3300, i5300, BBP33	Fig. 21	B33D-375-2-342BK	Black	12 to 4	3.2 - 8.1	9.5	3.1	0.6 +/- 0.07	1	500	B30-R4500-SV
142925	i3300, i5300, BBP33	Fig. 21	B33D-500-2-342BK	Black	8 to 1	4.8 - 11.4	12.7	4.7	0.6 +/- 0.07	1	350	B30-R4500-SV
142929	i3300, i5300, BBP33	Fig. 21	B33D-750-2-342BK	Black	6 to 4/0	6.4 - 17.8	19.1	6.4	0.6 +/- 0.07	1	250	B30-R4500-SV
142869	i3300, i5300, BBP33	Fig. 21	B33D-1000-2-342BK	Black	2 to 0.950 dia	8.5 - 24.1	25.4	9.5	0.9 +/- 0.07	1	250	B30-R4500-SV
142988	i3300, i5300, BBP33	Fig. 21	B33D-1500-2-342BK	Black	n/a	12.7 - 35.6	38.1	12.7	0.9 +/- 0.07	1	150	B30-R4500-SV

2-pass double-side sleeve printing with no wasted sleeves using i5300 printer and Brady Workstation

- Use double-sided sleeve module in Brady workstation
- Change text content, size and even rotation for each side!
- See a demo at BradyID.com.au



PermaSleeve® Fluid-Resistant Heat-Shrink Sleeves (B-344)

- Designed for labelling wires with exposure to fuels, lubricants and harsh chemicals such as in the installation of hydrogen fuel cells in aerospace
- Resistant to harsh chemicals including JP8 Jet Fuel, Skydrol® and DOT 3 brake fluid
- Meets SAE-AS23053/5
- Tested per: ASTM E162, ASTM E662, MIL-STD-202G





Figure 21



Part No.	For Use with Printers:	Diagram	Reference	Colour	For Wire Gauge (approx.)	For Wire Diameters (mm) Min - Max.	Supplied Diameter B (mm)	Recovered Diameter (mm)	Recovered Wall Thickness (mm)	Qty per Row	Qty per Roll	Rec. ribbon
3:1 Shrink ratio, Double-side printable, 2" sleeve width (dimension A)												
118999	i3300, i5300, BBP33	Fig. 21	B33D-94-2-344	White	28 to 20	0.6 - 2.0	2.4	0.6	0.6 +/- 0.1	1	1000	B30-R6600
119010	i3300, i5300, BBP33	Fig. 21	B33D-125-2-344	White	22 to 16	1.2 - 2.8	3.1	1.2	0.5 +/- 0.1	1	1000	B30-R6600
119021	i3300, i5300, BBP33	Fig. 21	B33D-187-2-344	White	20 to 10	1.6 - 3.81	4.8	1.6	0.5 +/- 0.1	1	750	B30-R6600
119032	i3300, i5300, BBP33	Fig. 21	B33D-250-2-344	White	16 to 8	2.4 - 5.5	6.35	2.4	0.6 +/- 0.1	1	500	B30-R6600
119043	i3300, i5300, BBP33	Fig. 21	B33D-375-2-344	White	12 to 4	3.2 - 8.1	9.5	3.2	0.6 +/- 0.1	1	500	B30-R6600
119054	i3300, i5300, BBP33	Fig. 21	B33D-500-2-344	White	8 to 1	4.8 - 11.4	12.7	3.0	0.6 +/- 0.1	1	350	B30-R6600
119065	i3300, i5300, BBP33	Fig. 21	B33D-750-2-344	White	6 to 4/0	6.4 - 17.8	19.05	6.35	0.6 +/- 0.1	1	250	B30-R6600
139829	i3300, i5300, BBP33	Fig. 21	B33D-1000-2-344	White	2 to 0.950 dia	8.5 - 24.1	25.4	9.5	0.9 +/- 0.1	1	250	B30-R6600
119087	i3300, i5300, BBP33	Fig. 21	B33D-1500-2-344	White	n/a	12.7 - 35.6	38.1	12.7	0.9 +/- 0.1	1	150	B30-R6600
119000	i3300, i5300, BBP33	Fig. 21	B33D-94-2-344YL	Yellow	28 to 20	0.6 - 2.0	2.4	0.6	0.6 +/- 0.1	1	1000	B30-R6600
119011	i3300, i5300, BBP33	Fig. 21	B33D-125-2-344YL	Yellow	22 to 16	1.2 - 2.8	3.1	1.2	0.5 +/- 0.1	1	1000	B30-R6600
119022	i3300, i5300, BBP33	Fig. 21	B33D-187-2-344YL	Yellow	20 to 10	1.6 - 3.81	4.8	1.6	0.5 +/- 0.1	1	750	B30-R6600
119033	i3300, i5300, BBP33	Fig. 21	B33D-250-2-344YL	Yellow	16 to 8	2.4 - 5.5	6.35	2.4	0.6 +/- 0.1	1	500	B30-R6600
119044	i3300, i5300, BBP33	Fig. 21	B33D-375-2-344YL	Yellow	12 to 4	3.2 - 8.1	9.5	3.2	0.6 +/- 0.1	1	500	B30-R6600
119055	i3300, i5300, BBP33	Fig. 21	B33D-500-2-344YL	Yellow	8 to 1	4.8 - 11.4	12.7	3.0	0.6 +/- 0.1	1	350	B30-R6600
119066	i3300, i5300, BBP33	Fig. 21	B33D-750-2-344YL	Yellow	6 to 4/0	6.4 - 17.8	19.05	6.35	0.6 +/- 0.1	1	250	B30-R6600
119077	i3300, i5300, BBP33	Fig. 21	B33D-1000-2-344YL	Yellow	2 to 0.950 dia	8.5 - 24.1	25.4	9.5	0.9 +/- 0.1	1	250	B30-R6600
119088	i3300, i5300, BBP33	Fig. 21	B33D-1500-2-344YL	Yellow	n/a	12.7 - 35.6	38.1	12.7	0.9 +/- 0.1	1	150	B30-R6600
119005	i3300, i5300, BBP33	Fig. 21	B33D-94-2-344BK	Black	28 to 20	0.6 - 2.0	2.4	0.6	0.6 +/- 0.1	1	1000	B30-R6700-WT
119016	i3300, i5300, BBP33	Fig. 21	B33D-125-2-344BK	Black	22 to 16	1.2 - 2.8	3.1	1.2	0.5 +/- 0.1	1	1000	B30-R6700-WT
119027	i3300, i5300, BBP33	Fig. 21	B33D-187-2-344BK	Black	20 to 10	1.6 - 3.81	4.8	1.6	0.5 +/- 0.1	1	750	B30-R6700-WT
119038	i3300, i5300, BBP33	Fig. 21	B33D-250-2-344BK	Black	16 to 8	2.4 - 5.5	6.35	2.4	0.6 +/- 0.1	1	500	B30-R6700-WT
119049	i3300, i5300, BBP33	Fig. 21	B33D-375-2-344BK	Black	12 to 4	3.2 - 8.1	9.5	3.2	0.6 +/- 0.1	1	500	B30-R6700-WT
119060	i3300, i5300, BBP33	Fig. 21	B33D-500-2-344BK	Black	8 to 1	4.8 - 11.4	12.7	3.0	0.6 +/- 0.1	1	350	B30-R6700-WT
119071	i3300, i5300, BBP33	Fig. 21	B33D-750-2-344BK	Black	6 to 4/0	6.4 - 17.8	19.05	6.35	0.6 +/- 0.1	1	250	B30-R6700-WT
119082	i3300, i5300, BBP33	Fig. 21	B33D-1000-2-344BK	Black	2 to 0.950 dia	8.5 - 24.1	25.4	9.5	0.9 +/- 0.1	1	250	B30-R6700-WT
119093	i3300, i5300, BBP33	Fig. 21	B33D-1500-2-344BK	Black	n/a	12.7 - 35.6	38.1	12.7	0.9 +/- 0.1	1	150	B30-R6700-WT

PermaSleeve® High-Temp Heat-Shrink Sleeves (B-345)

- A 2:1 shrink ratio wire marker sleeve specifically designed for high-temperature and low-vacuum outgassing applications
- Made from irradiated high-temp polyvinylidene fluoride (PVDF) heat-shrink tubing
- Fade-resistant and flame-retardant
- Meets NASA SP-R-0022A Outgassing Performance
- Meets SAE-AS-81531
- Tested per ASTM E162, ASTM E662 and MIL-STD-202




Figure 21



Part No.	For Use with Printers:	Diagram	Reference	Colour	For Wire Gauge (approx.)	For Wire Diameters (mm) Min - Max.	Supplied Diameter B (mm)	Recovered Diameter (mm)	Recovered Wall Thickness (mm)	Qty per Row	Qty per Roll	Rec. ribbon
3:1 Shrink ratio double-side printable, 2 in. sleeve width (dimension A)												
142987	i3300, i5300, BBP33	Fig. 21	B33D-94-2-345	White	26 to 20	0.8 - 2.0	2.4	0.8	0.4 +/- 0.07	1	1000	B30-R6000
142986	i3300, i5300, BBP33	Fig. 21	B33D-94-2-345BK	Black	26 to 20	0.8 - 2.0	2.4	0.8	0.4 +/- 0.07	1	1000	B30-R4400-WT
2:1 Shrink ratio double-side printable, 2 in. sleeve width (dimension A)												
142973	i3300, i5300, BBP33	Fig. 21	B33D-125-2-345	White	20 to 16	1.6 - 2.8	3.2	1.6	0.4 +/- 0.07	1	1000	B30-R6000
142977	i3300, i5300, BBP33	Fig. 21	B33D-187-2-345	White	16 to 10	2.4 - 3.8	4.7	2.4	0.4 +/- 0.07	1	750	B30-R6000
142979	i3300, i5300, BBP33	Fig. 21	B33D-250-2-345	White	12 to 8	3.2 - 5.5	6.4	3.2	0.4 +/- 0.07	1	500	B30-R6000
142981	i3300, i5300, BBP33	Fig. 21	B33D-375-2-345	White	8 to 4	3.2 - 8.1	9.5	4.7	0.4 +/- 0.07	1	500	B30-R6000
142983	i3300, i5300, BBP33	Fig. 21	B33D-500-2-345	White	6 to 1	6.4 - 11.4	12.7	6.4	0.4 +/- 0.07	1	350	B30-R6000
142985	i3300, i5300, BBP33	Fig. 21	B33D-750-2-345	White	2 to 4/0	9.5 - 17.8	19.1	9.5	0.4 +/- 0.07	1	250	B30-R6000
142971	i3300, i5300, BBP33	Fig. 21	B33D-1000-2-345	White	2/0 to 0.950 dia	11.4 - 24.1	25.4	12.7	0.4 +/- 0.1	1	250	B30-R6000
142975	i3300, i5300, BBP33	Fig. 21	B33D-1500-2-345	White	N/A	19.1 - 35.6	38.1	19.1	0.6 +/- 0.1	1	150	B30-R6000
142972	i3300, i5300, BBP33	Fig. 21	B33D-125-2-345BK	Black	20 to 16	1.6 - 2.8	3.2	1.6	0.4 +/- 0.07	1	1000	B30-R4400-WT
142976	i3300, i5300, BBP33	Fig. 21	B33D-187-2-345BK	Black	16 to 10	2.4 - 3.8	4.7	2.4	0.4 +/- 0.07	1	750	B30-R4400-WT
142978	i3300, i5300, BBP33	Fig. 21	B33D-250-2-345BK	Black	12 to 8	3.2 - 5.5	6.4	3.2	0.4 +/- 0.07	1	500	B30-R4400-WT
142980	i3300, i5300, BBP33	Fig. 21	B33D-375-2-345BK	Black	8 to 4	3.2 - 8.1	9.5	4.7	0.4 +/- 0.07	1	500	B30-R4400-WT
142982	i3300, i5300, BBP33	Fig. 21	B33D-500-2-345BK	Black	6 to 1	6.4 - 11.4	12.7	6.4	0.4 +/- 0.07	1	350	B30-R4400-WT
142984	i3300, i5300, BBP33	Fig. 21	B33D-750-2-345BK	Black	3 to 4/0	9.5 - 17.8	19.1	9.5	0.4 +/- 0.07	1	250	B30-R4400-WT
142970	i3300, i5300, BBP33	Fig. 21	B33D-1000-2-345BK	Black	2/0 to 0.950 dia	11.4 - 24.1	25.4	12.7	0.4 +/- 0.1	1	250	B30-R4400-WT
142974	i3300, i5300, BBP33	Fig. 21	B33D-1500-2-345BK	Black	N/A	19.1 - 35.6	38.1	19.1	0.6 +/- 0.1	1	150	B30-R4400-WT

PermaSleeve® Low Smoke Zero Halogen Heat-Shrink Sleeves (B-7641)

- Low halogen wire marking sleeves offer outstanding fire safety properties and minimal smoke emission
- Meets SAE-AS-81531 and EN45545-2
- Tested per ASTM E162, ASTM E662 and MIL-STD-202




Figure 21



Part No.	For Use with Printers:	Diagram	Reference	Colour	For Wire Gauge (approx.)	For Wire Diameters (mm) Min - Max.	Supplied Diameter B (mm)	Recovered Diameter (mm)	Recovered Wall Thickness (mm)	Qty per Row	Qty per Roll	Rec. ribbon
2:1 Shrink ratio double-side printable, 2 in. sleeve width (dimension A)												
140928	i3300, i5300, BBP33	Fig. 21	B33D-94-2-7641	White	24 to 20	1.2 - 2.0	2.4	1.2	0.5 +/- 0.07	1	500	B30-R6000
140929	i3300, i5300, BBP33	Fig. 21	B33D-125-2-7641	White	20 to 16	1.6 - 2.8	3.2	1.6	0.5 +/- 0.07	1	500	B30-R6000
140930	i3300, i5300, BBP33	Fig. 21	B33D-187-2-7641	White	16 to 10	2.4 - 3.8	4.8	2.4	0.5 +/- 0.07	1	450	B30-R6000
140931	i3300, i5300, BBP33	Fig. 21	B33D-250-2-7641	White	12 to 8	3.2 - 5.5	6.4	3.2	0.6 +/- 0.07	1	400	B30-R6000
140932	i3300, i5300, BBP33	Fig. 21	B33D-375-2-7641	White	8 to 4	4.8 - 8.1	9.5	4.8	0.6 +/- 0.07	1	250	B30-R6000
140933	i3300, i5300, BBP33	Fig. 21	B33D-500-2-7641	White	6 to 1	6.4 - 11.4	12.7	6.4	0.6 +/- 0.07	1	225	B30-R6000
140934	i3300, i5300, BBP33	Fig. 21	B33D-750-2-7641	White	2 to 4/0	9.5 - 17.8	19.1	9.5	0.8 +/- 0.07	1	150	B30-R6000
140935	i3300, i5300, BBP33	Fig. 21	B33D-1000-2-7641	White	2/0 to 0.950 dia	11.4 - 24.1	25.4	12.7	0.9 +/- 0.1	1	150	B30-R6000
140936	i3300, i5300, BBP33	Fig. 21	B33D-1500-2-7641	White	N/A	19.1 - 35.6	38.1	19.1	1.0 +/- 0.2	1	50	B30-R6000
140919	i3300, i5300, BBP33	Fig. 21	B33D-94-2-7641Y	Yellow	24 to 20	1.2 - 2.0	2.4	1.2	0.5 +/- 0.07	1	500	B30-R6000
140920	i3300, i5300, BBP33	Fig. 21	B33D-125-2-7641Y	Yellow	20 to 16	1.6 - 2.8	3.2	1.6	0.5 +/- 0.07	1	500	B30-R6000
140921	i3300, i5300, BBP33	Fig. 21	B33D-187-2-7641Y	Yellow	16 to 10	2.4 - 3.8	4.8	2.4	0.5 +/- 0.07	1	450	B30-R6000
140922	i3300, i5300, BBP33	Fig. 21	B33D-250-2-7641Y	Yellow	12 to 8	3.2 - 5.5	6.4	3.2	0.6 +/- 0.07	1	450	B30-R6000
140923	i3300, i5300, BBP33	Fig. 21	B33D-375-2-7641Y	Yellow	8 to 4	4.8 - 8.1	9.5	4.8	0.6 +/- 0.07	1	250	B30-R6000
140924	i3300, i5300, BBP33	Fig. 21	B33D-500-2-7641Y	Yellow	6 to 1	6.4 - 11.4	12.7	6.4	0.6 +/- 0.07	1	225	B30-R6000
140925	i3300, i5300, BBP33	Fig. 21	B33D-750-2-7641Y	Yellow	2 to 4/0	9.5 - 17.8	19.1	9.5	0.8 +/- 0.07	1	150	B30-R6000
140926	i3300, i5300, BBP33	Fig. 21	B33D-1000-2-7641Y	Yellow	2/0 to 0.950 dia	11.4 - 24.1	25.4	12.7	0.9 +/- 0.1	1	150	B30-R6000
140927	i3300, i5300, BBP33	Fig. 21	B33D-1500-2-7641Y	Yellow	N/A	19.1 - 35.6	38.1	19.1	1.0 +/- 0.2	1	50	B30-R6000

PermaSleeve® 2:1 Heat-Shrink Sleeves

(B-7642)

- Flame retardant and high-temp rated but not as high-temp as B-345 PermaSleeve
- Meets SAE-AS23053/5 and SAE-AS-81531
- Tested per ASTM E162, ASTM E662 and MIL-STD-202





Figure 21



Part No.	For Use with Printers:	Diagram	Reference	Colour	For Wire Gauge (approx.)	For Wire Diameters (mm) Min - Max.	Supplied Diameter B (mm)	Recovered Diameter (mm)	Recovered Wall Thickness (mm)	Qty per Row	Qty per Roll	Rec. ribbon
2:1 Shrink ratio single-side printable, 2 in. sleeve width (dimension A)												
142897	i3300, i5300, BBP33	Fig. 21	B33-94-2-7642	White	24 to 20	1.2 - 2.0	2.4	1.2	0.5 +/- 0.07	1	500	B30-R4300
142898	i3300, i5300, BBP33	Fig. 21	B33-125-2-7642	White	20 to 16	1.6 - 2.8	3.2	1.6	0.5 +/- 0.07	1	500	B30-R4300
142899	i3300, i5300, BBP33	Fig. 21	B33-187-2-7642	White	16 to 10	2.4 - 3.8	4.8	2.4	0.5 +/- 0.07	1	450	B30-R4300
142900	i3300, i5300, BBP33	Fig. 21	B33-250-2-7642	White	12 to 8	3.2 - 5.5	6.4	3.2	0.6 +/- 0.07	1	400	B30-R4300
142901	i3300, i5300, BBP33	Fig. 21	B33-375-2-7642	White	8 to 4	4.8 - 8.1	9.5	4.8	0.6 +/- 0.07	1	250	B30-R4300
142902	i3300, i5300, BBP33	Fig. 21	B33-500-2-7642	White	6 to 1	6.4 - 11.4	12.7	6.4	0.6 +/- 0.07	1	225	B30-R4300
142903	i3300, i5300, BBP33	Fig. 21	B33-750-2-7642	White	2 to 4/0	9.5 - 17.8	19.1	9.5	0.8 +/- 0.07	1	150	B30-R4300
142904	i3300, i5300, BBP33	Fig. 21	B33-1000-2-7642	White	2/0 to 0.950 dia	11.4 - 24.1	25.4	12.7	0.9 +/- 0.1	1	150	B30-R4300
142905	i3300, i5300, BBP33	Fig. 21	B33-1500-2-7642	White	N/A	19.1 - 35.6	38.1	19.1	1.0 +/- 0.2	1	50	B30-R4300
142906	i3300, i5300, BBP33	Fig. 21	B33-2000-2-7642	White	N/A	25.4 - 48.3	50.8	25.4	1.1 +/- 0.2	1	50	B30-R4300
2:1 Shrink ratio, Double-side printable, 2 in. sleeve width (dimension A)												
142907	i3300, i5300, BBP33	Fig. 21	B33D-94-2-7642	White	24 to 20	1.2 - 2.0	2.4	1.2	0.5 +/- 0.07	1	500	B30-R4300
142908	i3300, i5300, BBP33	Fig. 21	B33D-125-2-7642	White	20 to 16	1.6 - 2.8	3.2	1.6	0.5 +/- 0.07	1	500	B30-R4300
142909	i3300, i5300, BBP33	Fig. 21	B33D-187-2-7642	White	16 to 10	2.4 - 3.8	4.8	2.4	0.5 +/- 0.07	1	450	B30-R4300
142910	i3300, i5300, BBP33	Fig. 21	B33D-250-2-7642	White	12 to 8	3.2 - 5.5	6.4	3.2	0.6 +/- 0.07	1	400	B30-R4300
142911	i3300, i5300, BBP33	Fig. 21	B33D-375-2-7642	White	8 to 4	4.8 - 8.1	9.5	4.8	0.6 +/- 0.07	1	250	B30-R4300
142912	i3300, i5300, BBP33	Fig. 21	B33D-500-2-7642	White	6 to 1	6.4 - 11.4	12.7	6.4	0.6 +/- 0.07	1	225	B30-R4300
142913	i3300, i5300, BBP33	Fig. 21	B33D-750-2-7642	White	2 to 4/0	9.5 - 17.8	19.1	9.5	0.8 +/- 0.07	1	150	B30-R4300
142914	i3300, i5300, BBP33	Fig. 21	B33D-1000-2-7642	White	2/0 to 0.950 dia	11.4 - 24.1	25.4	12.7	0.9 +/- 0.1	1	150	B30-R4300
142915	i3300, i5300, BBP33	Fig. 21	B33D-1500-2-7642	White	N/A	19.1 - 35.6	38.1	19.1	1.0 +/- 0.2	1	50	B30-R4300
142916	i3300, i5300, BBP33	Fig. 21	B33D-2000-2-7642	White	N/A	25.4 - 48.3	50.8	25.4	1.1 +/- 0.2	1	50	B30-R4300


QuickSleeve Handheld Sleeve Applicator

The QuickSleeve Handheld Sleeve Applicator is an intuitive multi-tool designed to help you quickly apply sleeves on to wires in three simple steps – just pick, slip and apply. This tool includes:

- Four specially designed slanted tubes sized for sleeve sizes 2.38mm, 3.17mm, 4.75mm and 6.35mm
- Built-in LED flashlight for use in low-lit conditions
- Terminal block sized screwdriver



Part No.	Reference	Description	Qty.
149474	QS	QuickSleeve multi-tool	1 Tool



Pick

Slip

Apply

Zero-Halogen Polyurethane Cable Markers (B-7643)

- Thermoplastic polyether polyurethane is a zero-halogen high-density, thermoplastic cable marker
- The non-adhesive tag is pre-cut with 4 holes and tag is fastened to cable or wire harness bundle with cable ties
- Meets the requirements of a halogen-free material per IEC 61249-2-21 (2003-11)
- Excellent chemical, oil and water resistance




Figure 86



Part No.	For Use with Printers:	Diagram	Reference	Colour	Label width A (mm)	Label height B (mm)	Labels per row	Labels per roll	Rec. ribbon
197481	i3300, i5300	Fig. 86	B33-60X10-7643-WT	White	60	9.91	1	1000	B30-R6000
197488	i3300, i5300	Fig. 86	B33-75X10-7643-WT	White	75	9.91	1	750	B30-R6000
197495	i3300, i5300	Fig. 86	B33-75X15-7643-WT	White	75	14.9	1	500	B30-R6000
197503	i3300, i5300	Fig. 86	B33-75X25-7643-WT	White	75	24.9	1	250	B30-R6000
197482	i3300, i5300	Fig. 86	B33-60X10-7643-YL	Yellow	60	9.91	1	1000	B30-R6000
197489	i3300, i5300	Fig. 86	B33-75X10-7643-YL	Yellow	75	9.91	1	750	B30-R6000
197496	i3300, i5300	Fig. 86	B33-75X15-7643-YL	Yellow	75	14.9	1	500	B30-R6000
197504	i3300, i5300	Fig. 86	B33-75X25-7643-YL	Yellow	75	24.9	1	250	B30-R6000

Pre-Printed Pre-Cut Blank Sign Headers (B-595)

- Allows printer to create multicolour signs fast in a single print pass
- Headers meet NFPA 70E, OSHA 1910.145 and ASME / ANSI Z535 standards
- Indoor / outdoor grade material conforms to rough, highly textured and difficult-to-adhere-to surfaces




Figure 70a

Part No.	Diagram	Reference	B#	Material	Header	Label Height A (mm)	Label Width B (mm)	Labels Per Row	Labels Per Roll	Rec. Ribbon
142191	Fig. 70a	B30-241-595-OSHADA	B-595	Vinyl		57.5	76.2	1	300	B30-R10000
142190	Fig. 70a	B30-25-595-OSHADA	B-595	Vinyl		101.6	152.4	1	175	B30-R10000
142193	Fig. 70a	B30-241-595-OSHACA	B-595	Vinyl		57.5	76.2	1	300	B30-R10000
142192	Fig. 70a	B30-25-595-OSHACA	B-595	Vinyl		101.6	152.4	1	175	B30-R10000
872946	Fig. 70a	B30-241-595-ANSIWA	B-595	Vinyl		57.5	76.2	1	300	B30-R10000
872948	Fig. 70a	B30-25-595-ANSIWA	B-595	Vinyl		101.6	152.4	1	175	B30-R10000
142189	Fig. 70a	B30-241-595-ANSINO	B-595	Vinyl		57.5	76.2	1	300	B30-R10000
142188	Fig. 70a	B30-25-595-ANSINO	B-595	Vinyl		101.6	152.4	1	175	B30-R10000
142196	Fig. 70a	B30-242-595-BLNKWT	B-595	Vinyl		28.6	69.9	300	B30-R10000	B30-R10000
142195	Fig. 70a	B30-241-595-BLNKWT	B-595	Vinyl		57.5	76.2	300	B30-R10000	B30-R10000
142197	Fig. 70a	B30-219-595-BLNKWT	B-595	Vinyl		57.5	95.3	250	B30-R10000	B30-R10000
142194	Fig. 70a	B30-25-595-BLNKWT	B-595	Vinyl		101.6	152.4	175	B30-R10000	B30-R10000
142199	Fig. 70a	B30-241-595-BLNKYL	B-595	Vinyl		57.5	76.2	1	300	B30-R10000
142198	Fig. 70a	B30-25-595-BLNKYL	B-595	Vinyl		101.6	152.4	1	175	B30-R10000

Non-Adhesive Tags (B-551)

- Non-adhesive semi-rigid card stock in pre-cut and continuous styles
- Tags are pre-cut with hole or easy to hole punch, are micro-perforated between tags to separate cleanly and some feature chamfered corners
- Snap-in plastic grommets available for extra strength around mounting hole (Reference 20596, 100/bag)




Figure 3b




Figure 69



Part No.	Diagram	Reference	B#	Header	Tag Width A (mm)	Tag Height B (mm)	Tags Per Row	Tags Per Roll	Rec. Ribbon
142223	Fig. 69	B30-255-551-OSHADA	B-551		82.6	146.1	1	100	B30-R10000
142224	Fig. 69	B30-255-551-ANSICA	B-551		82.6	146.1	1	100	B30-R10000
142226	Fig. 69	B30-255-551-WHT	B-551		82.6	146.1	1	100	B30-R10000
118013	Fig. 3b	B30C-2500-551-WT	B-551		63.5	15.2 m	1 roll (cont.)		B30-R10000
118012	Fig. 3b	B30C-3250-551-WT	B-551		82.6	15.2 m	1 roll (cont.)		B30-R10000
118011	Fig. 3b	B30C-4250-551-WT	B-551		107.9	15.2 m	1 roll (cont.)		B30-R10000

All part numbers above are compatible with BradyPrinter i3300 and BBP®33. Parts may also be compatible with BradyPrinter S3000, BradyPrinter S3100, BBP®30, BBP®31, BBP®35 and BBP®37 printers. Visit BradyID.com.au to confirm compatibility.

All-Weather Vinyl (B-595)

- For general facility and safety identification
- Durable, low-shrink vinyl with our most aggressive adhesive
- Conforms to irregular, curved, rough and highly textured surfaces (painted cinder blocks, uneven wood, textured plastics, paper-jacketed pipes, powder-coated surfaces)
- Adheres to difficult low-surface energy items (PVC piping, blow-molded equipment cases, ABS plastics, recycled plastics)





Figure 3



Part No.	For Use with Printers:	Diagram	Reference	Colour	Label Width A (mm)	Roll Length B (m)	Labels Per Roll	Rec. Ribbon
142031	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-595-WT	White	12.7	30.5	1 roll (cont.)	B30-R10000
142030	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-595-WT	White	28.6	30.5	1 roll (cont.)	B30-R10000
142029	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-595-WT	White	57.5	30.5	1 roll (cont.)	B30-R10000
142028	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-3000-595-WT	White	76.2	30.5	1 roll (cont.)	B30-R10000
142027	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-595-WT	White	101.6	30.5	1 roll (cont.)	B30-R10000
142036	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-595-YL	Yellow	12.7	30.5	1 roll (cont.)	B30-R10000
142035	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-595-YL	Yellow	28.6	30.5	1 roll (cont.)	B30-R10000
142034	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-595-YL	Yellow	57.5	30.5	1 roll (cont.)	B30-R10000
142033	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-3000-595-YL	Yellow	76.2	30.5	1 roll (cont.)	B30-R10000
142032	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-595-YL	Yellow	101.6	30.5	1 roll (cont.)	B30-R10000
142026	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-595-RD	Red	12.7	30.5	1 roll (cont.)	B30-R10000-WT
142025	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-595-RD	Red	28.6	30.5	1 roll (cont.)	B30-R10000-WT
142024	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-595-RD	Red	57.5	30.5	1 roll (cont.)	B30-R10000-WT
142023	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-595-RD	Red	101.6	30.5	1 roll (cont.)	B30-R10000-WT
141994	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-595-BL	Blue	12.7	30.5	1 roll (cont.)	B30-R10000-WT
141993	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-595-BL	Blue	28.6	30.5	1 roll (cont.)	B30-R10000-WT
141992	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-595-BL	Blue	57.5	30.5	1 roll (cont.)	B30-R10000-WT
141991	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-595-BL	Blue	101.6	30.5	1 roll (cont.)	B30-R10000-WT
142010	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-595-GN	Green	12.7	30.5	1 roll (cont.)	B30-R10000-WT
142009	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-595-GN	Green	28.6	30.5	1 roll (cont.)	B30-R10000-WT
142008	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-595-GN	Green	57.5	30.5	1 roll (cont.)	B30-R10000-WT
142007	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-595-GN	Green	101.6	30.5	1 roll (cont.)	B30-R10000-WT
142018	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-595-OR	Orange	12.7	30.5	1 roll (cont.)	B30-R10000
142017	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-595-OR	Orange	28.6	30.5	1 roll (cont.)	B30-R10000
142016	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-595-OR	Orange	57.5	30.5	1 roll (cont.)	B30-R10000
142015	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-595-OR	Orange	101.6	30.5	1 roll (cont.)	B30-R10000
141990	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-595-BK	Black	12.7	30.5	1 roll (cont.)	B30-R10000-WT
141989	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-595-BK	Black	28.6	30.5	1 roll (cont.)	B30-R10000-WT
141988	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-595-BK	Black	57.5	30.5	1 roll (cont.)	B30-R10000-WT
141987	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-595-BK	Black	101.6	30.5	1 roll (cont.)	B30-R10000-WT
141998	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-595-BR	Brown	12.7	30.5	1 roll (cont.)	B30-R10000-WT
141997	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-595-BR	Brown	28.6	30.5	1 roll (cont.)	B30-R10000-WT
141996	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-595-BR	Brown	57.5	30.5	1 roll (cont.)	B30-R10000-WT
141995	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-595-BR	Brown	101.6	30.5	1 roll (cont.)	B30-R10000-WT
142006	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-595-GD	Gold	12.7	30.5	1 roll (cont.)	B30-R10000
142005	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-595-GD	Gold	28.6	30.5	1 roll (cont.)	B30-R10000
142004	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-595-GD	Gold	57.5	30.5	1 roll (cont.)	B30-R10000
142003	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-595-GD	Gold	101.6	30.5	1 roll (cont.)	B30-R10000
142014	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-595-GY	Grey	12.7	30.5	1 roll (cont.)	B30-R10000
142013	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-595-GY	Grey	28.6	30.5	1 roll (cont.)	B30-R10000
142012	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-595-GY	Grey	57.5	30.5	1 roll (cont.)	B30-R10000
142011	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-595-GY	Grey	101.6	30.5	1 roll (cont.)	B30-R10000
142022	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-595-PL	Purple	12.7	30.5	1 roll (cont.)	B30-R10000-WT
142021	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-595-PL	Purple	28.6	30.5	1 roll (cont.)	B30-R10000-WT
142020	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-595-PL	Purple	57.5	30.5	1 roll (cont.)	B30-R10000-WT
142019	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-595-PL	Purple	101.6	30.5	1 roll (cont.)	B30-R10000-WT
142002	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-595-CL	Clear	12.7	30.5	1 roll (cont.)	B30-R10000
142001	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-595-CL	Clear	28.6	30.5	1 roll (cont.)	B30-R10000
142000	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-595-CL	Clear	57.5	30.5	1 roll (cont.)	B30-R10000
141999	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-595-CL	Clear	101.6	30.5	1 roll (cont.)	B30-R10000

U.S. Patent Nos. 5,823,689; 6,570,602. Additional Patents Pending.

Low-Halide Multi-Purpose Polyester (B-569)

- Low-halide content for labelling stainless steel pipes and surfaces.
- Adheres best to very smooth surfaces and ideal for mounting to rigid panels




Figure 3



Part No.	For Use with Printers:	Diagram	Reference	Colour	Label Width A (mm)	Roll Length B (m)	Labels Per Roll	Rec. Ribbon
117989	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-WT	White	12.7	30.5	1 roll (cont.)	B30-R10000
117988	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-WT	White	28.6	30.5	1 roll (cont.)	B30-R10000
117987	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-WT	White	57.5	30.5	1 roll (cont.)	B30-R10000
117986	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-3000-569-WT	White	76.2	30.5	1 roll (cont.)	B30-R10000
117985	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-WT	White	101.6	30.5	1 roll (cont.)	B30-R10000
117993	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-YL	Yellow	12.7	30.5	1 roll (cont.)	B30-R10000
117992	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-YL	Yellow	28.6	30.5	1 roll (cont.)	B30-R10000
117991	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-YL	Yellow	57.5	30.5	1 roll (cont.)	B30-R10000
117990	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-YL	Yellow	101.6	30.5	1 roll (cont.)	B30-R10000
117976	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-RD	Red	12.7	30.5	1 roll (cont.)	B30-R10000-WT
117975	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-RD	Red	28.6	30.5	1 roll (cont.)	B30-R10000-WT
117974	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-RD	Red	57.5	30.5	1 roll (cont.)	B30-R10000-WT
117973	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-RD	Red	101.6	30.5	1 roll (cont.)	B30-R10000-WT
117936	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-BL	Blue	12.7	30.5	1 roll (cont.)	B30-R10000-WT
117935	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-BL	Blue	28.6	30.5	1 roll (cont.)	B30-R10000-WT
117934	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-BL	Blue	57.5	30.5	1 roll (cont.)	B30-R10000-WT
117933	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-BL	Blue	101.6	30.5	1 roll (cont.)	B30-R10000-WT
117956	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-LB	Light Blue	12.7	30.5	1 roll (cont.)	B30-R10000
117955	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-LB	Light Blue	28.6	30.5	1 roll (cont.)	B30-R10000
117954	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-LB	Light Blue	57.5	30.5	1 roll (cont.)	B30-R10000
117953	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-LB	Light Blue	101.6	30.5	1 roll (cont.)	B30-R10000
117980	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-SB	Sky Blue	12.7	30.5	1 roll (cont.)	B30-R10000
117979	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-SB	Sky Blue	28.6	30.5	1 roll (cont.)	B30-R10000
117978	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-SB	Sky Blue	57.5	30.5	1 roll (cont.)	B30-R10000
117977	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-SB	Sky Blue	101.6	30.5	1 roll (cont.)	B30-R10000
117948	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-GN	Green	12.7	30.5	1 roll (cont.)	B30-R10000-WT
117947	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-GN	Green	28.6	30.5	1 roll (cont.)	B30-R10000-WT
117946	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-GN	Green	57.5	30.5	1 roll (cont.)	B30-R10000-WT
117945	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-GN	Green	101.6	30.5	1 roll (cont.)	B30-R10000-WT
117964	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-OR	Orange	12.7	30.5	1 roll (cont.)	B30-R10000
117963	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-OR	Orange	28.6	30.5	1 roll (cont.)	B30-R10000
117962	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-OR	Orange	57.5	30.5	1 roll (cont.)	B30-R10000
117961	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-OR	Orange	101.6	30.5	1 roll (cont.)	B30-R10000
117932	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-BK	Black	12.7	30.5	1 roll (cont.)	B30-R10000-WT
117931	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-BK	Black	28.6	30.5	1 roll (cont.)	B30-R10000-WT
117930	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-BK	Black	57.5	30.5	1 roll (cont.)	B30-R10000-WT
117929	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-BK	Black	101.6	30.5	1 roll (cont.)	B30-R10000-WT
117940	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-BR	Brown	12.7	30.5	1 roll (cont.)	B30-R10000-WT
117939	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-BR	Brown	28.6	30.5	1 roll (cont.)	B30-R10000-WT
117938	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-BR	Brown	57.5	30.5	1 roll (cont.)	B30-R10000-WT
117937	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-BR	Brown	101.6	30.5	1 roll (cont.)	B30-R10000-WT
117960	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-OC	Ochre	12.7	30.5	1 roll (cont.)	B30-R10000
117959	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-OC	Ochre	28.6	30.5	1 roll (cont.)	B30-R10000
117958	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-OC	Ochre	57.5	30.5	1 roll (cont.)	B30-R10000
117957	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-OC	Ochre	101.6	30.5	1 roll (cont.)	B30-R10000
117984	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-TN	Tan	12.7	30.5	1 roll (cont.)	B30-R10000
117983	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-TN	Tan	28.6	30.5	1 roll (cont.)	B30-R10000
117982	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-TN	Tan	57.5	30.5	1 roll (cont.)	B30-R10000
117981	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-TN	Tan	101.6	30.5	1 roll (cont.)	B30-R10000
117952	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-GY	Grey	12.7	30.5	1 roll (cont.)	B30-R10000
117951	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-GY	Grey	28.6	30.5	1 roll (cont.)	B30-R10000
117950	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-GY	Grey	57.5	30.5	1 roll (cont.)	B30-R10000
117949	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-GY	Grey	101.6	30.5	1 roll (cont.)	B30-R10000
117972	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-PL	Purple	12.7	30.5	1 roll (cont.)	B30-R10000-WT
117971	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-PL	Purple	28.6	30.5	1 roll (cont.)	B30-R10000-WT
117970	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-PL	Purple	57.5	30.5	1 roll (cont.)	B30-R10000-WT
117969	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-PL	Purple	101.6	30.5	1 roll (cont.)	B30-R10000-WT
117968	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-PK	Pink	12.7	30.5	1 roll (cont.)	B30-R10000
117967	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-PK	Pink	28.6	30.5	1 roll (cont.)	B30-R10000
117966	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-PK	Pink	57.5	30.5	1 roll (cont.)	B30-R10000
117965	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-PK	Pink	101.6	30.5	1 roll (cont.)	B30-R10000
117944	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-569-CL	Clear	12.7	30.5	1 roll (cont.)	B30-R10000
117943	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-569-CL	Clear	28.6	30.5	1 roll (cont.)	B30-R10000
117942	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-569-CL	Clear	57.5	30.5	1 roll (cont.)	B30-R10000
117941	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-569-CL	Clear	101.6	30.5	1 roll (cont.)	B30-R10000

ToughWash® Washdown Resistant Labels

(B-854, B-855)

- Withstands high pressure, heat, harsh chemicals and numerous washdown cycles
- Legible and long-lasting for even the toughest washdown cycles
- Ideal for use in the food and beverage industry
- B-854 offers metal detectable layer to allow detection in food stream




Figure 3




Figure 73



Part No.	Diagram	Reference	B#	Colour/ Header	Label Width A (mm)	Length B (mm)	Labels Per Roll	Rec. Ribbon
ToughWash Metal Detectable Material (B-854):								
133119	Fig. 3	B30C-4000-854-YL	B-854		101.06	15.2 m	1 roll (cont.)	B30-R6000
133120	Fig. 3	B30C-4000-854-WT	B-854		101.06	15.2 m	1 roll (cont.)	B30-R6000
139804	Fig. 73	B30-25-854-OSHADA	B-854		101.06	158.8	100	B30-R6000
133123	Fig. 73	B30-25-854-ANSIWA	B-854		101.06	158.8	100	B30-R6000
133125	Fig. 73	B30-25-854-ANSICA	B-854		101.06	158.8	100	B30-R6000
ToughWash Material (B-855):								
133146	Fig. 3	B30C-1125-855-YL	B-855		28.6	15.2 m	1 roll (cont.)	B30-R6000
133142	Fig. 3	B30C-2250-855-YL	B-855		57.5	15.2 m	1 roll (cont.)	B30-R6000
133144	Fig. 3	B30C-4000-855-YL	B-855		101.06	15.2 m	1 roll (cont.)	B30-R6000
133147	Fig. 3	B30C-1125-855-WT	B-855		28.6	15.2 m	1 roll (cont.)	B30-R6000
133143	Fig. 3	B30C-2250-855-WT	B-855		57.5	15.2 m	1 roll (cont.)	B30-R6000
133145	Fig. 3	B30C-4000-855-WT	B-855		101.06	15.2 m	1 roll (cont.)	B30-R6000
139803	Fig. 73	B30-25-855-OSHADA	B-855		101.06	158.8	100	B30-R6000
133148	Fig. 73	B30-25-855-ANSIWA	B-855		101.06	158.8	100	B30-R6000
133150	Fig. 73	B30-25-855-ANSICA	B-855		101.06	158.8	100	B30-R6000

All part numbers above are compatible with BradyPrinter i3300, i5300, S3000, S3100, and BBP30, 31, 33, 35, 37 models. Visit BradyID.com.au to confirm compatibility.

Chemical and Solvent Resistant Matte Polypropylene Labels (B-425A)

- Excellent solvent, fuel oil and liquids resistance
- Also has write-on ability for printed labels that require future hand-written data be added
- Flexible material conforms to irregular surfaces better than traditional polyesters
- Consult technical data sheet for UL / CSA ratings and complete performance and testing details




Figure 1




Figure 2



Part No.	For Use with Printers:	Diagram	Reference	Colour	Label width A (mm)	Label height B (mm)	Horiz. repeat C (mm)	Vert. repeat D (mm)	Web width E (mm)	Labels per row	Labels per roll	Rec. ribbon
142962	i3300, i5300, BBP33	Fig. 1	B33-5-425	White	25.4	12.7	27.3	15.2	85.1	3	5000	B30-R4300
153321	i3300, i5300, BBP33	Fig. 1	B33-6-425	White	38.1	19.1	41.9	22.2	85.1	2	3300	B30-R4300
153320	i3300, i5300, BBP33	Fig. 2	B33-53-425	White	50.8	12.7	-	15.2	55.9	1	2000	B30-R4300
142891	i3300, i5300, BBP33	Fig. 2	B33-17-425	White	50.8	25.4	-	28.6	55.9	1	1500	B30-R4300
153322	i3300, i5300, BBP33	Fig. 2	B33-7-425	White	69.9	31.8	-	34.9	74.9	1	1000	B30-R4300
142892	i3300, i5300, BBP33	Fig. 2	B33-18-425	White	76.2	25.4	-	28.6	81.3	1	1500	B30-R4300
143053	i3300, i5300, BBP33	Fig. 2	B33-19-425	White	76.2	50.8	-	54.0	81.3	1	500	B30-R4300
153325	i3300, i5300, BBP33	Fig. 2	B33-20-425	White	76.2	127.0	-	130.1	81.3	1	250	B30-R4300
153323	i3300, i5300, BBP33	Fig. 2	B33-55-425	White	101.6	50.8	-	53.9	106.7	1	600	B30-R4300
153324	i3300, i5300, BBP33	Fig. 2	B33-76-425	White	101.6	76.2	-	79.3	106.7	1	400	B30-R4300

Retro Reflective Labels (B-584)

- Highly reflective material shines back brightly when struck by light
- Ideal for labelling outdoor utility pedestals, hard hats, jobsite equipment and roof-top equipment
- Recommended for low light or inclement weather conditions




Figure 3



Part No.	For Use with Printers:	Diagram	Reference	Colour	Label Width A (mm)	Roll Length B (m)	Labels Per Roll	Rec. Ribbon
117999	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-584-SL	Silver	28.6	15.2	1 roll (cont.)	B30-R10000
117998	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-584-SL	Silver	57.5	15.2	1 roll (cont.)	B30-R10000
117997	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-584-SL	Silver	101.6	15.2	1 roll (cont.)	B30-R10000
118002	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-584-YL	Yellow	28.6	15.2	1 roll (cont.)	B30-R10000
118001	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-584-YL	Yellow	57.5	15.2	1 roll (cont.)	B30-R10000
118000	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-584-YL	Yellow	101.6	15.2	1 roll (cont.)	B30-R10000
117996	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-584-OR	Orange	28.6	15.2	1 roll (cont.)	B30-R10000
117995	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-584-OR	Orange	57.5	15.2	1 roll (cont.)	B30-R10000
117994	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-584-OR	Orange	101.6	15.2	1 roll (cont.)	B30-R10000

BradyGlo™ High-Intensity Glow-in-the-Dark Labels (B-526)

- For glow-in-the-dark identification up to 10 hours
- Designed for directional, evacuation and equipment marking. Ideal for marking emergency utility shut-offs, fire extinguishers, alarm pulls and vital equipment controls
- Complies with indoor use requirements specified in RS 6-1 and 6-1A of New York Local Law 26




Figure 3



Part No.	For Use with Printers:	Diagram	Reference	Colour	Label Width A (mm)	Roll Length B (m)	Labels Per Roll	Rec. Ribbon
117928	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-526	Luminous Green	28.6	15.2	1 roll (cont.)	B30-R10000
117926	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-526	Luminous Green	57.5	15.2	1 roll (cont.)	B30-R10000
117924	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-526	Luminous Green	101.6	15.2	1 roll (cont.)	B30-R10000

Printable Magnetic Labels

(B-509)

- Easiest and quickest material for removing and repositioning
- Non-adhesive magnetic material that can be printed on directly
- Ideal for changing shelf storage locations, and reusable/repositionable Lean / 5S applications




Figure 3b



Part No.	For Use with Printers:	Diagram	Reference	Colour	Label Width A (mm)	Roll Length B (m)	Labels Per Roll	Rec. Ribbon
117917	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3b	B30C-2500-509-WT	White	63.5	7.62	1 roll (cont.)	B30-R10000
117916	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3b	B30C-4250-509-WT	White	107.8	7.62	1 roll (cont.)	B30-R10000
117919	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3b	B30C-2500-509-YL	Yellow	63.5	7.62	1 roll (cont.)	B30-R10000
117918	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3b	B30C-4250-509-YL	Yellow	107.8	7.62	1 roll (cont.)	B30-R10000

Repositionable Multi-Purpose Vinyl

(B-581)

- Aggressive adhesive stays in place but removes cleanly without leaving adhesive residue
- Ideal for temporary, removable and repositionable facility labels, such as Lean / 5S inventory labels




Figure 3



Part No.	For Use with Printers:	Diagram	Reference	Colour	Label Width A (mm)	Roll Length B (m)	Labels Per Roll	Rec. Ribbon
118006	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-581-WT	White	12.7	30.5	1 roll (cont.)	B30-R10000
118005	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-581-WT	White	28.6	30.5	1 roll (cont.)	B30-R10000
118004	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-581-WT	White	57.5	30.5	1 roll (cont.)	B30-R10000
118003	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-581-WT	White	101.6	30.5	1 roll (cont.)	B30-R10000
118010	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-500-581-YL	Yellow	12.7	30.5	1 roll (cont.)	B30-R10000
118009	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-581-YL	Yellow	28.6	30.5	1 roll (cont.)	B30-R10000
118008	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-581-YL	Yellow	57.5	30.5	1 roll (cont.)	B30-R10000
118007	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-581-YL	Yellow	101.6	30.5	1 roll (cont.)	B30-R10000

Cold Temperature Application Labels

(B-549)

- Special adhesive permanently adheres to extremely cold surfaces
- Can be applied in -5° C and lasts in -22° C
- Ideal for cold storage warehouses, coolers, freezers and short-term winter outdoor use




Figure 3



Part No.	For Use with Printers:	Diagram	Reference	Colour	Label Width A (mm)	Roll Length B (m)	Labels Per Roll	Rec. Ribbon
117862	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-549-WT	White	28.6	30.5	1 roll (cont.)	B30-R10000
117861	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-549-WT	White	57.5	30.5	1 roll (cont.)	B30-R10000
117860	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-549-WT	White	101.6	30.5	1 roll (cont.)	B30-R10000
117865	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-1125-549-YL	Yellow	28.6	30.5	1 roll (cont.)	B30-R10000
117864	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-2250-549-YL	Yellow	57.5	30.5	1 roll (cont.)	B30-R10000
117863	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3	B30C-4000-549-YL	Yellow	101.6	30.5	1 roll (cont.)	B30-R10000

Pre-Printed GHS / CLP Chemical Labels (B-569, B-7569)

- Blank labels with pre-printed red diamonds allow the printer to produce 2-colour GHS / CLP labels in one print pass
- Three sizes of labels, each with six diamond layouts that match templates in the printer app (if applicable) or in the Brady Workstation GHS App
- Indoor / outdoor vinyl material and durable inks withstand exposure to moisture, chemicals and handling



Part No.	Reference	B#	Material	Legend		Label Height (mm)	Label Width (mm)	Labels Per Row	Labels Per Roll	Rec. Ribbon
121633	B30-260-7569-CLP1	B-7569	Vinyl		L1 Diamond + Text	55.0	85.1	1	340	B30-R10000
121639	B30-261-7569-CLP1	B-7569	Vinyl		L1 Diamond + Text	75.0	110.0	1	270	B30-R10000
121645	B30-262-7569-CLP1	B-7569	Vinyl		L1 Diamond + Text	105.0	155.0	1	200	B30-R10000
121634	B30-260-7569-CLP2	B-7569	Vinyl		L2 Diamond + Text	55.0	85.1	1	340	B30-R10000
121640	B30-261-7569-CLP2	B-7569	Vinyl		L2 Diamond + Text	75.0	110.0	1	270	B30-R10000
121646	B30-262-7569-CLP2	B-7569	Vinyl		L2 Diamond + Text	105.0	155.0	1	200	B30-R10000
121635	B30-260-7569-CLP3A	B-7569	Vinyl		L3A Diamond + Text	55.0	85.1	1	340	B30-R10000
121641	B30-261-7569-CLP3A	B-7569	Vinyl		L3A Diamond + Text	75.0	110.0	1	270	B30-R10000
121647	B30-262-7569-CLP3A	B-7569	Vinyl		L3A Diamond + Text	105.0	155.0	1	200	B30-R10000
121636	B30-260-7569-CLP3B	B-7569	Vinyl		L3B Diamond + Text	55.0	85.1	1	340	B30-R10000
121642	B30-261-7569-CLP3B	B-7569	Vinyl		L3B Diamond + Text	75.0	110.0	1	270	B30-R10000
121648	B30-262-7569-CLP3B	B-7569	Vinyl		L3B Diamond + Text	105.0	155.0	1	200	B30-R10000
121637	B30-260-7569-CLP4A	B-7569	Vinyl		L4A Diamond + Text	55.0	85.1	1	340	B30-R10000
121643	B30-261-7569-CLP4A	B-7569	Vinyl		L4A Diamond + Text	75.0	110.0	1	270	B30-R10000
121649	B30-262-7569-CLP4A	B-7569	Vinyl		L4A Diamond + Text	105.0	155.0	1	200	B30-R10000
149503	B30-260-569-CLP4B	B-569	Polyester		L4B Diamond + Text	55.0	85.1	1	340	B30-R10000
121638	B30-260-7569-CLP4B	B-7569	Vinyl		L4B Diamond + Text	55.0	85.1	1	340	B30-R10000
149504	B30-261-569-CLP4B	B-569	Polyester		L4B Diamond + Text	75.0	110.0	1	270	B30-R10000
121644	B30-261-7569-CLP4B	B-7569	Vinyl		L4B Diamond + Text	75.0	110.0	1	270	B30-R10000
149505	B30-262-569-CLP4B	B-569	Polyester		L4B Diamond + Text	105.0	155.0	1	200	B30-R10000
121650	B30-262-7569-CLP4B	B-7569	Vinyl		L4B Diamond + Text	105.0	155.0	1	200	B30-R10000
149209	B30-18-7569-CLP4C	B-7569	Vinyl		L4C Diamond + Text	25.4	76.2	1	1000	B30-R10000

▶ Easily create your GHS labels with Brady Workstation GHS App

- Use built-in pre-formatted label layouts with approved GHS symbols
- Search the built-in chemical database by CAS number to auto-populate your label, then edit to meet your specific SDS
- Print any of the six template sizes
- No driver required when using the BradyPrinter i5300



All part numbers above are compatible with BradyPrinter i3300, i5300, S3000, S3100, and BBP30, 31, 33, 35, 37 models. Visit BradyID.com.au to confirm compatibility.

General Identification Die Cut Labels for Bins, Shelves, Tools and Production Areas

(B-439, B-498, B-499, B-595)

- These labels are all highly conforming to irregular, angled or rough surfaces frequently found in industrial production line areas
- Die-cut labels are an ideal choice when pre-cut labels are preferred or consistent label sizing is required
- B-595 is a convenient cut-to-length continuous material that reduces the need to stock multiple parts when inconsistent label lengths are expected




Figure 1




Figure 2




Figure 3a



Part No.	For Use with Printers:	Diagram	Reference	Colour	Label width A (mm)	Label height B (mm)	Horiz. repeat C (mm)	Vert. repeat D (mm)	Web width E (mm)	Labels per row	Labels per roll	Rec. ribbon
Vinyl - Highly pliable and conforming with aggressive permanent adhesive and excellent chemical resistance (B-439)												
152853	i3300, i5300, BBP33	Fig. 1	B33-5-439	White	25.4	12.7	27.3	15.2	85.1	3	7000	B30-R6000
152857	i3300, i5300, BBP33	Fig. 1	B33-37-439	White	38.1	12.7	41.9	15.2	85.1	2	5000	B30-R6000
152858	i3300, i5300, BBP33	Fig. 2	B33-53-439	White	50.8	12.7	-	15.2	55.9	1	2500	B30-R6000
152854	i3300, i5300, BBP33	Fig. 2	B33-17-439	White	50.8	25.4	-	28.5	55.9	1	1000	B30-R6000
152855	i3300, i5300, BBP33	Fig. 2	B33-18-439	White	76.2	25.4	-	28.5	85.1	1	1000	B30-R6000
152856	i3300, i5300, BBP33	Fig. 2	B33-19-439	White	76.2	50.8	-	53.9	81.3	1	700	B30-R6000
152859	i3300, i5300, BBP33	Fig. 2	B33-55-439	White	101.6	50.8	-	53.9	106.7	1	700	B30-R6000
152860	i3300, i5300, BBP33	Fig. 2	B33-76-439	White	101.6	76.2	-	79.3	106.7	1	500	B30-R6000
Flexible Vinyl Cloth - Pliable with aggressive hold adhesive that can be removed and reapplied (B-498)												
143074	i3300, i5300, BBP33	Fig. 1	B33-68-498	White	12.7	19.1	15.2	22.2	63.5	4	5000	B30-R6200
143009	i3300, i5300, BBP33	Fig. 1	B33-87-498	White	12.7	36.5	15.2	39.7	94.0	6	2500	B30-R6200
142966	i3300, i5300, BBP33	Fig. 1	B33-5-498	White	25.4	12.7	27.3	15.2	85.1	3	5000	B30-R6200
142874	i3300, i5300, BBP33	Fig. 1	B33-88-498	White	25.4	19.1	27.9	22.2	58.4	2	2500	B30-R6200
142967	i3300, i5300, BBP33	Fig. 1	B33-89-498	White	25.4	36.5	27.9	39.7	86.4	3	2300	B30-R6200
Flexible Nylon Cloth - Permanent adhesive (B-499)												
143018	i3300, i5300, BBP33	Fig. 1	B33-68-499	White	12.7	19.1	15.2	22.2	63.5	4	1500	B30-R6000
143002	i3300, i5300, BBP33	Fig. 1	B33-165-499	White	20.3	36.5	22.9	39.7	94.0	4	2500	B30-R6000
143011	i3300, i5300, BBP33	Fig. 1	B33-126-499	White	25.4	12.7	27.3	15.2	85.1	3	5000	B30-R6000
143001	i3300, i5300, BBP33	Fig. 2	B33-163-499	White	25.4	19.1	27.9	22.2	58.4	2	2500	B30-R6000
142997	i3300, i5300, BBP33	Fig. 2	B33-136-499	White	38.1	19.1	-	22.2	45.0	1	1500	B30-R6000
143066	i3300, i5300, BBP33	Fig. 2	B33-137-499	White	50.8	25.4	-	28.6	55.9	1	1100	B30-R6000
Glossy Polyester - Ultra-aggressive adhesive for flat but highly textured surfaces (B-483)												
133806	i3300, i5300, BBP33	Fig. 1	B33-149-483	Gloss White	12.7	12.7	15.2	15.2	63.5	4	5000	B30-R6000
143075	i3300, i5300, BBP33	Fig. 1	B33-5-483	Gloss White	25.4	12.7	27.3	15.2	85.1	3	5000	B30-R6000
143084	i3300, i5300, BBP33	Fig. 2	B33-17-483	Gloss White	50.8	25.4	-	28.6	55.9	1	1500	B30-R6000
133965	i3300, i5300, BBP33	Fig. 2	B33-7-483	Gloss White	69.9	31.8	-	34.9	74.9	1	1000	B30-R6000
143079	i3300, i5300, BBP33	Fig. 2	B33-18-483	Gloss White	76.2	25.4	-	28.6	81.3	1	1500	B30-R6000
142956	i3300, i5300, BBP33	Fig. 2	B33-19-483	Gloss White	76.2	50.8	-	54.0	81.3	1	500	B30-R6000
133897	i3300, i5300, BBP33	Fig. 2	B33-55-483	Gloss White	101.6	50.8	-	54.0	106.7	1	750	B30-R6000
Cut-to-Length Vinyl - Highly pliable all weather with aggressive permanent adhesive (B-595)												
142031	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3a	B30C-500-595-WT	White	12.7	30.5 m	-	-	17.8	1 roll (cont.)		B30-R10000
142030	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3a	B30C-1125-595-WT	White	28.6	30.5 m	-	-	34.9	1 roll (cont.)		B30-R10000
142036	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3a	B30C-500-595-YL	Yellow	12.7	30.5 m	-	-	17.8	1 roll (cont.)		B30-R10000
142035	i3300, i5300, S3000, S3100, BBP30, BBP31, BBP33, BBP35, BBP37	Fig. 3a	B30C-1125-595-YL	Yellow	28.6	30.5 m	-	-	34.9	1 roll (cont.)		B30-R10000

ToughStripe® Printable Floor Marking Tape (B-483A with overlamine)

- Revolutionary B-483A material has ultra-aggressive adhesive
- Withstands forklift and pallet jack traffic without tearing or lifting
- Each roll ships with a roll of clear overlamine which must be applied over printed label and onto appropriate surface for best performance




Figure 3b



Part No.	Diagram	Reference	B#	Colour	Label Width A (mm)	Roll Length B (m)	Labels Per Roll	Rec. Ribbon
139950	Fig. 3b	B30C-1125-483WT-KT	B-483	White	28.6	30.5	1 roll (cont.)	B30-R6000
139949	Fig. 3b	B30C-2250-483WT-KT	B-483	White	57.5	30.5	1 roll (cont.)	B30-R6000
139948	Fig. 3b	B30C-3000-483WT-KT	B-483	White	76.2	30.5	1 roll (cont.)	B30-R6000
139947	Fig. 3b	B30C-4000-483WT-KT	B-483	White	101.6	30.5	1 roll (cont.)	B30-R6000
139946	Fig. 3b	B30C-1125-483YL-KT	B-483	Yellow	28.6	30.5	1 roll (cont.)	B30-R6000
139945	Fig. 3b	B30C-2250-483YL-KT	B-483	Yellow	57.5	30.5	1 roll (cont.)	B30-R6000
139944	Fig. 3b	B30C-3000-483YL-KT	B-483	Yellow	76.2	30.5	1 roll (cont.)	B30-R6000
139943	Fig. 3b	B30C-4000-483YL-KT	B-483	Yellow	101.6	30.5	1 roll (cont.)	B30-R6000
139942	Fig. 3b	B30C-1125-483RD-KT	B-483	Red	28.6	30.5	1 roll (cont.)	B30-R4400-WT
139941	Fig. 3b	B30C-2250-483RD-KT	B-483	Red	57.5	30.5	1 roll (cont.)	B30-R4400-WT
139940	Fig. 3b	B30C-4000-483RD-KT	B-483	Red	101.6	30.5	1 roll (cont.)	B30-R4400-WT
139939	Fig. 3b	B30C-1125-483BL-KT	B-483	Blue	28.6	30.5	1 roll (cont.)	B30-R4400-WT
139938	Fig. 3b	B30C-2250-483BL-KT	B-483	Blue	57.5	30.5	1 roll (cont.)	B30-R4400-WT
139937	Fig. 3b	B30C-4000-483BL-KT	B-483	Blue	101.6	30.5	1 roll (cont.)	B30-R4400-WT
139936	Fig. 3b	B30C-1125-483GN-KT	B-483	Green	28.6	30.5	1 roll (cont.)	B30-R4400-WT
139935	Fig. 3b	B30C-2250-483GN-KT	B-483	Green	57.5	30.5	1 roll (cont.)	B30-R4400-WT
139934	Fig. 3b	B30C-4000-483GN-KT	B-483	Green	101.6	30.5	1 roll (cont.)	B30-R4400-WT
139933	Fig. 3b	B30C-1125-483BK-KT	B-483	Black	28.6	30.5	1 roll (cont.)	B30-R4400-WT
139932	Fig. 3b	B30C-2250-483BK-KT	B-483	Black	57.5	30.5	1 roll (cont.)	B30-R4400-WT
139931	Fig. 3b	B30C-4000-483BK-KT	B-483	Black	101.6	30.5	1 roll (cont.)	B30-R4400-WT
139930	Fig. 3b	B30C-1125-483OR-KT	B-483	Orange	28.6	30.5	1 roll (cont.)	B30-R6000
139929	Fig. 3b	B30C-2250-483OR-KT	B-483	Orange	57.5	30.5	1 roll (cont.)	B30-R6000
139928	Fig. 3b	B30C-4000-483OR-KT	B-483	Orange	101.6	30.5	1 roll (cont.)	B30-R6000

ToughStripe part numbers above are compatible with BradyPrinter i3300, i5300, BradyPrinter S3000, BradyPrinter S3100, and BBP®35 and BBP®37 printers. **ToughStripe material is not compatible with BBP®30, BBP®33 and BBP®31 printers.**

Microscope Slide Labels (B-481)

- Designed specifically to identify slides and to resist exposure to harsh chemicals during the slide-staining process
- Performs well in stains such as hematoxylin and eosin
- Extreme chemical resistance withstands the rigors of typical deparaffinization, including ethanol, xylene and H&E staining processes




Figure 2

Figure 25



Part No.	For Use with Printers:	Diagram	Reference	B#	Colour	Label Width A (mm)	Label Height B (mm)	Labels Per Row	Labels Per Roll	Rec. Ribbon
143055	i3300, i5300, BBP33	Fig. 2	B33-194-481	B-481	White	22.9	19.1	1	2000	B30-R6400
143047	i3300, i5300, BBP33	Fig. 25	B33-141-481	B-481	White	22.9	22.9	2	1500	B30-R6400
133831	i3300, i5300, BBP33	Fig. 2	B33-195-481	B-481	White	22.9	9.5	1	3000	B30-R6400

Cryogenic Tube and Vial Labels (B-461, B-490, B-492, B-7425)

FreezerBondz™ labels can be applied to room temperature or already frozen samples, with a small overlap. The label remains legible and will stick to the tube during processing, even when immersed in liquid or vapor phase nitrogen and ultra-low temperature freezer storage.

- **B-461 Self-Laminating Polyester:** Ultra-thin polyester label with clear overlaminating tail that protects print and allows liquid levels to be visible
- **B-490 Polyester:** White FreezerBondz label ideal for flat frozen surfaces. Adheres to frozen tubes and vials when wrapped around itself by at least 3mm.
- **B-492 Polyester:** FreezerBondz ultra-thin white polyester label for labelling of frosted/frozen or room temperature vials, tubes and canes. Superior chemical and abrasion resistance
- **B-7425 Polypropylene:** Ideal for labelling dry, room temperature specimen containers. Material withstands temperature ranges from -196° to 121° C. Chemical resistance to ethanol, DMSO, IPS, short-term xylene, 10% formalin, 50% acetic acid and toluene




Figure 2




Figure 5




Figure 7b




Figure 14c




Figure 15c




Figure 25a

Part No.	For Use with Printers:	Diagram	Reference	B#	Colour	Label Width A (mm)	Label Height B (mm)	Print-On Height C (mm)	Labels Per Row	Labels Per Roll	Rec. Ribbon
Self-Laminating Polyester (B-461):											
143012	i3300, i5300, BBP33	Fig. 15c	B33-127-461	B-461	White/Clear	12.7	55.9	19.1	1	1500	B30-R4300
143014	i3300, i5300, BBP33	Fig. 15c	B33-133-461	B-461	White/Clear	15.2	41.3	25.4	1	1500	B30-R4300
143046	i3300, i5300, BBP33	Fig. 14c	B33-139-461	B-461	White/Clear	25.4	133.4	38.1	2	650	B30-R4300
143010	i3300, i5300, BBP33	Fig. 15c	B33-123-461	B-461	White/Clear	45.7	9.5	19.1	1	1500	B30-R4300
143043	i3300, i5300, BBP33	Fig. 15c	B33-122-461	B-461	White/Clear	45.7	12.7	19.1	1	1500	B30-R4300
143013	i3300, i5300, BBP33	Fig. 14c	B33-276-461	B-461	White/Clear	66.7	25.4	25.4	1	1500	B30-R4300
143044	i3300, i5300, BBP33	Fig. 15c	B33-134-461	B-461	White/Clear	88.9	38.1	31.8	1	1000	B30-R4300
Polyester (B-490):											
142939	i3300, i5300, BBP33	Fig. 7b	B33-126-490	B-490	White	22.9	12.7	12.7 dia.	1	2500	B30-R4300
142893	i3300, i5300, BBP33	Fig. 2	B33-154-490	B-490	White	31.8	9.5	-	1	1500	B30-R4300
143089	i3300, i5300, BBP33	Fig. 2	B33-155-490	B-490	White	41.3	15.2	-	1	1500	B30-R4300
142894	i3300, i5300, BBP33	Fig. 2	B33-156-490	B-490	White	48.2	25.4	-	1	1500	B30-R4300
142895	i3300, i5300, BBP33	Fig. 2	B33-157-490	B-490	White	55.9	38.1	-	1	1000	B30-R4300
142896	i3300, i5300, BBP33	Fig. 2	B33-158-490	B-490	White	95.3	44.4	-	1	1100	B30-R4300
Polyester (B-492):											
142918	i3300, i5300, BBP33	Fig. 5	B33-143-492	B-492	White	9.5 dia.	-	-	4	1500	B30-R6400
143082	i3300, i5300, BBP33	Fig. 7b	B33-182-492	B-492	White	12.7	25.4	11.17 dia.	1	1500	B30-R6400
143051	i3300, i5300, BBP33	Fig. 2	B33-180-492	B-492	White	22.9	25.4	-	1	1500	B30-R6400
142942	i3300, i5300, BBP33	Fig. 25a	B33-152-492	B-492	White	25.4	9.5	-	2	2500	B30-R6400
143000	i3300, i5300, BBP33	Fig. 7b	B33-163-492	B-492	White	25.4	9.5	9.5 dia.	1	1500 sets	B30-R6400
143100	i3300, i5300, BBP33	Fig. 7b	B33-181-492	B-492	White	25.4	12.7	9.5 dia.	1	1500 sets	B30-R6400
143063	i3300, i5300, BBP33	Fig. 2	B33-59-492	B-492	White	25.4	12.7	-	1	2500	B30-R6400
143067	i3300, i5300, BBP33	Fig. 2	B33-179-492	B-492	White	25.4	25.4	-	1	1900	B30-R6400
142917	i3300, i5300, BBP33	Fig. 2	B33-156-492	B-492	White	48.3	25.4	-	1	1500	B30-R6400
Polypropylene (B-7425):											
148677	i3300, i5300, BBP33	Fig. 2	B33-257-7425	B-7425	White	21.0	6.4	-	1	1500	B30-R4300
148681	i3300, i5300, BBP33	Fig. 25a	B33-152-7425	B-7425	White	25.4	9.5	-	2	2000	B30-R4300
148673	i3300, i5300, BBP33	Fig. 2	B33-59-7425	B-7425	White	25.4	12.7	-	1	2000	B30-R4300
148680	i3300, i5300, BBP33	Fig. 25a	B33-88-7425	B-7425	White	25.4	19.1	-	2	2000	B30-R4300
148671	i3300, i5300, BBP33	Fig. 2	B33-256-7425	B-7425	White	33.0	15.2	-	1	1500	B30-R4300
148679	i3300, i5300, BBP33	Fig. 25a	B33-37-7425	B-7425	White	38.1	12.7	-	2	1500	B30-R4300

Centrifuge and PCR Tube Labels

(B-499, B-7425)

Designed with ultra-thin material that prevents vials from jamming in centrifuges or racks, these labels withstand harsh temperatures and chemicals without falling off, fading or smearing.

- **B-499 Nylon Cloth:** Thick white nylon cloth for easy handling and conformability
- **B-7425 Polypropylene:** Moderate chemical resistance, ideal for labelling dry, room-temperature specimen containers that withstand temperature ranges from -196° to 121° C. Chemical resistance to ethanol, DMSO, IPS, short-term xylene, 10% formalin, 50% acetic acid and toluene




Figure 2




Figure 5




Figure 7b



Part No.	For Use with Printers:	Diagram	Reference	B#	Colour	Label Width A (mm)	Label Height B (mm)	Vial Top Dia. C (mm)	Labels Per Row	Labels Per Roll	Rec. Ribbon
Nylon Cloth (B-499):											
143015	i3300, i5300, BBP33	Fig. 5	B33-143-499	B-499	White	9.5	-	-	4	1500	B30-R6000
143016	i3300, i5300, BBP33	Fig. 5	B33-144-499	B-499	White	12.7	-	-	3	1500	B30-R6000
Polypropylene (B-7425):											
148677	i3300, i5300, BBP33	Fig. 2	B33-257-7425	B-7425	White	21.0	6.4	-	1	1500	B30-R4300
148681	i3300, i5300, BBP33	Fig. 2	B33-152-7425	B-7425	White	25.4	9.5	-	2	2000	B30-R4300
148682	i3300, i5300, BBP33	Fig. 7b	B33-249-7425	B-7425	White	25.4	9.5	9.5 dia.	1	1500	B30-R4300
148673	i3300, i5300, BBP33	Fig. 2	B33-59-7425	B-7425	White	25.4	12.7	-	1	2000	B30-R4300
148670	i3300, i5300, BBP33	Fig. 7b	B33-251-7425	B-7425	White	25.4	12.7	11.1 dia.	1	1500	B30-R4300
148675	i3300, i5300, BBP33	Fig. 2	B33-179-7425	B-7425	White	25.4	25.4	-	1	1500	B30-R4300
148671	i3300, i5300, BBP33	Fig. 2	B33-256-7425	B-7425	White	33.0	15.2	-	1	1500	B30-R4300
148679	i3300, i5300, BBP33	Fig. 2	B33-37-7425	B-7425	White	38.1	12.7	-	2	1500	B30-R4300
148676	i3300, i5300, BBP33	Fig. 2	B33-136-7425	B-7425	White	38.1	19.1	-	1	1500	B30-R4300
148684	i3300, i5300, BBP33	Fig. 2	B33-258-7425	B-7425	White	38.1	44.5	-	1	900	B30-R4300
148683	i3300, i5300, BBP33	Fig. 2	B33-137-7425	B-7425	White	50.8	25.4	-	1	1500	B30-R4300

Colour-Stripe Polyester Lab Labels

(B-494)

White labels with preprinted colour borders for colour-coding samples. Ultra-thin material that prevents vials from jamming in centrifuges or racks, these labels withstand harsh temperatures and chemicals without falling off, fading or smearing. The coloured boarder is non-printable, but the coloured vial top is printable.




Figure 25c




Figure 24b





Figure 2e



Part No.	For Use with Printers:	Diagram	Reference	Border Colour	Label width A (mm)	Label height B (mm)	Print-On Height C (mm)	Print-On Height F (mm)	Labels per row	Labels per roll	Rec. ribbon
149808	i3300, i5300, BBP33	Fig. 25c	B33-152-494-BL	Blue	25.4	9.5	-	6.4	2	1,500	B30-R6400
149810	i3300, i5300, BBP33	Fig. 25c	B33-152-494-GN	Green	25.4	9.5	-	6.4	2	1,500	B30-R6400
149809	i3300, i5300, BBP33	Fig. 25c	B33-152-494-OR	Orange	25.4	9.5	-	6.4	2	1,500	B30-R6400
149811	i3300, i5300, BBP33	Fig. 25c	B33-152-494-PK	Pink	25.4	9.5	-	6.4	2	1,500	B30-R6400
149807	i3300, i5300, BBP33	Fig. 25c	B33-152-494-RD	Red	25.4	9.5	-	6.4	2	1,500	B30-R6400
149806	i3300, i5300, BBP33	Fig. 25c	B33-152-494-YL	Yellow	25.4	9.5	-	6.4	2	1,500	B30-R6400
149784	i3300, i5300, BBP33	Fig. 24b	B33-250-494-BL	Blue	25.4	12.7	9.5 dia.	9.5	1	1,500	B30-R6400
149786	i3300, i5300, BBP33	Fig. 24b	B33-250-494-GN	Green	25.4	12.7	9.5 dia.	9.5	1	1,500	B30-R6400
149785	i3300, i5300, BBP33	Fig. 24b	B33-250-494-OR	Orange	25.4	12.7	9.5 dia.	9.5	1	1,500	B30-R6400
149787	i3300, i5300, BBP33	Fig. 24b	B33-250-494-PK	Pink	25.4	12.7	9.5 dia.	9.5	1	1,500	B30-R6400
149783	i3300, i5300, BBP33	Fig. 24b	B33-250-494-RD	Red	25.4	12.7	9.5 dia.	9.5	1	1,500	B30-R6400
149782	i3300, i5300, BBP33	Fig. 24b	B33-250-494-YL	Yellow	25.4	12.7	9.5 dia.	9.5	1	1,500	B30-R6400
149790	i3300, i5300, BBP33	Fig. 2e	B33-179-494-BL	Blue	25.4	25.4	-	22.2	1	1,500	B30-R6400
149792	i3300, i5300, BBP33	Fig. 2e	B33-179-494-GN	Green	25.4	25.4	-	22.2	1	1,500	B30-R6400
149791	i3300, i5300, BBP33	Fig. 2e	B33-179-494-OR	Orange	25.4	25.4	-	22.2	1	1,500	B30-R6400
149793	i3300, i5300, BBP33	Fig. 2e	B33-179-494-PK	Pink	25.4	25.4	-	22.2	1	1,500	B30-R6400
149789	i3300, i5300, BBP33	Fig. 2e	B33-179-494-RD	Red	25.4	25.4	-	22.2	1	1,500	B30-R6400
149788	i3300, i5300, BBP33	Fig. 2e	B33-179-494-YL	Yellow	25.4	25.4	-	22.2	1	1,500	B30-R6400

Dissolvable Paper Labels

(B-403)

- Designed for temporary applications where easy removal, re-identification or waste reduction are valued
- Ideal for labelling vials, tubes or general glassware, temporary asset tracking, animal housing identification, and general use
- Completely dissolves in warm water within 30 seconds, leaving no adhesive residue




Figure 3



Part No.	For Use with Printers:	Diagram	Reference	B#	Colour	Label Width A (mm)	Roll Length B (mm)	Labels Per Roll	Rec. Ribbon
149268	i3300, i5300, BBP33	Fig. 3	B30C-1125-403-WT	B-403	White	28.575	30.5	1 (cont.)	B30-R4300
149269	i3300, i5300, BBP33	Fig. 3	B30C-2250-403-WT	B-403	White	57.15	30.5	1 (cont.)	B30-R4300
149270	i3300, i5300, BBP33	Fig. 3	B30C-3000-403-WT	B-403	White	76.2	30.5	1 (cont.)	B30-R4300
149271	i3300, i5300, BBP33	Fig. 3	B30C-4000-403-WT	B-403	White	101.6	30.5	1 (cont.)	B30-R4300

Sterilisation Indicating Labels

(B-7425-AC)

- Specially designed with a pre-printed “sterilised” header that indicates steam sterilisation with a colour-changing pre-printed header when autoclaved at 121.5° C for 10 minutes
- Withstands temperature ranges from -196° to 121° C
- For use in LN2, freezers, autoclave and hot water baths
- Chemical resistance to ethanol, DMSO, IPS, short-term xylene, 10% formalin, 50% acetic acid and toluene




Figure 29a



Part No.	For Use with Printers:	Diagram	Reference	B#	Colour	Label Width A (mm)	Label Height B (mm)	Print Area Height F (mm)	Labels Per Row	Labels Per Roll	Rec. Ribbon
149261	i3300, i5300, BBP33	Fig. 29a	B33-235-7425-AC	B-7425-AC	White	38.1	25.4	19.1	1	1250	B30-R4300
149262	i3300, i5300, BBP33	Fig. 29a	B33-137-7425-AC	B-7425-AC	White	50.8	25.4	19.1	1	1500	B30-R4300

Tissue Cassette Labels

(B-481)

- White polyester label with superior resistance to tissue processing chemicals and embedding procedures. Use with the BSP™31 Label Attachment system for pre-process tissue cassette identification




Figure 2



Part No.	For Use with Printers:	Diagram	Reference	B#	Colour	Label Width A (mm)	Label Height B (mm)	Labels Per Row	Labels Per Roll	Rec. Ribbon
151979	i3300, i5300, BBP33	Fig. 2	B33-199-481	B-481	White	26.7	6.4	1	3000	B30-R6400
151980	i3300, i5300, BBP33	Fig. 2	B33-213-481	B-481	White	26.7	8	1	3000	B30-R6400

General Identification for Laboratory Storage, Equipment and Safety Labels

(B-499, B-595, B-7569)

- Super strong adhesives and colours ideal for marking laboratory equipment, containers, hoses and lab storage cabinets, shelves and drawers
- GHS labels available for marking chemicals in the lab and shipment boxes when collaborating with other labs
- Pre-printed sign header labels make your safety and housekeeping reminders stand out and stay put!




Figure 1




Figure 2




Figure 3a




Figure 70



Part No.	Diagram	Reference	Colour / Legend	Label Width A (mm)	Label Height B (mm)	Horiz. Repeat C (mm)	Vert. Repeat D (mm)	Web Width E (mm)	Roll Length B (m)	Labels Per Row	Labels Per Roll	Rec. Ribbon
Nylon Cloth - Permanent Adhesive (B-499):												
143018	Fig. 1	B33-68-499	White	12.7	19.1	15.2	22.2	63.5	–	4	1500	B30-R6000
143002	Fig. 1	B33-165-499	White	20.3	36.5	22.9	39.7	94.0	–	4	2500	B30-R6000
142995	Fig. 2	B33-125-499	White	22.9	12.7	–	–	–	–	1	1500	B30-R6000
143011	Fig. 1	B33-126-499	White	22.9	12.7	–	–	–	–	2	1500	B30-R6000
143001	Fig. 2	B33-163-499	White	25.4	9.5	–	–	–	–	1	1500	B30-R6000
143017	Fig. 1	B33-152-499	White	25.4	9.5	–	–	–	–	2	1500	B30-R6000
142997	Fig. 2	B33-136-499	White	38.1	19.1	–	22.2	45.0	–	1	1500	B30-R6000
143066	Fig. 2	B33-137-499	White	50.8	25.4	–	28.6	55.9	–	1	1100	B30-R6000
142995	Fig. 2	B33-125-499	White	50.8	6.4	–	–	–	–	1	1500	B30-R6000
Indoor/Outdoor Vinyl (B-595):												
142031	Fig. 3a	B30C-500-595-WT	White	12.7	–	–	–	–	30.5	–	1 roll (cont.)	B30-R10000
142030	Fig. 3a	B30C-1125-595-WT	White	28.6	–	–	–	–	30.5	–	1 roll (cont.)	B30-R10000
142036	Fig. 3a	B30C-500-595-YL	Yellow	12.7	–	–	–	–	30.5	–	1 roll (cont.)	B30-R10000
142035	Fig. 3a	B30C-1125-595-YL	Yellow	28.6	–	–	–	–	30.5	–	1 roll (cont.)	B30-R10000
142026	Fig. 3a	B30C-500-595-RD	Red	12.7	–	–	–	–	30.5	–	1 roll (cont.)	B30-R10000-WT
142025	Fig. 3a	B30C-1125-595-RD	Red	28.6	–	–	–	–	30.5	–	1 roll (cont.)	B30-R10000-WT
141994	Fig. 3a	B30C-500-595-BL	Blue	12.7	–	–	–	–	30.5	–	1 roll (cont.)	B30-R10000-WT
141993	Fig. 3a	B30C-1125-595-BL	Blue	28.6	–	–	–	–	30.5	–	1 roll (cont.)	B30-R10000-WT
142010	Fig. 3a	B30C-500-595-GN	Green	12.7	–	–	–	–	30.5	–	1 roll (cont.)	B30-R10000-WT
142009	Fig. 3a	B30C-1125-595-GN	Green	28.6	–	–	–	–	30.5	–	1 roll (cont.)	B30-R10000-WT
Pre-Printed Pre-Cut Blank Sign Headers (B-595):												
142183	Fig. 70	B30-241-595-ANSIDA		57.5	76.2	–	–	–	–	1	300	B30-R10000
142182	Fig. 70	B30-25-595-ANSIDA		101.6	152.4	–	–	–	–	1	175	B30-R10000
142189	Fig. 70	B30-241-595-ANSINO		57.5	76.2	–	–	–	–	1	300	B30-R10000
142188	Fig. 70	B30-25-595-ANSINO		101.6	152.4	–	–	–	–	1	175	B30-R10000
Pre-Printed GHS/CLP Chemical (B-7569):												
121638	L4B Diamond	B30-260-7569-CLP4B		55.0	85.1	–	–	–	–	1	340	B30-R10000
121644	+ Text	B30-261-7569-CLP4B		75.0	110.0	–	–	–	–	1	270	B30-R10000
149209	L4C Diamond + Text	B30-18-7569-CLP4C		25.4	76.2	–	–	–	–	1	1000	B30-R10000

(B-595) U.S. Patent Nos. 5,823,689; 6,570,602. Additional Patents Pending.

All part numbers above are compatible with BradyPrinter i3300, i5300, and BBP®33. Parts may also be compatible with BradyPrinter S3000, BradyPrinter S3100, BBP®30, BBP®31, BBP®35 and BBP®37 printers. Visit BradyID.com.au to confirm compatibility.

Print Ribbons

Drop and Click print ribbons for 5-second ribbon supply changes


- Tough, smear-proof ribbons that produce long-lasting printed text and can withstand years in industrial areas and outdoor conditions
- Self-contained cartridges drop straight into printer with a “click”
- No calibrating, no threading, no wasted feeding, no hassles and the ink will always be facing the right direction!
- Printer notifies user if installed ribbon is not recommended for installed labels



Installs in 5 seconds...just snap into place!

Single-Colour Print Ribbons

Part No.	Reference	Colour	Size (mm)	Length (m)
118084	B30-R10000	Black	109.9	60.9 m
118094	B30-R4300	Black	109.9	60.9 m
149263	B30-R4900	Black	109.9	60.9 m
118093	B30-R6000	Black	109.9	60.9 m
143119	B30-R6200	Black	109.9	60.9 m
152848	B30-R6300	Black	109.9	60.9 m
143118	B30-R6400	Black	109.9	60.9 m
118095	B30-R6600	Black	109.9	60.9 m
118090	B30-R10000-WT	White	109.9	60.9 m
118097	B30-R4400-WT	White	109.9	60.9 m
133357	B30-R6700-WT	White*	109.9	60.9 m
149264	B30-R6800-WT	White***	109.9	60.9 m
118923	B30-R4500-SV	Silver*	109.9	60.9 m
118089	B30-R10000-RD	Red****	109.9	60.9 m
118086	B30-R10000-GN	Green****	109.9	60.9 m
118085	B30-R10000-BL	Blue****	109.9	60.9 m
118091	B30-R10000-YL	Yellow** / ****	109.9	60.9 m
143501	B30-R10000-YL2	Yellow** / ****	109.9	60.9 m
118088	B30-R10000-OR	Orange****	109.9	60.9 m
118087	B30-R10000-MA	Magenta****	109.9	60.9 m



* B30-R4500-SV ribbon for use with B-342 black and B-345 black sleeves only; B30-R6700-WT ribbon for use with B-345 black sleeves only.

** B30-R10000-YL for printing yellow onto white. B30-R10000-YL2 for printing yellow onto other colours of B-595.

*** B30-R6800-WT for use with B-8117 black labels only.

**** Coloured ribbons optimised for use on white material. Test use on other material colours for suitability to your application.

Print Ribbon / Label Material Compatibility

To ensure the best legend permanence, all ribbons have been developed to meet the requirements of the materials to be printed on. Use the guide below to determine which ribbon series is recommended with your print materials.



●	Recommended ribbon for use with respective material.
▲	Acceptable ribbon for use with respective material.
UL	Materials are UL recognised with its respective ribbon.
CSA	Materials are CSA approved with its respective ribbon.

B-# material		B30-R4300	B30-R4900	B30-R6000	B30-R6200	B30-R6300	B30-R6400	B30-R6600	B30-R10000	B30-R4500-SV*	B30-R4400-WT	B30-R6700-WT*	B30-R6800-WT***	B30-R10000-WT	B30-R10000-YL**	B30-R10000-YL2**	B30-R10000****	
B-342	Polyolefin	●	-	-	-	-	-	●	-	-	-	-	-	-	-	-	-	-
B-342 BLK	Polyolefin	-	-	-	-	-	-	-	-	●	-	-	-	-	-	-	-	-
B-344	Polyolefin	-	-	-	-	-	-	●	-	-	-	-	-	-	-	-	-	-
B-344 YEL	Polyolefin	●	-	-	-	-	-	●	-	-	-	-	-	-	-	-	-	-
B-344 BLK	Polyolefin	-	-	-	-	-	-	-	-	-	●	-	-	-	-	-	-	-
B-345	Polyolefin	-	-	▲	-	-	-	●	-	-	-	-	-	-	-	-	-	-
B-345 BLK	Polyolefin	-	-	-	-	-	-	-	-	●	●	-	-	-	-	-	-	-
B-403	Paper	●	-	-	-	-	-	-	-	-	-	●	-	-	-	-	-	-
B-413	Polyester	-	-	● UL	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-414	Printable VELCRO® Hook	-	-	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-
B-417	Vinyl	● UL	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-422	Polyester	-	-	● UL / CSA	●	-	-	-	-	-	-	-	-	-	-	-	-	-
B-423	Polyester	-	-	● UL / CSA	▲	-	-	-	-	-	-	-	-	-	-	-	-	-
B-424	Paper	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-425	Polypropylene	● UL / CSA	-	-	-	-	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-
B-427	Vinyl	● UL	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-428	Metallised Polyester	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-430	Polyester	-	-	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-432	Clear Polyester	-	▲ UL	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-434A	Metallised Polyester	-	-	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-435	Metallised Polyester	-	-	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-437	Polyvinylfluoride	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-437 YEL	Polyvinylfluoride	●	-	-	●	-	-	-	-	-	-	-	-	-	-	-	-	-
B-438	Metallised Polyester	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-439	Vinyl	-	-	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-443	Polyester	-	-	-	-	-	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-
B-461	Polyester	●	-	-	▲	-	-	-	-	-	-	-	-	-	-	-	-	-
B-472	Polyimide	●	-	-	●	-	-	-	-	-	-	-	-	-	-	-	-	-
B-473	Polyester	-	-	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-481	Polyester	-	-	-	-	-	●	-	-	-	-	-	-	-	-	-	-	-
B-483	Polyester	-	-	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-483A	ToughStripe® Polyester	-	-	●	-	-	-	-	-	-	●	-	-	-	-	-	-	-
B-484A	Polyester	-	-	● UL	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-486B	Metallised Polyester	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

For further material compatibility related to UL/CSA, see pages 18-22 or refer to Brady Tech Data Sheet for complete material performance specifications

Print Ribbon / Label Material Compatibility

●	Recommended ribbon for use with respective material.
▲	Acceptable ribbon for use with respective material.
UL	Materials are UL recognised with its respective ribbon.
CSA	Materials are CSA approved with its respective ribbon.

B-# material		B30-R4300	B30-R4900	B30-R6000	B30-R6200	B30-R6300	B30-R6400	B30-R6600	B30-R10000	B30-R4500-SV*	B30-R4400-WT	B30-R6700-WT*	B30-R6800-WT***	B30-R10000-WT	B30-R10000-YL***	B30-R10000-YL2***	B30-R10000-****
B-489A	Polyester	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-490	Polyester	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-492	Polyester	-	-	-	-	-	●	-	-	-	-	-	-	-	-	-	-
B-494	Polyester	-	-	-	-	-	●	-	-	-	-	-	-	-	-	-	-
B-498	Repos Cloth	▲ UL	-	-	● UL	-	-	-	-	-	-	-	-	-	-	-	-
B-499	Nylon Cloth	▲ UL / CSA	-	● UL	-	-	-	-	-	-	-	-	-	-	-	-	-
B-509	Printable Magnetic	-	-	●	-	-	-	-	●	-	-	-	-	-	-	-	●
B-526	Photoluminescent Polyester	-	-	●	-	-	-	-	●	-	-	-	-	-	-	-	●
B-549	Polyester	-	-	●	-	-	-	-	●	-	-	-	-	-	-	-	●
B-551	Non-Adhesive Tag	-	-	●	-	-	-	-	●	-	-	-	-	-	-	-	●
B-569	Polyester	-	-	●	-	-	-	-	●	-	-	-	-	●	-	-	●
B-581	Repos Vinyl	-	-	●	-	-	-	-	●	-	-	-	-	-	-	-	●
B-584	Reflective	-	-	●	-	-	-	-	●	-	-	-	-	-	-	-	●
B-593	Polyester	-	-	●	-	-	-	-	●	-	●	-	-	-	-	-	-
B-595	Outdoor Vinyl	-	-	●	-	-	-	-	●	-	-	-	-	●	-	●	●
B-618	Polyester	-	● UL	● UL	-	-	-	-	-	-	-	-	-	-	-	-	-
B-717	Polyimide	-	-	● UL	-	-	-	-	-	-	-	-	-	-	-	-	-
B-718	Polyimide	-	-	● UL	-	-	-	-	-	-	-	-	-	-	-	-	-
B-719	Polyimide	-	-	● UL	-	-	-	-	-	-	-	-	-	-	-	-	-
B-724	Polyimide	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
B-727	Polyimide	-	-	● UL	-	-	-	-	-	-	-	-	-	-	-	-	-
B-728	Polyimide	-	-	● UL	-	-	-	-	-	-	-	-	-	-	-	-	-
B-729	Polyimide	-	-	● UL	-	-	-	-	-	-	-	-	-	-	-	-	-
B-777	Polyimide	-	-	●	-	● UL / CSA	-	-	-	-	-	-	-	-	-	-	-
B-854	ToughWash® Metal Detectable	-	-	●	-	-	-	-	-	-	-	-	-	-	-	-	-
B-855	ToughWash	-	-	●	-	-	-	-	-	-	-	-	-	-	-	-	-
B-7425	Polypropylene	▲	-	-	-	-	●	-	-	-	-	-	-	-	-	-	-
B-7425-AC	Polypropylene	▲	-	-	-	-	●	-	-	-	-	-	-	-	-	-	-
B-7569	Vinyl Film	-	-	●	-	-	-	-	●	-	-	-	-	-	-	-	-
B-7641	Polyolefin	-	-	●	-	-	-	●	-	-	-	-	-	-	-	-	-
B-7642	Polyolefin	●	-	-	-	-	●	-	-	-	-	-	-	-	-	-	-
B-7643	Polyurethane	-	-	●	-	-	-	-	-	-	-	-	-	-	-	-	-
B-8117	Black Polyester	-	-	-	-	-	-	-	-	-	▲ UL	-	● UL	-	-	-	-
B-8591	Outdoor Polyester	-	-	● UL	-	-	-	● UL	-	-	-	-	-	-	-	-	-
B-8591 SLV	Outdoor Polyester	-	-	-	-	-	-	● UL	-	-	●	-	-	-	-	-	-
B-8591 BLK	Outdoor Polyester	-	-	-	-	-	-	-	-	-	● UL	-	-	-	-	-	-

For further material compatibility related to UL/CSA, see pages 18-22 or refer to Brady Tech Data Sheet for complete material performance specifications

Printer Specifications

Model(s):	
Model name	BradyPrinter i5300 Industrial Label Printer
Media alignment	Center justified
Volume guidelines*	5,000+ labels per day. 5 days per week
Printhead / Printing Characteristics:	
Print resolution	300 dpi model 600 dpi model
Print method	Thermal transfer, direct transfer
Cutter type / Auto cutter	Auto cutter built-in (all models)
Print colour capability	Single colour
Print speed	up to 178mm / sec – die cuts (300 dpi) up to 254mm / sec – continuous (300 dpi) up to 76mm / sec – die cuts (600 dpi) up to 127mm / sec – continuous (600 dpi)
Print width (max, cross-web)	102mm
Print length (max, down-web)	1.5m
Print job interrupt options	Resume print job where pause or interruption occurs, or select specific label in job
Printhead replacement	Field replaceable (with same dpi only)
Print roller replacement	Field replaceable (T10 wrench required)
Print on demand	Yes
Print pause	Yes
Print job list on stand-alone printer	Yes - BradyWorkstation print jobs can be saved to printer for later on-printer selection and placement into a print queue. This function also write-protects the print jobs from unwanted editing.
Interface:	
Display type	Colour LCD touchscreen
Display size (diagonal)	178mm
Display resolution (H x W)	600 x 1024 pixels
Display languages	Bahasa Indonesia, Bahasa Melayu, Bulgarian, Chinese (simplified), Chinese (traditional), Croatian, Czech, Danish, Dutch, Estonian, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Slovakian, Slovenian, Spanish, Swedish, Turkish, Thai, Vietnamese
Display status bar	Installed ribbon and label part numbers, amount of supplies remaining, Wi-Fi connection, Bluetooth connection, receiving data icon, ready state / error state
Media Characteristics:	
Label width (cross-web)	6.35mm to 108mm (continuous linerless media) 6.35mm to 102mm (other media)
Label length (down-web)**	5mm minimum (die-cut media). 13mm minimum (continuous media)
Media roll o.d. (max)	109mm
Media roll core i.d.	n/a (media roll integrated into drop-in cartridge)
Media width (cross-web, including liner)	18mm to 108mm
Media thickness	0.061mm to 0.79mm max (label media) 1.8mm max (B-593 push-button media) 1.1mm max (heat-shrink sleeves)
Media roll winding	n/a
PrintSmart technology	Yes - Reads datachip on supplies for no-waste printing, requires no calibration, has pre-optimised energy and speed settings and features auto label setup in Brady software
Sensor and energy setting adjustments	No calibration required, no wasted labels, sensor; speed and heat settings are auto-set
Media loading / handling	Labels: In cartridge, drops into place, 15-second changeover Ribbon: In cartridge, snaps into place, 5-second changeover
Media parts offering	1,300+ stock parts and custom (made-to-request) parts. All B30- and B33- series parts are compatible in the BradyPrinter i5300
Media styles	All media is on an integrated cartridge roll with part data on the smart cell. Die-cut media, continuous media, tagstock liner-mounted, tagstock linerless, perforated materials, adhesive labels, heat-shrink sleeves size 24mm and larger (single- and double-sided with 2-pass print), self-laminating cable labels, cable ties and tags, raised panel push-button labels, rapido-style cable tags, PermaShield-style labels, pre-printed GHS labels, SFID outdoor-grade labels, direct thermal labels
Media material types	PE (polyethylene), PET (polyester), PET (metallised), PU (polyurethane), PVC (vinyl), PVF (polyvinyl fluoride), PVDF (polyvinylidene fluoride), PP (polypropylene), PI (polyimide), polyamide, polyether polyurethane (Heatex™), raised panel push-button material, paper, tamper-evident and tamper-resistant materials, 8-10 year outdoor vinyl, 10-hour glow-in-the-dark material, retroreflective labels, printable floor marking tape, nylon and vinyl cloth, wash-down materials, extreme temperature laboratory materials, slides / lab-staining materials, other materials not listed

Ribbon Characteristics:	
Ribbon length (max)	61m
Ribbon roll o.d. (max)	n/a (ribbon roll integrated into drop-in cartridge)
Ribbon roll core i.d.	n/a (ribbon roll integrated into drop-in cartridge)
Ribbon width (cross-web)	110mm
Ink side	n/a (ribbon integrated in cartridge — guaranteed correct orientation to printhead)
Software and Firmware:	
Label Creation Software	Brady Workstation (v4.12 or newer) and Brady Workstation apps (latest updates)
WHQL certified Windows® drivers	Windows 7, 8, 8.1, 10, server 2008, 2008 R2, 2012, 2012 R2, 2017
Printer command language	BPL – scripting commands for sending scripts to the printer
Connectivity:	
PC connection port	1 x USB 2.0 hi-speed device port
Serial port	No
Ethernet	1 x Ethernet 100 BASE-T
USB host ports	3 x USB 2.0 type A host port (1 front, 2 back)
SD card slot	No
Wireless	Wi-Fi 802.11b/g/n (wireless model only)
Bluetooth	Internal Bluetooth module (future functionality)
Electronics:	
Processor	32-bit 800 MHz clock rate
Memory (RAM)	512 MB
Data storage (IFFS)	195 MB
Internal battery	For internal date and time (RTC)
Data storage when power Off	Yes
Physical / Operational Characteristics:	
Dimensions (closed) (HxWxD)	279mm x 284mm x 401mm
Weight (empty)	14kg
Power supply	101-240 VAC, 50/60 Hz, 3.5A
Power consumption	20W standby / 80W operating / 200W max
Operating environment	10 - 40°C / 10 - 85% RH non condensing
Storage environment	-20 - 50°C / 15 - 90% RH non condensing
Transport environment	-20 - 50°C / 15 - 90% RH non condensing
Agency approvals	CE, FCC class A, cUL. Contact Brady for up-to-date list of environmental compliance information and agency approvals and / or marks covering over 75 countries (awarded or applied for)
Fonts and Graphics:	
Character sets	ASCII character set
Font types (resident)	Arial, Courier New, MS Gothic, Malgun Gothic, MingLiU, SimSun, Tahoma, Times New Roman, Trebuchet MS, Verdana
Font types (storable to printer)	TrueType fonts storable to printer via jump drive
Font attributes	Bold, italic, underlined
Graphic elements	Arrow, line, rectangle, square, circle, ellipse, diamond, dot, star, triangle, seal, cross
Graphic formats	BMP, GIF, JPEG, PNG
Barcodes:	
Barcode symbologies — 2D	Aztec, DataMatrix, QR Code, PDF-417
Barcode attributes	Sizing: variable in height and ratio Rotation: 0°, 90°, 180°, 270° human-readable and human-readable location density
Barcode symbologies — linear	Code 39, Code 93, Code 128 A, B, C, Codabar, EAN-8, EAN-13, JAN-8, JAN-13, HIBC, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, MSI Plessey, UPC-A
Options / Accessories:	
Replacement printheads	User replaceable (to same dpi)
Replacement print rollers	115 mm width, user replaceable (T10 wrench required)
Auto cutter	Built-in

* General volume levels for directional model comparison purposes only. Assumes basic text on 25mm x 51mm polyester labels. Actual results vary depending on combination of material, burn and speed settings, label content, ambient temperature and length of print run.
 **User should test to the application. Print performance on small parts or parts smaller than a printer's minimum label dimension spec is dependent on multiple factors including print speed, quantity in print run, heat setting, and the size / layout of the printed elements.
 Windows® is a registered trademark of Microsoft Corporation.



**We identify and protect premises,
products and people.**

For more information or to learn more about our innovative products, visit [BradyID.com.au](https://bradyID.com.au) or call 1800 620 816.

Brady Australia Pty Ltd
Customer Service: 1800 620 816
bradyID.com.au