

BradyPrinter i7100 & BradyPrinter PR Plus Comparison

Brady's reliable, heavy-duty, high volume workhorse printer is getting even better. Take a look at the enhancements of the new BradyPrinter i7100 from its predecessor the BradyPrinter PR Plus.







| Key Features | PR-Plus | i7100 NEW |
|--|---|--|
| Touch Screen | Νο | Yes, ultra-intuitive colour touch screen to quickly and easily adjust printer settings and access on board training videos |
| Media Alignment | Left-aligned | Center-aligned for better print accuracy and to reduce ribbon wrinkling |
| Material Loading | Metal unfoldable cover | Bi-foldable cover in impact-proof plastic results in a smaller system footprint Standard anti-static brush on non-peel BradyPrinter i7100 |
| Small Core Media Roll (I-inch core) | Compatible | Not compatible |
| Print Head Wear | Standard | Reduced print head wear with hardened sharp-edge print head & narrow width interchangeable platen rollers |
| Print Resolution/Models | 101.6mm 300dpi 101.6mm 600dpi 152.4mm 300dpi | 101.6mm 300dpi 101.6mm 600dpi |
| Max. Print Speed | Up to 254mm/sec | Up to 299.72mm/sec to print your labels in no time |
| Connectivity Options | 2 x USB, serial, ethernet | 4 x USB, serial, ethernet, options for WLAN, bluetooth, I/O connection port |
| Minimum Label Dimension | 5.08mm | 3.17mm (print job dependent) |
| Max. Label Width | 115.82mm | 109.98mm |
| Max. Liner Width | 119.88mm | 114.04mm |
| Max. Print Width | 105.41mm | 105.66mm |
| Max. Ribbon Roll | 80.01mm o.d. | 68.07mm o.d. (984 ft max length) |
| Processor 32 bit Clock Rate | 266 MHz | 800 MHz to be faster and more powerful, reducing buffer overruns |
| Memory | 64 MB (RAM) - 8 MB (Flash) | 256 MB (RAM) - 50 MB (Flash) - Slot for SD memory card (up to 512 GB) |
| Software Compatibility | LabelMark, Windows based driver for 3rd party software use | Brady Workstation (free download) & Workstation Apps, Brady LabelMark software (v6.5.0.9 or higher) |
| Accessories | • Auto cutter • Perf cutter • Present sensor | Auto cutter Perf cutter Present sensor WLAN USB stick I/O connection port Interchangeable narrow width rollers to (improve print head life) |
| Size | 241.80mm W x 273.81mm H x 445.77mm D | 251.96mm W x 287.78mm H x 459.99mm D |
| Weight | 8.48kg | 9.97kg |





