



Donaldson Part No: **P902973**

Ideal for all low flow applications up to 220lpm

Maximum working pressure: 150 psi (10.3 bar)

Contaminated diesel can cause equipment downtime and costly repairs. One of the most common sources for contaminant is the diesel storage tank.

Many sites have aging bulk and transportable fuel tanks with obsolete filtration and poor quality breathers.

Donaldson's Bulk Fuel tank Kit contains all the necessary components all of the necessary components to upgrade existing diesel fuel tanks with modern filtration technology.

FEATURES & BENEFITS

- Simple spin-on design for ease of service
- Filtration efficiency 99.5% removal of particles 10 micron or larger ($\beta_{10} = 200$)
- Water absorbing media
- Suitable for gravity fed or pumped diesel applications
- T.R.A.P.™ Breather included with kit to help remove moisture and airborne contaminant, replaces desiccant and silica gel style breathers
- Kit includes adapters for head and breather to connect to BSP fittings
- Not suitable for petrol

SPECIFICATIONS

Image	Part No	Description	Qty
	P564147	Filter Head 1 5/8" SAE-20 ports	1
	P506076	Male 1 5/8" SAE to 1" BSPT Adapter	2
	P574959	Dimensions: OD 128mm, Length 271mm Efficiency $\beta_{10} = 200$ (99.5% @ 10 micron) With water absorbing media	1
	P563298	Pressure Gauge If used on suction side of pump gauge measures filter restriction. Not required in gravity fed applications	1
	P564669	T.R.A.P.™ Breather 1" NPT male thread Dimensions: OD 114.3mm, Height 115.1mm Efficiency $\beta_3 = 50$ (98% @ 3 micron)	1
	POL503	1" Female BSP Socket Attaches T.R.A.P. Breather to male 1" BSP threads	1

