



SANKI

SK52 Industrial Widebody Series

Gear pumps & Dispensers



- Customer Friendly Operation
- Precise Metrology Equipment
- High Performance Hydraulic & Electronic Components
- High Quality Explosion Proof Motors
- Specially designed reusable (cleanable) fuel filtering cartridges
- Available as a dispenser or pump
- Suitable for both diesel and adblue
- Works well in harsh Australian conditions
- NMI Approved
- Flow rates 40-130LPM
- Options
 - Remote Display Option
 - Single Product Integrated ATG Option
 - Upload pump and Skid

Technical Specifications

Accuracy	± 0.25%
Flow Rate	40 - 130L/min
Ambient Temperature	-25°C ~ +55°C
Relative Humidity	0% - 95%
Unit Noise Rate	< 70dB
Inlet Vacuum Rate (Suction Pump)	≥ 54kPa
Communication Protocols Supported	Sanki RS485, NZPP (PEC/Compac), Gilbarco*
Power Supply	AC 220V, AC380V (-15% ~ +10%)
Sale Digits	7 (0.00 - 99999.99) Decimal Adjustable
Volume Digits	6 (0.00 - 9999.99) Decimal Adjustable
Unit Price Digits	5 (0.00 - 999.99) Decimal Adjustable
NMI Approval Number	5-6A-231

*Contact us to confirm controller compatibility



Models

Model	Type	Notes	Nozzles	Products	Flow Meters	Main Displays
SK52GF111B-80	Pump	Single Hose 80LPM	1	1	1	1
SK52GF222B-80	Pump	Dual Hose 80LPM	2	2	2	2
SK52QF111B-80	Dispenser	Single Hose 80LPM	1	1	1	1
SK52QF222B-80	Dispenser	Dual Hose 80LPM	2	2	2	2
SK52QF111A-130	Dispenser	Single Hose 130LPM	1	1	2	1
SK52QF222A-130	Dispenser	Dual Hose 130LPM	2	2	4	2
SK52QF222-AD	Dispenser	Dual Hose Adblue 40LPM	2	1	2	2
SK52QF222-ADA	Dispenser	Adblue 40LPM / Diesel 110LPM	2	2	3	2

