

ATEX ZONE 1 FUEL TRANSFER

Piusi Panther EX 56

Explosion protected version of the Panther 56, certified for petrol, diesel and kerosene in classified hazardous areas. Cast iron body, continuous duty motor, integrated bypass valve. Supplied as pump only.



56 L/min

Flow rate at 230V 50Hz, 14.7 GPM

ATEX

II 2 G Ex d IIA T4 Gb, Zone 1 and Zone 2

S1

Continuous duty with thermal protection

SPECIFICATIONS

PART NUMBER

F00580030

HAZARDOUS AREA MARKING

II 2 G Ex d IIA T4 Gb

FLOW RATE

56 L/min (14.7 GPM)

INLET / OUTLET

1" BSP

POWER SUPPLY

230V / 50Hz AC, 500 W, 2.3 A

FLUIDS

Diesel, petrol, kerosene

CONSTRUCTION AND FEATURES

- Cast iron body, sintered steel rotor, technopolymer vanes, Viton seals, steel shaft
- Self priming vane pump, integrated bypass valve, magnetic ON/OFF switch
- Removable feet supplied non mounted, for permanent bolt down installation
- 12.4 kg, packed 400 x 240 x 300 mm, made in Italy, 12 month warranty
- ATEX certification must be maintained across the whole installation