

FLUID HANDLING · NOZZLE ACCESSORIES

SANKI Nozzle Holster

A polymer nozzle holster with an integrated low voltage magnetic switch for automatic pump control. The explosion-proof, normally open switch is hazardous-area rated for fuel dispensing, suitable for diesel and for flammable liquids when fitted with an intrinsically safe barrier.


T6

ATEX and IECEx certified switch

50 VDC

Maximum rating at 0.5 A

385 mm

Overall height, 110 W x 250 D

SPECIFICATIONS

PART NUMBER

NH

HAZARDOUS AREA MARKING

II 2G Ex mb IIC T6 Gb

SWITCH TYPE

Explosion-proof magnetic, normally open

CERTIFICATION

INERIS 16ATEX0035X, IECEx CNEX 16.0003X

ELECTRICAL RATING

50 VDC, 0.5 A maximum

DIMENSIONS

110 W x 385 H x 250 D mm

AMBIENT TEMPERATURE

-40 to +75 °C

INSTALLED DEPTH

140 mm

FEATURES

- Poly nozzle holster with an integrated low voltage nozzle switch assembly
- Explosion-proof magnetic switch, normally open, for automatic pump control
- Hazardous area rated II 2G Ex mb IIC T6 Gb, ATEX and IECEx certified
- 50 VDC, 0.5 A maximum rating, ambient range -40 to +75 °C
- Suitable for diesel; petroleum requires an intrinsically safe barrier