

SKU GO-FPA12V · GO-FPM12V

GO Fill 12V Diesel Pump Kit 40 L/min

Portable 12V DC diesel pump kit with a self-priming rotary vane pump, carry handle and 2 m battery cable with alligator clips. Supplied with 4 m hose, nozzle and fittings, in automatic or manual nozzle versions.



40 L/min

Free flow

12V DC

Battery powered

30 min

Duty cycle on, then off

Key features

- Self-priming rotary vane pump with IP55 protection
- Built in by-pass valve
- Carry handle, 2 m power cable with alligator clips
- 19 mm x 4 m delivery and suction hose, cut to suit
- Automatic (GO-FPA12V) or manual (GO-FPM12V) nozzle
- For diesel and kerosene only, not petrol rated



Technical data

SPECIFICATION	VALUE
Order codes	GO-FPA12V (automatic nozzle), GO-FPM12V (manual nozzle)
Supplier codes	L-FPA12V (automatic nozzle), L-FPM12V (manual nozzle)
Flow rate	40 L/min (free flow)
Voltage	12V DC
Fuse	25 A
Duty cycle	30 min on, 30 min off
Inlet / outlet	3/4" BSP (F)
Hose	19 mm (3/4") x 4 m, cut to suit
Power cable	2 m with alligator clips
Protection	IP55
Operating temperature	-20 to +60 °C
Max by-pass time	3 minutes
Suitable fluids	Diesel and kerosene only

In the box

12V pump unit, 2 m power cable with alligator clips, delivery and suction hose (cut to suit length), delivery nozzle and fittings.

Installation and use

Suction hose 3/4" I/D minimum and 2 m maximum; above 2 m and below 3 m of suction height a foot valve may be needed. The motor is not explosion proof, so do not install where flammable vapours are present.

