

SKU GO-HFFPA12V · GO-HFFPM12V

GO Fill 12V High Flow Diesel Pump Kit 56 L/min

12V DC high flow diesel pump kit with a self-priming rotary vane pump and 2 m battery cable with alligator clips. Supplied with 4 m hose, nozzle and fittings, in automatic or manual nozzle versions.



56 L/min

Free flow

12V DC

Battery powered

1" BSP

Inlet and outlet

Key features

- Self-priming rotary vane pump with IP55 protection
- Built in by-pass valve
- 2 m power cable with alligator clips, 40 A fuse
- 19 mm x 4 m delivery and suction hose, cut to suit
- Automatic (GO-HFFPA12V) or manual (GO-HFFPM12V) nozzle
- For diesel and kerosene only, not petrol rated



Technical data

SPECIFICATION	VALUE
Order codes	GO-HFFPA12V (automatic nozzle), GO-HFFPM12V (manual nozzle)
Flow rate	56 L/min (free flow)
Voltage	12V DC
Fuse	40 A
Duty cycle	30 min on, 30 min off
Inlet / outlet	1" BSP (F)
Hose	19 mm (3/4") x 4 m, cut to suit
Power cable	2 m with alligator clips
Protection	IP55
Suitable fluids	Diesel and kerosene only

In the box

12V pump unit, 2 m power cable with alligator clips, delivery and suction hose (cut to suit length), delivery nozzle and fittings. The pump is not sold separately.

