IN-LINE METERS · 3/4 IN

IM20 in-line meters

3/4 in in-line meters for tracking oil and antifreeze in the supply line, at a tank outlet or on a reel inlet. The IM20P adds petroleum and synthetic oils including gear oil and ATF.



76 L/min
Maximum flow rate

1,500 psi
Maximum working pressure

3/4 in
NPT in-line connection

Features

- Mounts in the line, not at the nozzle
- Indoor and outdoor rated
- IM20P for motor, gear and ATF oils plus antifreeze

PUBLISHED FIGURES

Technical specifications

Published figures for IM20 meters.

Specifications

SPECIFICATION	VALUE
IM20 fluids	**Oil, antifreeze**
IM20P fluids	**Petroleum and synthetic oils (motor, gear, ATF), antifreeze**
Maximum working pressure	**103.4 bar (1,500 psi)**
Maximum flow rate	**76 L/min (20 gpm)**
Connection	**3/4 in NPT (19 mm)**
Intended use	**Indoor and outdoor**

LEAD TIMES

Most models are held in Australia. Some ratios and drum sizes are made to order and arrive by air or sea freight. Call for a delivery date before ordering.

P 07 3204 2240 E sales@goind.com.au W goind.com.au

PART NUMBERS

Ordering information

Quote the part number when ordering. Prices, stock and delivery times from GO Industrial on 07 3204 2240 or sales@goind.com.au.

Models and parts

PART NUMBER	DESCRIPTION
25C841	**IM20 in-line meter, 3/4 in**
133480	**IM20P in-line meter, 3/4 in**

ORDERING

GO Industrial supplies the full range Australia-wide. Call 07 3204 2240 or email sales@goind.com.au with the part number for price and delivery.