LINE MARKING SPRAY TIPS · RAC 5 · YELLOW

LineLazer RAC 5 tips (LL5)

Reversible line marking tips for waterborne and solvent traffic paint. The tip number gives the line width and the orifice size.



51-305 mm
Line width range

0.013-0.055 in
Orifice range

152 mm
Gun stand-off

Features

- Sharp line edges with even paint film across the line
- Reverse the tip to clear a blockage without removing it
- Fits the RAC 5 HandTite guard 243161
- Size stamped on the handle for quick checks

P 07 3204 2240 E sales@goind.com.au W goind.com.au

PUBLISHED FIGURES

Technical specifications

Read the tip number LL5 W OO. W sets the line width at a 152 mm stand-off, OO is the orifice in thousandths of an inch.

Specifications

SPECIFICATION	VALUE
LL52xx	**51 mm line**
LL53xx	**102 mm line**
LL54xx	**102 to 204 mm line**
LL56xx	**204 to 305 mm line**
0.019 in orifice	**1.47 L/min water at 138 bar**
0.021 in orifice	**1.79 L/min water at 138 bar**
0.025 in orifice	**2.54 L/min water at 138 bar**
0.027 in orifice	**2.96 L/min water at 138 bar**
0.033 in orifice	**4.42 L/min water at 138 bar**
Guard	**RAC 5 HandTite 243161, 7/8 in thread**
Seal	**OneSeal, supplied with the tip**

TIP SIZE AND GUN COUNT

Check the machine's maximum tip for the number of guns running. A LineLazer V 3900 takes up to 0.025 in on two guns.

P 07 3204 2240 E sales@goind.com.au W goind.com.au

PART NUMBERS

Ordering information

Quote the part number when ordering. Prices, stock and delivery from GO Industrial on 07 3204 2240 or sales@goind.com.au.

Models and parts

PART NUMBER	DESCRIPTION
LL5213 to LL5219	**51 mm line, 0.013 to 0.019 in**
LL5315 to LL5355	**102 mm line, 0.015 to 0.055 in**
LL5417 to LL5443	**102 to 204 mm line, 0.017 to 0.043 in**
LL5621 to LL5643	**204 to 305 mm line, 0.021 to 0.043 in**
LL5319	**102 mm line, 0.019 in**
LL5421	**102 to 204 mm line, 0.021 in**
LL5425	**102 to 204 mm line, 0.025 in**
243161	**RAC 5 HandTite guard**

REPLACE WORN TIPS

Replace a tip when the line has narrowed by a quarter from new. A worn tip lays more paint per metre and changes bead embedment.