PRESET DISPENSE METERS · OILS, ATF AND ANTIFREEZE

PM Series preset meters

Electronic preset meters that stop the dispense at the set volume. For petroleum and synthetic oils (motor, gear and ATF) and antifreeze, indoor or outdoor.



76 L/min
Maximum flow rate

1,500 psi
Maximum working pressure

Preset
Stops at the set volume

Features

- Set the volume and the meter shuts off the dispense
- PM8 for 1/2 in lines, PM20 for 3/4 in lines
- Flex or rigid extensions
- Indoor and outdoor rated

PUBLISHED FIGURES

Technical specifications

Published figures for PM Series meters.

Specifications

SPECIFICATION	VALUE
Fluids	**Petroleum and synthetic oils (motor, gear, ATF), antifreeze**
Type	**Preset**
Maximum working pressure	**103.4 bar (1,500 psi)**
Maximum flow rate	**76 L/min (20 gpm)**
Intended use	**Indoor and outdoor**
PM8 inlet	**1/2 in NPT (13 mm)**
PM20 inlet	**3/4 in NPT (19 mm)**

LEAD TIMES

Most models are held in Australia. Some ratios and drum sizes are made to order and arrive by air or sea freight. Call for a delivery date before ordering.

P 07 3204 2240 E sales@goind.com.au W goind.com.au

PART NUMBERS

Ordering information

Quote the part number when ordering. Prices, stock and delivery times from GO Industrial on 07 3204 2240 or sales@goind.com.au.

Models and parts

PART NUMBER	DESCRIPTION
273157	**PM8 preset meter, 1/2 in, flex**
273156	**PM8 preset meter, 1/2 in, rigid**
25U085	**PM8 preset meter, 1/2 in, rigid**
273167	**PM20 preset meter, 3/4 in, rigid**
273168	**PM20 preset meter, 3/4 in, flex**

ORDERING

GO Industrial supplies the full range Australia-wide. Call 07 3204 2240 or email sales@goind.com.au with the part number for price and delivery.