

SKU RVP-01

MACNAUGHT RVP-01 Rotary Vane Hand Pump

A die cast aluminium rotary vane hand pump for diesel, kerosene and lubricating oils up to SAE 90, delivering up to 20 L/min in both directions. Suits 60 to 205 L drums with its 2 inch BSP sliding bung adaptor.

**20 L/min**

Maximum flow, both directions

SAE 90

Maximum oil viscosity at 20 °C

1.8 m

Delivery hose with anti-kink spring

Key features

- Self priming, primes by rotating the handle
- Rotary action pumps in both directions
- Lockable handle to prevent theft of fluid
- Nozzle holder sets the nozzle in a non siphoning position
- Three piece suction tube adjusts to different drum heights
- Fully repairable, seal kit RVP-1K available



Technical data

SPECIFICATION	VALUE
Order code	RVP-01
Type	Hand operated rotary vane pump
Flow rate	Up to 20 L/min
Fluids	Diesel, kerosene, lubricating oils
Maximum viscosity	SAE 90 at 20 °C
Maximum suction head	1.2 m
Maximum discharge	2 m
Delivery hose	1.8 m PVC / nitrile, anti-kink spring
Bung adaptor	2 inch BSP, sliding
Suction tube	Three piece, adjustable
Drums and tanks	60 to 205 L drums, tanks up to 0.9 m deep
Body	Die cast aluminium
Wetted components	Aluminium, steel, zinc, nitrile rubber
Seal kit	RVP-1K

In the box

RVP-01 hand operated rotary vane pump, 1.8 m delivery hose with anti-kink spring, 2 inch BSP sliding bung adaptor, three piece suction tube and instruction manual.

Installation and use

Not suitable for petrol or most biodiesel blends. Chemicals, solvents or water will cause premature failure of seals and o-rings.

