

SKU SK10GF111B

SANKI SK10 Single Hose Diesel Fuel Dispenser

Single hose diesel unit with its own internal gear suction pump, approved for trade under NMI pattern approval 5/6A/231 variant 6 with the same operating components and field of operation as the approved pattern.


50 L/min

NMI approved Qmax

Class 0.5

NMI accuracy class

NMI 5/6A/231

Pattern approval, variant 6

Key features

- Internal gear suction pump (GF, suffix B)
- Sanki GP-50 pump, strainer and gas separator
- Sanki FM-500 positive displacement meter
- Delivery stops if excess air or vapour is detected
- Displayed delivery is retained on power failure
- Must be resealed and certified in situ for trade use



Technical data

SPECIFICATION	VALUE
Model	SK10GF111B
Fluid	Diesel only
Pump	Internal gear, suction pump (GF, suffix B)
NMI approval	NMI 5/6A/231, variant 6
Max flow rate (Qmax)	50 L/min
Min flow rate (Qmin)	5 L/min
Min measured quantity	2 L
Liquid pressure	100 to 300 kPa
Liquid viscosity	0.5 to 20 mPa.s at 20 °C
Liquid temperature	-10 °C to 50 °C
Ambient temperature	-25 °C to 55 °C
Accuracy class	0.5

Installation and use

For trade use the unit must be resealed in situ and have its initial calibration and certification carried out.

