



AQUAMAX™

Graco's Complete Line of Professional Pressure Washers



www.graco.com

AQUAMAX ADVANTAGES

- Highest performing **Honda®** and **Briggs & Stratton engines** for the toughest professional cleaning jobs: surface preparation, chemical treatment, horizontal cleaning, etc.
- **QuikDisconnect™ tips and chemical injector kit**, very easy to exchange, covering widest range of applications.
- Tubed pneumatic tyres, gun and hose holder for easy transport and storage.

Professional Cleaning Applications

**AQUAMAX™ 2730 DD - AQUAMAX™ 3030 DD - AQUAMAX™ 3540 DD -
AQUAMAX™ 4043 BD - AQUAMAX™ 3540 GHW**



AQUAMAX™

Pressure Washers for professionals: extreme reliability and performance

This guide is designed to help you select the right solution for your pressure washing needs.

PRESSURE WASHERS

Our compact direct drive pressure washers offer enough horsepower to tackle most cleaning and preparation jobs.

The belt drive pressure washers are Graco's top-of-the-line cold water units, designed to tackle the toughest cleaning jobs. They offer features that are required in severe-duty applications.

And if cold water "just won't remove the dirt," we now offer a hot water pressure washer in our range: the AquaMax™ 3540 GHW.

No job is too big for our hot water pressure washer!

When choosing Graco, you can be assured that you are choosing the highest quality product ...



QuikDisconnect™ Tips

Maximize your cleaning power by selecting the tip that best matches the maximum pressure and flow of your pressure washer from the chart at the right. The QuikDisconnect features make it very easy to exchange tips.



High Pressure Gun and Hose

15 meter hose x 3/8" with quick connections, swivel and bend restrictors. Professional-grade insulated trigger gun comes with insulated lance (dual on hot gas)

Diesel Fired Burner

- Burner can run diesel or kerosene
- Maximum outlet temperature of 93°C (200°F) [65°C = 150°F rise]
- Easy coil drain helps prevent freezing in cold weather
- High quality fuel filter/water separator ensures clean fuel supply (Hot Water version only).

Double Belt Drive

For durability and power (AquaMax 4043 BD only)



ELECTRIC START



Hot Direct drive



Cold Belt Drive



Cold Direct Drive

Materials & Applications

Use Graco pressure washers for the most demanding jobs: commercial buildings, bridges and water towers. The AquaMax 3540 GHW hot water pressure washer is for applications where cold water just won't remove the dirt. With hot water you can effectively clean grease, oil or any other heat reactive substance.

You can maximize your cleaning power by selecting the tip that best matches the maximum pressure and flow of your pressure washer from the chart on the opposite page.





Chemical Injector Kit

120 cm suction tube, built-in on direct drive cold water models, modular on other models

Rugged Steel Frame
Reinforced powder coated steel frame with center lift hook
- Gun and hose holder for easy transport and storage





GOOD TO KNOW



ROTATING AND OSCILLATING TIPS

Rotating and oscillating tips increase your cleaning power and decrease your cleaning time. They offer 0° spray impact with 25° coverage. Tips include a filter with quick connection and offer heavy-duty components for long life and reliability. Can be used on pavements, driveways, vehicle tracks, muddy areas, old peeling paints and concrete surfaces.



Gardena® Water Hose Connection

Tube Pneumatic Tyres
roll easily over rough terrain and withstand the harsh jobsite environment

Pump
Triplex piston and ceramic plungers with continuously lubricated packings, for ultimate performance

Thermal Relief Valve
protects the pump from overheating and prevents excessive packing wear

www.graco.com

! TIP

CHEMICAL INJECTOR

The chemical injector kit sucks the chemical component from a bucket and mixes it with the water flow. To apply detergent for misting and rinsing, we advise to use the special (black) low pressure tip.

Tip Selection Chart

| | 0° | 15° | 25° | 40° | CHEMICAL |
|------------------------|---|--|--|---|--|
| TIP DESCRIPTION | Cutting | Chiseling | Flushing | Washing | Chemical |
| USE | Delivers a concentrated stream that can gouge or cut. | Works like a scraper when used at a 40° angle. | Most common nozzle for general cleaning. | Wide spray for washing or rinsing a large area. | Low pressure nozzle for use with detergent injector. |
| TYPICAL JOBS | Removes stains from concrete or other hard surfaces. | Strips paint; removes grease, mildew and stains. | Cleans dirt from outer walls, pavements, outdoor furniture, etc. | Washes vehicles, windows, aluminium cladding and other delicate surfaces. | Applies detergent, mists and rinses. |





AQUAMAX™ Accessories

Get the most out of your equipment, use our professional accessories

Improve your spraying quality

Guns

Professional grade gun, 350 bar
16F029 With 90 cm lance and vented handle



Tips

198012 Rotating tip - 276 bar
198014 Rotating tip - 345 bar
198013 Oscillating tip - 345 bar



| ORIFICE SIZE | 0° | 15° | 25° | 40° | SET OF 4 TIPS (0°-15°-25°-40°) |
|--------------|--------|--------|--------|--------|--------------------------------|
| 3.0 | 805535 | 805536 | 805537 | 805538 | 244768 |
| 3.5 | 805539 | 805540 | 805541 | 805542 | 244769 |
| 4.0 | 805543 | 805544 | 805545 | 805546 | 800708 |
| 4.5 | 805547 | 805548 | 805549 | 805550 | 800709 |
| 5.0 | 805551 | 805552 | 805553 | 805554 | 800710 |
| 5.5 | 805555 | 805556 | 805557 | 805558 | 800711 |



Wand Extension 276 bar

116564 Telescoping - 5.5 m

Non-Marking Hose

244783 For 2730 DD, 3030 DD, 3540 DD, 4035 BD and 4043 BD: 15 m x 3/8" non-marking hose with quick disconnects, 280 bar



Wet Sandblasting

244766 Kit, 280 bar: fittings, couplers, clamps, adapters, housing, sealant and hose assembly (tip not included)
800031 Sand saver adjustable valve



Sand Blast Tip

805313 for 2730 DD
805316 for 3030 DD & 3540 DD
805321 for 4043 BD



Horizontal Surface Cleaner

116562 280 bar



Couplers

801009 1/4" coupler for wand extensions
801568 3/8" OD(m) x 3/8" npt(f) stem
801569 3/8" OD(f) x 3/8" npt(f) coupler

Fluids

246377 Pump oil, 1 liter
Use only with triplex plunger pumps

AQUAMAX

READY TO CLEAN

All units are shipped complete with 15 m x 3/8" high-pressure hose, heavy duty (belt driven) gun with vented handle, wand* and QuickDisconnect™ fittings, 4 standard QuickDisconnect coloured tips, RotoBlast tip, Gardena® water connection, chemical injector kit with 1.2 m tube, general pump with triplex piston and ceramic plunger, thermal relief valve, electrical start (belt driven only).

* The AquaMax 3540 GHW has a dual lance.

Find this unit at:

Specifications



| | AquaMax 2730 DD | AquaMax 3030 DD | AquaMax 3540 DD | AquaMax 4043 BD | AquaMax 3540 GHW |
|----------------------------------|--------------------|--------------------|--------------------|--------------------|---------------------|
| Part Numbers: | 262318 | 262320 | 262322 | 262326 | 262314 |
| Engine Type | DD Honda® | DD Honda® | DD Honda® | BD B&S | DD Honda® |
| Engine Output | 200 cm³ | 270 cm³ | 390 cm³ | 480 cm³ | 390 cm³ |
| Max. Pressure - bar (psi) | 190 (2700) | 210 (3000) | 245 (3500) | 280 (4000) | 245 (3500) |
| Fuel Tank Capacity - liter | 3.6 | 6.0 | 6.5 | 8.5 | 7.5 |
| Weight - kg (lb) | 40 (85) | 60 (130) | 65 (140) | 110 (240) | 195 (430) |
| Professional Grade Gun - cm (in) | 90 (36) | 90 (36) | 120 (48) | 120 (48) | 120 (48) |
| Tips | Orifice | | | | |
| | 3.0 | 3.5 | 4.0 | 4.0 | 3.5 |
| | 0° | 805535 | 805539 | 805543 | 805539 |
| | 15° | 805536 | 805540 | 805544 | 805540 |
| | 25° | 805537 | 805541 | 805545 | 805541 |
| | 40° | 805538 | 805542 | 805546 | 805542 |
| | Chemical | ✓ | ✓ | ✓ | ✓ |
| | Injector | 805634 | 805634 | 805634 | 805404 |
| | RotoBlast Tip | ✓ | ✓ | ✓ | ✓ |