



**TOUGHTTEK® F800e**

Redefining the High-output Fireproofing Market

## Switch to a Higher Output Fireproofing Pump

Designed with Graco's patent-pending piston pump technology and an efficient direct drive motor, the ToughTek F800e packs a powerful punch without drawing a lot of power. Spray up to 40 bags an hour from a pump that plugs into any standard 240V, 30A outlet.

Graco's ToughTek F800e fireproofing pump is setting a new standard in the industry by keeping your operation moving quickly and efficiently from one jobsite to another.

### Benefits

- **High performance** – Get the job done sooner and pump up to 40 bags an hour
- **Lightweight and portable** – Smaller and lighter than comparable high performance pumps
- **Plug and play** – Only requires a standard 240V, 30A single-phase power source
- **Less downtime** – Longer life from piston pump seals (compared to rotor stator pumps) with less maintenance
- **Easy maintenance** – Tool-less disassembly of outlet manifold and pump components to keep your pump up and running from one job to another

### Ordering Information

#### Bare Systems

- 25M800 F800e bare
- 25M802 F800e bare, w/ low power kit

#### Packages

Include 200 ft (60 m) hose, Pole applicator and required adapters

- 25M810 F800e pkg
- 25M812 F800e pkg, w/low power kit

## Maneuver Around a Jobsite with Ease

As sites get smaller and more compact, there is less room for materials and equipment. Weighing only 385 lbs, this mid-size pump has a smaller footprint than competitive pumps, making it easy to get on and off a service elevator, push through doorways or move around a jobsite.

#### Low Power Requirements

- 230V, 30A, 1-PH
- Optional: (2) 120V, 15A, 1-PH

#### Lightweight Molded Hopper

- 41 gal capacity
- Optimized design, with bottom-drain, for smooth material flow

#### Tool-less Outlet Manifold

- Allows for easy disassembly and maintenance

#### Next Generation Piston Pump Technology

- Spray up to 40 bags an hour
- All stainless steel design
- Improved captured seal design
- Tool-less disassembly
- Rated to 600 psi

#### Direct Drive Brushless Motor

- 4.5 hp
- Compact and maintenance free
- High performance drive train

#### Easy-to-use Control Box

- Standard remote start/stop
- Variable speed for operator control
- Includes troubleshooting error codes

#### 2 inch Male Camlock Outlet

- Plug and play with existing large camlock hoses

#### Quick Disconnect Inlet Clamps

- Remove in seconds for easy cleaning of inlet assembly



→ **Contact us today!**

Email [toughtek@graco.com](mailto:toughtek@graco.com) to learn more or have a Graco representative contact you.

