

Extensions

Extended Reach Tools

Graco's full line of Extended Reach Tools are ideal for hard-to-reach areas like soffits, stairways and vaulted ceilings. Extend your range and spray more efficiently without ladders or scaffolding.

DESCRIPTION **PART #**
3 ft Pole Gun (0.9 m) 287023

MAXIMUM WPR
3600 (248 bar, 24.8 MPa)

DESCRIPTION **PART #**
6 ft Pole Gun (1.8 m) 287024

MAXIMUM WPR
3600 (248 bar, 24.8 MPa)

DESCRIPTION **PART #**
CleanShot Valve 287030

MAXIMUM WPR
3600 (248 bar, 24.8 MPa)

REPAIR KIT
Valve - 244162
Swivel - 244363



3 ft Pole Gun Shown

Features

Pole Gun

- ▶ For unmatched spraying performance in high or recessed areas
- ▶ Provides better spray control and less fatigue
- ▶ Balanced design; no excessive weight at the end of pole

CleanShot Shut-Off Valve

- ▶ Unique needle valve shuts fluid off at the tip for a clean pattern – no spitting
- ▶ 180° tip swivel provides versatility when spraying walls and ceilings
- ▶ Pressure-actuated – operates at a minimum of 700 psi (4.8 MPa, 48 bar)

Contractor In-Line Valve

- ▶ Can be used with other extended reach tools such as Heavy-Duty Extensions and Telescoping Extensions for Pressure Rolling
- ▶ Provides a straight connection to extensions for the most optimal rolling position
- ▶ In-handle paint filter and built-in swivel connection for top spraying performance
- ▶ Ability to rotate 180° allows spraying in any position

Pole Gun Extensions

- ▶ Use with Contractor In-Line Valve and the CleanShot Shut-Off Valve to create different length pole guns
- ▶ Smaller diameter tube is lightweight and can be used for interior pressure rolling
- ▶ Ability to attach directly to an airless spray gun – order 45° adapter 224399 for increased comfort while rolling



CleanShot Shut-Off Valve (287030)



Contractor In-Line Valve (244161)

Extended Reach Accessories



Pole Gun Extensions

Maximum WPR: 3600 psi, (248 bar, 24.8 MPa)

- ▶ Use with Contractor In-Line Valve and the CleanShot Shut-Off Valve to create different length pole guns
 - ▶ Thread Size: 7/8 in (22 mm)
- | | |
|--------|--------------|
| 244163 | 3 ft (0.9 m) |
| 244164 | 6 ft (1.8 m) |



RAC X Tip Extensions

Maximum WPR: 4050 psi, (280 bar, 28.0 MPa)

- ▶ Includes: RAC X HandTite Guard standard with 7/8 in (22 mm) gun nut and OneSeal
 - ▶ Can be combined for extended reach up to 6 ft (1.8 m)
- | | | | |
|--------|---------------|--------|---------------|
| 287019 | 10 in (25 cm) | 287021 | 20 in (50 cm) |
| 287020 | 15 in (38 cm) | 287022 | 30 in (75 cm) |



RAC 5 Tip Extensions

Maximum WPR: 4050 psi, (280 bar, 28.0 MPa)

- ▶ Includes: RAC 5 HandTite Guard standard with 7/8 in (22 mm) gun nut and OneSeal
 - ▶ Can be combined for extended reach up to 6 ft (1.8 m)
- | | | | |
|--------|---------------|--------|---------------|
| 243295 | 10 in (25 cm) | 243297 | 20 in (50 cm) |
| 243296 | 15 in (38 cm) | 243298 | 30 in (75 cm) |



Heavy-Duty Extensions

Maximum WPR: 3600 psi, (248 bar, 24.8 MPa)

- ▶ Tough, lightweight aluminum construction
 - ▶ Can be combined for extended reach up to 12 ft (3.6 m)
 - ▶ Attach to any airless spray gun or In-Line Valve
 - ▶ Ideal for high pressure spraying or low pressure roller applications
- | | | | |
|--------|----------------|--------|----------------|
| 232121 | 10 in (25 cm) | 232124 | 60 in (150 cm) |
| 232122 | 20 in (50 cm) | 232125 | 80 in (200 cm) |
| 232123 | 40 in (100 cm) | | |



Telescoping Extensions

Maximum WPR: 3000 psi, (207 bar, 20.7 MPa)

- ▶ Use Telescoping Extensions for Pressure Rolling only – do not use for airless spraying
 - ▶ All Telescoping Extensions include Adapter 244825; for use with 7/8 in (22 mm)
 - ▶ Contractor In-Line Valve
- | | |
|--------|------------------------------|
| 218775 | 18 to 36 in (45 to 90 cm) |
| 218776 | 36 to 72 in (90 to 180 cm) |
| 218777 | 72 to 144 in (180 to 360 cm) |

ADAPTERS



235486



224399

180° Easy Turn Directional Spray Nozzle

- ▶ Sprays at a variety of angles by attaching to any Graco Extensions
- ▶ Maximum Working Pressure: 3600 psi (248 bar, 24.8 MPa)
- ▶ Thread Size: 7/8 in (22 mm)
- ▶ Instruction Manual: 308244

45° Adapter

- ▶ Connects to Airless Spray Gun and any Graco Extension for use with Pressure Roller or JetRoller
- ▶ Maximum Working Pressure: 3600 psi (248 bar, 24.8 MPa)
- ▶ Thread Size: 7/8 in (22 mm)