

# Finex™

## Air Spray Guns



HVL Pressure Feed

Mini Gravity Feed

HVL Gravity Feed

HVL Gravity Feed Side Cup

### Lightweight, Ergonomic Air Spray Guns:

- Aircaps optimized for high quality spray performance
- Lightest trigger pull in its category
- Integrated air inlet adjustment (cheater) valve
- Durable stainless steel trigger comes standard on all Finex gun models

### Finex Pressure Feed Guns:

- Available in HVL and Conventional technologies
- Needle/nozzle sizes offered in 0.039" (1.0 mm), 0.047" (1.2 mm), 0.055" (1.4 mm) and 0.071" (1.8 mm)

### Finex Gravity Feed Guns:

- Mini and Standard Gravity Feed offered in a wide variety of needle/nozzle sizes
- Plastic cup included with the gun

### Finex Gravity Feed Side Cup Guns:

- Cup swivels for spraying in small spaces
- Aluminum cup included with gun

# Ordering Information

| Gun Style                          | Gun Part Number | Needle/Nozzle Size |     | Needle, Nozzle Air Cap Kit | Needle Packing Kit | Gravity Cup Kits                    | PPS Adapter | Trigger Repair Kit (stainless steel) |
|------------------------------------|-----------------|--------------------|-----|----------------------------|--------------------|-------------------------------------|-------------|--------------------------------------|
|                                    |                 | in                 | mm  |                            |                    |                                     |             |                                      |
| Pressure Feed Standard HVLP        | 289247          | 0.039              | 1.0 | 289301                     | 288891             | -                                   | -           | 24F061                               |
|                                    | 289248          | 0.047              | 1.2 | 289302                     |                    |                                     |             |                                      |
|                                    | 289249          | 0.055              | 1.4 | 289303                     |                    |                                     |             |                                      |
|                                    | 289250          | 0.071              | 1.8 | 289304                     |                    |                                     |             |                                      |
| Pressure Feed Conventional         | 289252          | 0.039              | 1.0 | 289306                     | 288891             | -                                   | -           | 24F061                               |
|                                    | 289253          | 0.047              | 1.2 | 289307                     |                    |                                     |             |                                      |
|                                    | 289254          | 0.055              | 1.4 | 289308                     |                    |                                     |             |                                      |
|                                    | 289255          | 0.071              | 1.8 | 289309                     |                    |                                     |             |                                      |
| Gravity Feed Mini-HVLP             | 289256          | 0.024              | 0.6 | 289286                     | 288890             | 289323 (125 cc Plastic)             | 289520      | 24F059                               |
|                                    | 289257          | 0.031              | 0.8 | 289287                     |                    |                                     |             |                                      |
|                                    | 289258          | 0.039              | 1.0 | 289288                     |                    |                                     |             |                                      |
|                                    | 289259          | 0.047              | 1.2 | 289289                     |                    |                                     |             |                                      |
|                                    | 289260          | 0.055              | 1.4 | 289290                     |                    |                                     |             |                                      |
| Gravity Feed Standard Conventional | 289243          | 0.051              | 1.3 | 289292                     | 288891             | 289322 (600 cc Plastic)             | 289520      | 24F061                               |
|                                    | 289244          | 0.055              | 1.4 | 289293                     |                    |                                     |             |                                      |
|                                    | 289245          | 0.059              | 1.5 | 289294                     |                    |                                     |             |                                      |
|                                    | 289246          | 0.071              | 1.8 | 289295                     |                    |                                     |             |                                      |
| Gravity Feed Standard HVLP         | 289238          | 0.051              | 1.3 | 289297                     | 288891             | 289322 (600 cc Plastic)             | 289520      | 24F061                               |
|                                    | 289239          | 0.055              | 1.4 | 289298                     |                    |                                     |             |                                      |
|                                    | 289240          | 0.059              | 1.5 | 289299                     |                    |                                     |             |                                      |
|                                    | 289241          | 0.071              | 1.8 | 289300                     |                    |                                     |             |                                      |
| Side Cup Gravity Feed Conventional | 24J601          | 0.039              | 1.0 | 24J881                     | 288891             | 24J884 (400 cc or 13.5 oz Aluminum) | -           | 24F061                               |
|                                    | 24J602          | 0.047              | 1.2 | 24J882                     |                    |                                     |             |                                      |
|                                    | 24J603          | 0.055              | 1.4 | 24J883                     |                    |                                     |             |                                      |
| Side Cup Gravity Feed HVLP         | 24J599          | 0.047              | 1.2 | 24J879                     | 288891             | 24J884 (400 cc or 13.5 oz Aluminum) | -           | 24F061                               |
|                                    | 24J600          | 0.055              | 1.4 | 24J880                     |                    |                                     |             |                                      |

| Technical Data | Accessories |
|----------------|-------------|
|----------------|-------------|

Maximum air inlet pressure . . . . . 100 psi (7 bar, 0.7 MPa)  
 Maximum fluid working pressure . . . . . 100 psi (7 bar, 0.7 MPa)  
 Gravity Feed:  
 Maximum HVLP inbound air pressure. . . . . 29 psi (2 bar, 0.2 MPa)\*  
 Pressure Feed:  
 Maximum HVLP inbound air pressure. . . . . 24 psi (1.7 bar, 0.17 MPa)\*  
 Air consumption  
 Mini HVLP Gravity . . . . . 7.0 SCFM at 29 psi (2.0 bar, 0.2 MPa)  
 Conventional Gravity . . . . . 9.5 SCFM at 43 psi (3.0 bar, 0.3 MPa)  
 HVLP Gravity. . . . . 9.5 SCFM at 29 psi (2.0 bar, 0.2 MPa)  
 HVLP Pressure . . . . . 11.8 SCFM at 24 psi (1.7 bar, 0.17 MPa)  
 Conventional Pressure. . . . . 11.0 SCFM at 50 psi (3.4 bar, 0.34 MPa)  
 Fluid and air operating temperature range . . . . . 32-109°F (0-43°C)  
 Spray Gun  
 Air inlet. . . . . 1/4 npsm (R1/4-19)  
 Fluid inlet (pressure feed) . . . . . 3/8-18 npsm (R3/8-19)  
 Wetted parts. . . . . Aluminum, stainless steel, engineered plastic

*\*Produces 10 psi (0.7 bar, 0.07 MPa) spraying pressure at aircap.*

- For use with Mini-Gun**  
 24F733 Glaze nozzles  
 24F734 Glaze aircap
- Aluminum Cups\*\***  
 289858 125 cc Aluminum  
 289860 600 cc Aluminum
- 3M's PPS Accessories\*\***  
 For use with standard gravity feed guns
- 6 oz (150 ml) 3M PPS**  
 234941 Cup and Collar (box of 8)  
 234940 Lid and Liner (box of 50)
- 25 oz (650 ml) 3M PPS**  
 234771 Cup and Collar (box of 8)  
 234772 Lid and Liner (box of 50)
- 32 oz (850 ml) 3M PPS**  
 234937 Cup and Collar (box of 4)  
 234938 Lid and Liner (box of 25)
- \*\*Not compatible with Finex gravity feed side cup guns.*



All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.  
**800.328.0211** or visit us at [www.graco.com/finishing](http://www.graco.com/finishing)

