



Finex™ Air Spray Package

Affordable Spray Package for High Quality Finishing



Finex air spray package provides:

- Finex Pressure Feed gun provides high quality spray performance
- Durable Husky™ 307 pump with stainless steel components
- Low pulsation output due to fluid regulator
- Package includes a 25 foot (7.6 m) air and fluid hose
- Small and lightweight package on a 2-legged stand is easy to transport
- Designed for custom wood and job shop applications

PROVEN QUALITY. LEADING TECHNOLOGY.



Ordering Information Packages & Guns

Package	Part Number	Gun Part Number	Needle/Nozzle Size in (mm)
Finex Air Spray Package with Conventional Finex Gun	289353	289254	0.055 (1.4)
Finex Air Spray Package with HVLP Finex Gun	289354	289249	0.055 (1.4)

Technical Specifications

Maximum fluid working pressure 100 psi (7 bar, 0.7 MPa)

Maximum incoming air pressure 100 psi (7 bar, 0.7 MPa)

Maximum HVLP gun inbound air pressure* . . .24 psi (1.7 bar, 0.17 MPa)

**produces 10 psi (0.7 bar, 0.07 MPa) spraying pressure at aircap*

Operating temperature range. 40-109°F (4.4-43°C)

Package weight 19.8 lb (9 kg)

Air consumption	Conventional	HVLP
Husky:	1.5 scfm	Husky: 1.5 scfm
Finex:	11.0 scfm	Finex: 13.0 scfm
Total:	12.5 scfm	Total: 14.5 scfm

Wetted parts

Pump Acetal, PTFE, SST

Gun Aluminum, SST, engineered plastic

Other Nylon

Instruction Manuals

Finex Air Spray Package 312473

Finex Air Spray Gun 312388

Husky 307 AODD Pumps 308553

Fluid Pressure Regulators 308325

Accessories

Suction Hoses

245082* Aluminum, 4 ft (1.2 m), for 5 gal (18.9 l) pail

245083** Stainless steel, 4 ft (1.2 m), for 5 gal (18.9 l) pail

**Requires adapter fitting 162485*

***Requires adapter fitting 112100*

Fluid Regulators

241976 Fluid regulator, acetal, 0-60 psi (0-4 bar, 0-0.4 MPa)

236450 Fluid regulator, acetal, 20-100 psi (1.4-7 bar, 0.14-0.7 MPa)

Pump Outlet Fluid Filters

Filters attach to the outlet of the Husky pump

235677 Fluid filter, aluminum, 60 mesh (250 micron), 1/4 npsm(f) inlet x 1/4 npsm(m) outlet, 3000 psi (207 bar, 21 MPa)

Gun Inlet Fluid Filters

Attaches between hose and gun inlet to prevent particles from contaminating sprayed surface

915921 Gun inlet filter, stainless steel, 100 mesh (150 micron), 3/8 npsm (m x f), 500 psi (35 bar, 3.5 MPa)

238564 Replacement screen elements, 25 count, 60 mesh (250 micron), stainless steel

238562 Replacement screen elements, 25 count, 100 mesh (150 micron), stainless steel

Bundled Hoses

289522 Air/fluid hose, 25 ft (7.6 m), stainless steel couplings for package number 289353

240421 Air/fluid hose, 25 ft (7.6 m), stainless steel couplings for package number 289354

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.

877.84GRACO (1-877-844-7226) or visit us at www.graco.com.