

Plural Component Equipment

Heated Hoses – Reliable performance for plural-component sprayers

Heated hoses are designed for use with plural component high-pressure airless equipment, such as the Graco XP™ and XM™ plural component sprayers.



Safety Information

Remember to check your airless hose for kinks anywhere along its length.

The hose should also be closely examined for splits, cracks or abrasions. Bulging anywhere on the hose or any amount of separation from the coupling could lead to hose failure and it should be replaced. For optimum hose life, never exceed the hose's rating for pressure and temperature.

Ordering Information

Water Jacketed Heated Hose (Approved for explosive atmospheres) 15.2 m (50 ft) sections

24M440.....	9.53 mm x 6.35 mm (3/8 in x 1/4 in)	345 bar (5000 psi, 34.5 MPa)
24M441.....	9.53 mm (3/8 in x 3/8 in)	345 bar (5000 psi, 34.5 MPa)
24M442.....	13 mm x 6.35 mm (1/2 in x 1/4 in)	345 bar (5000 psi, 34.5 MPa)
24M443.....	13 mm x 9.53 mm (1/2 in x 3/8 in)	345 bar (5000 psi, 34.5 MPa)
24M444.....	13 mm (1/2 in x 1/2 in)	345 bar (5000 psi, 34.5 MPa)
248118.....	13 mm (1/2 in x 1/2 in)	500 bar (7250 psi, 50 MPa)
248119.....	9.53 mm (3/8 in x 3/8 in)	500 bar (7250 psi, 50 MPa)
248120.....	13 mm x 9.53 mm (1/2 in x 3/8 in)	500 bar (7250 psi, 50 MPa)
248121.....	9.53 mm x 6.35 mm (3/8 in x 1/4 in)	500 bar (7250 psi, 50 MPa)
24M439.....	13 mm x 6.35 mm (1/2 in x 1/4 in)	500 bar (7250 psi, 50 MPa)

Electrically Heated Hoses - (Not approved for explosive atmospheres), 345 bar (5000 psi, 34.5 MPa) 15 m (50 ft), with FTS cable

248907.....	6 mm x 10 mm (1/4 in x 3/8 in)	345 bar (5000 psi, 34.5 MPa)
248908.....	10 mm (3/8 in x 3/8 in)	345 bar (5000 psi, 34.5 MPa)
262727.....	13 mm x 5 mm (1/2 in x 1/4 in)	345 bar (5000 psi, 34.5 MPa)
262728.....	13 mm x 10 mm (1/2 in x 3/8 in)	345 bar (5000 psi, 34.5 MPa)
262730.....	13 mm (1/2 in x 1/2 in)	345 bar (5000 psi, 34.5 MPa)
24P616.....	Electric hose heat control kit	
24M943.....	Fluid temperature sensor kit (FTS), 1/2 in (13 mm) (fbc) - requires adapter fittings (for 500 bar)	
261669.....	Fluid temperature sensor kit (FTS), 1/2 in (13 mm) (fbc) - requires adapter fittings (for 345 bar)	



Static Mixing, 500 bar (7250 psi, 50 MPa)

262478.....	Static mix housing kit, 12 mm x 127 mm (1/2 in x 5 in)	500 bar (7250 psi). Uses 248927 mix elements
248927.....	25-pack, disposable, 12 mm (1/2 in), 12 element acetal sticks fit 15E592 housing	
511352.....	Static mixer, 500 bar (7250 psi, 50.0 MPa), MxM, 9.5 mm x 241 mm (3/8 npt x 9.5) in npt, 12 welded set elements, SST	

Protect your investment! Scuff Guard provides extra protection and prolongs the life of your hose.

Available in two sizes and fabrications.

246078.....	Scuff Guard, 15.2 m (50 ft) braided polyester mesh. Blue 2.5 in nominal diameter
246456.....	Scuff Guard, 15.2 m (50 ft) polyethylene (6 mil) clear tubing 5 in diameter
16T138.....	Reusable Scuff Jacket with hook and loop fastener, 15.2 m (50 ft)