Husky™

Pumping Technology

Our Husky air-operated double diaphragm pumps are loaded with features to help you get the job done right, every time, and are built to save you money.

Rugged construction
Resists corrosion for reliable performance and long life

Heavy-duty design - Offers long life, increased productivity and lower overall cost of ownership

Flow rates up to 300 gpm (1135 lpm)

Lube-free for cleaner operation

DataTrak™ available to prevent pump runaway and track material usage

Husky 3300
3 in (76.2 mm) connection
Max flow: 300 gpm (1135 lpm)
Polypropylene, aluminum, stainless steel

Husky 2200
2 in (50.8 mm) connection
Max flow: 200 gpm (757 lpm)
Polypropylene, PVDF

Husky 2150
2 in (50.8 mm) connection
Max flow: 150 gpm (568 lpm)
Polypropylene, PVDF, aluminum, stainless steel, iron

Husky 15120
1-1/2 in (38.1 mm) connection
Max flow: 120 gpm (454 lpm)
Polypropylene, PVDF

Husky 1590
1-1/2 in (38.1 mm) connection
Max flow: 90 gpm (340 lpm)
Polypropylene, PVDF, aluminum, stainless steel

Husky 1050
1 in (25.4 mm) connection
Max flow: 50 gpm (189 lpm)
Aluminum, polypropylene, PVDF, conductive polypropylene, hastelloy, stainless steel