

# Air-Operated Double Diaphragm Pumps

## Husky™ Pumping Technology

Our Husky air-operated double diaphragm pumps are loaded with features to help you get the job done right, every time, and are built to save you money.

### Rugged construction

Resists corrosion for reliable performance and long life

**Heavy-duty design** - Offers long life, increased productivity and lower overall cost of ownership

**Flow rates** up to 300 gpm (1135 lpm)

**Lube-free** for cleaner operation

**DataTrak™** available to prevent pump runaway and track material usage



### Husky 3300

3 in (76.2 mm) connection  
Max flow: 300 gpm (1135 lpm)  
Polypropylene, aluminum,  
stainless steel



### Husky 2200

2 in (50.8 mm) connection  
Max flow: 200 gpm (757 lpm)  
Polypropylene, PVDF



### Husky 2150

2 in (50.8 mm) connection  
Max flow: 150 gpm (568 lpm)  
Polypropylene, PVDF, aluminum,  
stainless steel, iron



### Husky 15120

1-1/2 in (38.1 mm) connection  
Max flow: 120 gpm (454 lpm)  
Polypropylene, PVDF



### Husky 1590

1-1/2 in (38.1 mm) connection  
Max flow: 90 gpm (340 lpm)  
Polypropylene, PVDF, aluminum,  
stainless steel



### Husky 1050

1 in (25.4 mm) connection  
Max flow: 50 gpm (189 lpm)  
Aluminum, polypropylene, PVDF,  
conductive polypropylene,  
hastelloy, stainless steel