



XTR™ Airless Spray Guns

Rugged Design to Handle the Toughest Protective Coatings



Built for Extreme Conditions

- Compact design allows for easy maneuverability
- XTR-5: maximum fluid pressure of 5000 (345 bar, 34.5 MPa)
- XTR-7: maximum fluid pressure of 7250 (500 bar, 50 MPa)
- Variety of handle and trigger options
- High quality materials and construction

PROVEN QUALITY. LEADING TECHNOLOGY.



Lightweight and Ergonomic

Genuine Graco Fluid Hoses Make the Difference

Technical Specifications

Maximum fluid working pressure	XTR-5: 5000 psi (345 bar, 34.5 MPa) XTR-7: 7250 psi (500 bar, 50 MPa)
Fluid orifice	0.090 in (2.3 mm)
Fluid inlet	1/4 npsm
Maximum fluid temperature	160° F (71° C)
Sound pressure	84.3dB(A)*
Sound power	95.7dB(A)*
Dimensions	XTR-5: Weight 14.5 oz (411 g), Length 4.35 in (111 mm), Height 7.1 in (180 mm) XTR-7: Weight 24 oz (688 g), Length 4.35 in (111 mm), Height 7.1 in (180 mm)
Wetted parts	Aluminum, stainless steel, polyethylene, polyurethane, polypropylene, nylon, acetal, carbide, solvent-resistant O-rings
Instruction Manual	312145

* Results are maximum readings taken at 6000 psi (414 bar, 41 MPa), with GHD519 tip, using water. Sound power level was tested to ISO 9614-2.

Ordering Information

XTR-5 Airless Spray Gun

Maximum working pressure:	5000 psi (345 bar, 34.5 MPa)
XTR500	1" round handle, four-finger trigger, no tip
XTR501	1" round handle, four-finger trigger, flat tip*
XTR502	Oval insulated handle, four-finger trigger, GHD RAC tip*
XTR503	Oval insulated handle, two-finger trigger, GHD RAC tip*
XTR504	1" round handle, four-finger trigger, GHD RAC tip*
XTR505	1" round handle, two-finger trigger, GHD RAC tip*
XTR506	7/8" round handle, four-finger trigger, GHD RAC tip*
XTR507	7/8" round handle, two-finger trigger, GHD RAC tip*

XTR-7 Airless Spray Gun

Maximum working pressure:	7250 psi (500 bar, 50.0 MPa)
XTR700	Round handle, four-finger trigger, no tip
XTR701	Round handle, four-finger trigger, flat tip*
XTR702	Oval insulated handle, four-finger trigger, GHD RAC tip*
XTR703	Oval insulated handle, two-finger trigger, GHD RAC tip*
XTR704	Round handle, four-finger trigger, GHD RAC tip*
XTR705	Round handle, two-finger trigger, GHD RAC tip*

*Includes 519 tip

Accessories

287450	2-finger trigger kit	246297	180° spray nozzle, 7/8-14 UNC-2B, 7250 psi (500 bar, 50 MPa)
287449	4-finger round trigger kit	248837	Gun repair kit, includes gasket, needle and seat
287451	4-finger oval insulation trigger kit	245994	GHD tip guard kit
246294	10 in (254 mm) gun extension, 7250 psi (500 bar, 50 MPa)	287032	Filter, 60 mesh, included in every gun
246295	15 in (380 mm) gun extension, 7250 psi (500 bar, 50 MPa)	287033	Filter, 100 mesh
246296	18 in (457 mm) gun extension, 7250 psi (500 bar, 50 MPa)	287034	Filter, 60 and 100 mesh combination

Quality Features for Ultimate Coatings Results

Needle Assembly and GHD RAC® SwitchTip™

- Exceptional life, pattern and finish
- Great for high solids coatings
- Factory set needle needs no adjustments

Variety of Handle and Trigger Options

- 2- and 4-finger trigger options
- Oval-insulated or round handle
- Lightweight trigger pull

Easy Out™ Gun Filter

- Reduces tip plugs
- Eliminates collapsed filters
- Provides more filtration area

Trigger Guard

- Easily detaches for access to filter
- Acts as a wrench to remove filter from gun handle
- Small profile sprays in tight areas

EasyGlide™ Swivel

- Allows easier gun movement under high pressure



Xtreme-Duty 4500 psi (310 bar) High Pressure Hose			
Part #	Length	Hose Diameter	Female NPSM
H42503	3 ft (0.9 m)	1/4 in (6.4 mm)	1/4 in
H42506	6 ft (1.8 m)	1/4 in (6.4 mm)	1/4 in
H42510	10 ft (3.0 m)	1/4 in (6.4 mm)	1/4 in
H42525	25 ft (7.6 m)	1/4 in (6.4 mm)	1/4 in
H42550	50 ft (15.2 m)	1/4 in (6.4 mm)	1/4 in
H4251X	100 ft (30.5 m)	1/4 in (6.4 mm)	1/4 in
H43803	3 ft (0.9 m)	3/8 in (9.5 mm)	3/8 in
H43806	6 ft (1.8 m)	3/8 in (9.5 mm)	3/8 in
H43810	10 ft (3.0 m)	3/8 in (9.5 mm)	3/8 in
H43825	25 ft (7.6 m)	3/8 in (9.5 mm)	3/8 in
H43850	50 ft (15.2 m)	3/8 in (9.5 mm)	3/8 in
H4381X	100 ft (30.5 m)	3/8 in (9.5 mm)	3/8 in
H45010	10 ft (3.0 m)	1/2 in (12.7 mm)	1/2 in
H45025	25 ft (7.6 m)	1/2 in (12.7 mm)	1/2 in
H45050	50 ft (15.2 m)	1/2 in (12.7 mm)	1/2 in
H4501X	100 ft (30.5 m)	1/2 in (12.7 mm)	1/2 in

Xtreme-Duty 5600 psi (386 bar) High Pressure Hose			
Part #	Length	Hose Diameter	Female NPSM
H52503	3 ft (0.9 m)	1/4 in (6.4 mm)	1/4 in
H52506	6 ft (1.8 m)	1/4 in (6.4 mm)	1/4 in
H52510	10 ft (3.0 m)	1/4 in (6.4 mm)	1/4 in
H52525	25 ft (7.6 m)	1/4 in (6.4 mm)	1/4 in
H52550	50 ft (15.2 m)	1/4 in (6.4 mm)	1/4 in
H5251X	100 ft (30.5 m)	1/4 in (6.4 mm)	1/4 in
H53803	3 ft (0.9 m)	3/8 in (9.5 mm)	3/8 in
H53806	6 ft (1.8 m)	3/8 in (9.5 mm)	3/8 in
H53810	10 ft (3.0 m)	3/8 in (9.5 mm)	3/8 in
H53825	25 ft (7.6 m)	3/8 in (9.5 mm)	3/8 in
H53850	50 ft (15.2 m)	3/8 in (9.5 mm)	3/8 in
H5381X	100 ft (30.5 m)	3/8 in (9.5 mm)	3/8 in
H55010	10 ft (3.0 m)	1/2 in (12.7 mm)	1/2 in
H55025	25 ft (7.6 m)	1/2 in (12.7 mm)	1/2 in
H55050	50 ft (15.2 m)	1/2 in (12.7 mm)	1/2 in
H5501X	100 ft (30.5 m)	1/2 in (12.7 mm)	1/2 in

Xtreme-Duty 7250 psi (500 bar) High Pressure Hose			
Part #	Length	Hose Diameter	Female NPSM
H72503	3 ft (0.9 m)	1/4 in (6.4 mm)	1/4 in
H72506	6 ft (1.8 m)	1/4 in (6.4 mm)	1/4 in
H72510	10 ft (3.0 m)	1/4 in (6.4 mm)	1/4 in
H72525	25 ft (7.6 m)	1/4 in (6.4 mm)	1/4 in
H72550	50 ft (15.2 m)	1/4 in (6.4 mm)	1/4 in
H7251X	100 ft (30.5 m)	1/4 in (6.4 mm)	1/4 in
H73803	3 ft (0.9 m)	3/8 in (9.5 mm)	3/8 in
H73806	6 ft (1.8 m)	3/8 in (9.5 mm)	3/8 in
H73810	10 ft (3.0 m)	3/8 in (9.5 mm)	3/8 in
H73825	25 ft (7.6 m)	3/8 in (9.5 mm)	3/8 in
H73850	50 ft (15.2 m)	3/8 in (9.5 mm)	3/8 in
H7381X	100 ft (30.5 m)	3/8 in (9.5 mm)	3/8 in
H75010	10 ft (3.0 m)	1/2 in (12.7 mm)	1/2 in
H75025	25 ft (7.6 m)	1/2 in (12.7 mm)	1/2 in
H75050	50 ft (15.2 m)	1/2 in (12.7 mm)	1/2 in
H7501X	100 ft (30.5 m)	1/2 in (12.7 mm)	1/2 in