HIGH PRESSURE CLEANERS



APPLICATIONS



Domestic Cleaning



Car Cleaning



Motor Bike Cleaning



Agriculturist





STANDOUT FEATURES



OEM[™] sealed axial pump delivers performance and longer life.



13" premium pneumatic tyres.



0°, 15, 25, 40 and snap-on nozzles.

start series engine.

Domestic reliable Honda[™] GC190 pull



Jetwave Safety System[™] (JSS) thermal and safety valve to prevent overheating in excessive bypass and over pressurisation.



Dual M22 screw hose coupling system.







TECHNICAL DATA 0:00	0	JLACC GC
Product Code		CW3300-9.1P
Pressure / Flow Rate		3300 PSI (230 BAR) / 9.1 L/PM
Max Inlet Temp		60°C
Class (ASNZS: 4223)		A (2,093 Bar/Litres)
Usage Frequency		Domestic: 1 Hour a Week
Nozzle Size		03
Frame Structure		Heavy duty steel black powder coat 2-wheel trolley
MOTOR FEATURES 🕻	Ţ.	
Engine / Power		Honda [™] GC190 Pull Start (air cooled) 6HP / 190cc
Fuel Type / Capacity / Protection		Unleaded / 2L / Low Oil Shutdown
HYDRAULIC FEATUR	es 쁬	
Pump / Head / Pistons		Axial (OEM) / Brass / Ceramic Coated
Motor Pump Coupling / Pump RPM		Direct Drive / 3400RPM
Unloader Valve		Integral
Safety Valve		Yes
Detergent Injector		Yes - Downstream low pressure
DIMENSIONS & WEIG	нт 🗊	
Machine Dimensions / Weight		800mm(L) x 520mm(W) x 580mm(H) / 36KG
WARRANTY(S) 🕢		
Unit / Pump Warranty*		a Year
Engine Warranty*		2 Years (Domestic Use) / 90 Days (Commerical Use)
OPTIONAL ACCESSO	RIES	
10m Extension Hose + M22 Joiner	JWA018-EX	
JW3 Foaming Lance with Tank	JWA221	
15" Hammerhead with Lance	JWA-FSC15-CMPL	

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement. *Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).

