# 3L/CC GX









HONDA GX270

**HONDA** 







#### **APPLICATIONS**



Domestic Cleaning



Tradesmen



**Commercial Cleaners** 



Agriculturist





## STANDOUT FEATURES



AAA™ triplex plunger pump delivers performance & reliability.



Industrial Honda<sup>™</sup> GX270 pull start series engine.



Jetwave Safety System™ (JSS) thermal and safety valve to prevent overheating in excessive bypass and over pressurisation.



13" premium pneumatic tyres.



0°, 15, 25, 40 and snap-on nozzles.



Dual M22 screw hose coupling system.













High Pressure Gun + single lance + 5 snap on nozzles



15m High Pressure Hose with quick Couplings.



#### TECHNICAL DATA 0:00

**BLACK** GX

Product Code

Pressure / Flow Rate 4000 PSI (275 BAR) / 13.5 L/PM

Max Inlet Temp 60C°

Class (ASNZS: 4223) A (3,712 Bar/Litres)

Usage Frequency Semi Professional: 1-3 Hours a Week

Nozzle Size

Frame Structure Heavy duty steel 2-wheel trolley

# **MOTOR FEATURES**

Engine / Power Honda™ GX270 Pull Start (air cooled) 9HP / 270cc

Fuel Type / Capacity / Protection Unleaded / 4.5L / Low Oil Shutdown

#### عليل **HYDRAULIC FEATURES**

Pump / Head / Pistons Plunger Triplex / Brass / Ceramic Coated

Motor Pump Coupling / Pump RPM Direct Drive / 3400RPM

Unloader Valve Integral

Safety Valve Yes

Detergent Injector Yes - Downstream low pressure

## DIMENSIONS & WEIGHT

Machine Dimensions / Weight  $940mm(L) \times 560mm(W) \times 680mm(H) / 66KG$ 

#### WARRANTY(S) 🕢

Unit / Pump Warranty\* 1 Year Engine Warranty\* 📆 3 Years

#### **OPTIONAL ACCESSORIES**

10m Extension Hose + M22 Joiner JWA018-EX JW3 Foaming Lance with Tank JWA221 21" Hammerhead - Plastic JWA-FSC21

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement. \*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).







