

Mirka® AROS-B / AOS-B 32 mm (1 1/4")



Technical Data	Mirka® AROS-B 150NV	Mirka® AOS-B 130NV
Code	8991150311	8991230311
Voltage	10.8 VDC	10.8 VDC
Speed	4,000–8,000 rpm	4,000–8,000 rpm
Orbit	5.0 mm ($\frac{9}{16}$ ")	3.0 mm ($\frac{1}{8}$ ")
Weight	0.56 kg	0.57 kg
Size of backing pad	Ø 32 mm (1 1/4")	Ø 32 mm (1 1/4")
Degree of protection	III	III

Battery charger	BCA 108
Input	100–240 VAC, 50/60 Hz
Charging time	< 40 min (2.0 Ah)
Storage temperature range	-20 °C...80 °C
Charging temperature	-0 °C...40 °C
Dimension	191 x 102 x 86 mm
Net weight	0.66 kg
Degree of protection	II / □

Battery pack	BPA 10820
Type	Rechargeable Li-ion 3I(NCM)R19/65
Battery voltage	10.8 VDC
Capacity	2.0 Ah 21.6 Wh

Accessories for Mirka Cordless Sanders

			
8991123011	8991122111	8991112211	8991199111
Battery Charger BCA 108 10.8V w/o power cord	Battery Pack BPA 10820 10.8V 2.0Ah	Power Cord 2.0m for Battery Charger BCA 108	Mirka Multi-Purpose Belt