



Electric Start Diesel Pump DN50 (2 Inch) 240lpm Yanmar L48N Engine

No power, no problem. The GO Fill DMTP0012 Electric Start, Diesel Powered, Positive Displace Vane Pump provides a true stand alone, heavy duty diesel dispensing solution. An ever reliable Yanmar L48N Engine has been coupled with an Italian made Positive Displacement Vane Pump to provide a fully engineered diesel fuel dispensing package suitable for use with GO Self Bunded Tanks, GO Self Bunded Fuel Trailers or to retro fit to your existing site infrastructure.

Technical Specifications

Flow Rate (1 bar): 240lpm

Max Pressure: 2.5 Bar

Inlet DN50 (2") BSP F + Flanged

Outlet: DN50 (2") BSP F + Flanged

Suction: 2.5 metre

Engine Rotation: 3600 rpm

Power: 3550watt (4.7hp)

Seal: 6 Bar Mechanical Seal

Battery: not included - 12V 45A

Compatible Liquids: Diesel and Low Viscosity Oils

Product Dimensions: 45cm L x 37.5cm W x 37cm H

Package Dimensions: 58cm L x 68cm W x 63cm H

Weight: 59 kg





Features

- High Flow: DN50 (2") BSP Female Inlet and Outlet providing a consistent 200lpm flow rate
- Made in Italy Quality
- **Portability:** It is a portable solution as it doesn't require an external power source.
- **Self-Priming:** The Pump automatically draws fuel without manual priming.
- Pump Seal: The pump is equipped with a 6 bar mechanical seal. This high-quality seal prevents leaks and ensures a long service life.
- Inlet Strainer: 130µm inlet strainer, which helps to remove impurities from the fuel, protecting the pump's internal components from damage and ensuring clean fuel
- **Robust Design:** Built for durability in challenging environments.
- Yanmar Quality: Electric Start genuine Yanmar L48N Diesel Driven Engine
- Balanced Cylinders: The engine has balanced cylinders, which helps to reduce vibration during operation. This contributes to a smoother and quieter running pump.
- Motion Transmission: It uses a supported crankshaft for motion transmission, which contributes to its durability and stable operation.

