

# GO FAR

## SINGLE WALL TANK RANGE



The GO FAR Single Wall Tank range is designed as an economical bulk fuel, lubricants or waste oil tank for Agriculture, Construction and Industrial applications. This innovative yet cost effective single wall tank range is manufactured to the strictest quality

standards and meets the design and fabrication requirements of AS1692. The range includes 4,500L | 8,500L | 12,000L | 17,500L Safe Fill Level tanks. For quick deployment we carry these ex stock, subject of course to prior sale.

### PRODUCT FEATURES:

#### APPROVALS

- Designed and approved to AS1692.
- NOTE - to be installed in accordance with AS1940-2017 and State Environmental requirements

#### TANK DESIGN

- Mild Steel Q234B 3mm
- Robust Cylindrical Manufacture designed to handle our unique conditions
- Heavy Duty Cradle Assembly ready to fasten to a concrete pad
- Full under tank visibility for ongoing maintenance inspections
- Crane Lifting Lugs

#### PAINT

- White, Two Pack Epoxy Marine Grade

#### STATUTORY DECALS

- Supplied with all required Statutory Decals

#### OUTLET

- DN50 (2") Gravity Outlet with Isolation Valve

#### FILL

- DN50 (2") Fill Line with Camlock Dust Cap / Non Return Valve / Isolation Valve
- Nozzle Fill option with dedicated Fill / Dip Point.
- Dip Point with Calibrated Anodised Aluminium Dipstick
- Optional Overfill Alarm is available

#### ACCESS

- Galvanised stairway and platform assembly for access to the tank dip point.

#### VENT

- DN50 (2") Galvanised Vent Pipe with Updraft Vent Assembly.
- Option for Filtered Breather Assembly



### SPECIFICATIONS

CODE	CAPACITY (litres)	SAFE FILL LEVEL (litres)	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	WEIGHT (kg)
FAR-4.5	4,830	4,500	2,895	1,800	1,935	668
FAR-8.5	8,948	8,500	3,669	2,050	2,185	850
FAR-12	12,630	12,000	4,677	2,086	2,229	1,018
FAR-17.5	18,433	17,500	6,569	2,050	2,185	1,463