

## ► Z60, Z45 and Z25 Electric Series

The Z60, Z45 and Z25 Sprayers are an electric alternative to air-operated single-leg sprayers. They produce a smooth, consistent, evenly distributed spray pattern – without the need to tow a large compressor.

### *Disconnect Switch*

- Easily accepts 240V x 1-phase power

### *Portable, Lightweight Cart*

- Easy to maneuver

### *Xtreme Lower*

- 145cc for optimal pressure flow
- Quick knock down for easy repairs

### *Dual Cooling Fans*

- Sprayer operates in temperatures up to 120°F (50°C)
- Ideal for continuous duty applications

### *Electric Driver*

- Powerful and capable – up to 6000 psi (414 bar, 41.4 MPa)
- Fit for outdoor use



# ► Which Electric System is Right For You?



	Ex - Series		Z - Series		
APPROVALS	Hazardous Locations: ATEX, IECex, FM-US, FM-CAN		Non-Hazardous Locations: Not for use in explosive atmospheres		
MODEL	Ex45	Ex35	Z60	Z45	Z25
Maximum Working Pressure	4500 psi (310 bar, 31.0 MPa)	3500 psi (240 bar, 24.0 MPa)	6000 psi (414 bar, 41.4 MPa)	4500 psi (310 bar, 31.0 MPa)	2600 psi (179 bar, 17.9 MPa)
Maximum Recommended Tip Size	0.021 in (0.53 mm)	0.023 in (0.58 mm)	0.021 in (0.53 mm)	*XHD529	*XHD651
Flow Rate @ Spray Pressure	0.6 gpm (2.3 lpm) @ 4000 psi (276 bar, 27.6 MPa)	0.7 gpm (2.7 lpm) @ 3200 psi (220 bar, 22.0 MPa)	0.7 gpm (2.7 lpm) @ 5000 psi (345 bar, 34.5 MPa)	1.2 gpm (4.5 lpm) @ 4000 psi (276 bar, 27.6 MPa)	2.0 gpm (7.5 lpm) @ 2300 psi (159 bar, 15.9 MPa)
Pump Lower	145cc	180cc	145cc	145cc	250cc
Input Power	2.5 kVA	2.5 kVA	15A	20A	20A
Input Voltage	200 - 240V, 1-phase, 50/60Hz		200 - 240V, 1-phase, 50/60Hz		
Operating Temperature Range	23°F to 120°F (-5°C to 50°C)		23°F to 120°F (-5°C to 50°C)		
Sound Pressure	<80 dB (A)		<80 dB (A)		
Operation Manual	3A3164	3A3164	3A6917	333208	333208

\*Comes with XHD Tip for use with waterbased waterproofing materials.

