



GT RAPIDFLO™

HI-FLOW FUEL PUMP (GT-01)

10 Year
Warranty

*conditions apply

PRODUCT OVERVIEW

The GT RAPIDFLO™ is a rotary action pump suitable for transferring diesel, ULP, aviation fuels, kerosene & light oils (up to SAE30).

The RAPIDFLO™ is capable of transfer rates of 800ml per revolution (up to 100L/min depending on viscosity) from 60 - 205L drums and tanks.

The RAPIDFLO™ is also suitable for users who either cannot use an electric fuel pump for safety reasons or do not have access to power in remote locations.

It can be used to transfer AV-Gas* and Jet A1* although users of aviation fuels must check material compatibility with the fuel product they are using.

FEATURES & BENEFITS

Lockable Handle
To prevent theft of fluid

Anti-kink Springs
Prevents hose from restricting fluid delivery

Rotary Action
Quick, effortless delivery of fluids in both directions

2.4m Anti-static Rubber Hose
Safely transfer gasoline and kerosene

Steel Construction & Fully Repairable
Provides a much longer service life

Nozzle Holder To Prevent Spillage
Allows nozzle to be fixed in non-siphoning position

2" Sliding Bung Adaptor
Suits different height drums from 60L - 205L

Delivers 800ml Per Revolution
Able to achieve flow rates up to 100L/min

Three Piece Suction Tube
Allows length of suction tube to be adjusted to accommodate different height drums

TECHNICAL SPECIFICATIONS

Suitable for 60L - 205L drums

Delivers 800ml per revolution (Up to 100L/min)

2.4m anti-static rubber delivery hose

2" sliding bung adaptor

Three piece suction tube

Suitable for use with petrol, diesel, kerosene, lubricating

oils (up to SAE 30) and some aviation fuels

Wetted Components: Aluminium, Steel, zinc, nitrile rubber, viton

OPTIONAL ACCESSORIES

PACKAGE INCLUDES

GT RAPIDFLO™ pump

2.4m anti-static rubber delivery hose

3 piece suction tube

Built-in 2" sliding bung adaptor

Instruction manual