



Polarshine® 3

Technical data sheet

Product information

Technologically advanced ultra fine polish containing carnauba wax. This formula with antistatic properties gives a hologram free and high gloss finish. Polarshine 3 conserves and protects all paint and lacquer surfaces, top coats and gelcoats.

Product advantages

- · Creates a dust repellent surface
- · Leaves a long lasting surface protection
- Silicone free



Surfaces

- Clear coats
- Top coats
- · Gel coats

Polishing pad

- · Black foam pad
- · Microfibre cloth

Polishing machine

- · Random orbital polisher 6000 10000 rpm
- Manual application
- · Rotary polisher 800 1100 rpm

Product properties

Polish, gloss:

Work instruction

- 1. Shake or stir polishing compound before use
- 2. Do not use too much compound at a time. Use a small amount which is consumed on a focused area less messing and clean up!
- 3. Clean thoroughly before application
- 4. Work focused on an area of 40x40 cm at a time
- 5. Polish until final gloss is achieved
- 6. Wipe surface with microfiber cloth after application
- 7. Keep the pads clean, a dirty pad causes deep swirls and scratches

Technical specifications

Density: 0,95 kg/l Viscosity: 20,5 Pas Colour: White pH: 8,5

Storage recommendations

Recommended storage temperature: 5° - 35° C / 41° - 95° F Keep from freezing