



**Organoil Technical Data Sheet**  
Exterior Decking Oil

## DECKING OIL

For all your external timbers

<b>DESCRIPTION</b>	Natural penetrating oil for the nourishment and protection of all external timbers. Provides anti-mould protection. Contains genuine tung oil, citrus solvents and natural beeswax for water repellency and protection against wood rot. A natural alternative to petroleum hydrocarbons and water-based oils. Specially formulated to suit the Australian and New Zealand harsh climates.		
<b>FEATURES &amp; BENEFITS</b>	<ul style="list-style-type: none"> <li>• Easy application</li> <li>• Suitable for both soft &amp; hardwoods</li> </ul>	<ul style="list-style-type: none"> <li>• Anti mould protection</li> <li>• Waterproof</li> </ul>	<ul style="list-style-type: none"> <li>• Preserves and rejuvenates, protects, nourishes and waterproofs</li> <li>• A natural alternative to petroleum hydrocarbons</li> </ul>
<b>USES</b>	<ul style="list-style-type: none"> <li>• Decking</li> <li>• Joists</li> <li>• Bearers</li> <li>• Weatherboards</li> </ul>	<ul style="list-style-type: none"> <li>• Cladding</li> <li>• Garage doors</li> <li>• Walkways</li> <li>• Fencing</li> </ul>	<ul style="list-style-type: none"> <li>• Screens</li> <li>• Pergolas</li> </ul>
<b>COLOURS</b>	<p><b>Classic Clear</b> Semi-transparent results in a honey brown, producing a minimal colour change to the natural timber colour</p> <p><b>UV Red</b> Semi-transparent finish with additional UV protection. Recommended for use on red/pink timber species</p>	<p><b>Merbau</b> Semi-transparent finish with added colourants and UV protection to enhance redwood timbers</p>	<p><b>Jarrah</b> A heavy weight pigmented oil offering solid colour, suitable for treated pine or old, weathered hardwoods</p>
<b>SHEEN LEVEL</b>	Semi-transparent to semi-opaque matt finish		
<b>SIZE</b>	1L, 4L, 10L	<b>COVERAGE</b>	Up to 14 m <sup>2</sup> per L
<b>NUMBER OF COATS</b>	2 for first time application. For maintenance 1 coat only	<b>RECOAT</b>	24-48 hours
<b>PRECAUTIONS &amp; LIMITATIONS (IMPORTANT INFORMATION):</b>	<p>Not recommended for use on tongue &amp; groove decking and verandahs</p> <p>Organoil is a penetrating oil – not a coating product. Over application or excess oil above the surface will remain tacky, leaving unwanted film that will attract and hold dust/dirt, be easily scratched and readily water marked.</p> <p>Previously finished timber – due to the use of synthetic resins in most other brand finishes, Organoil products may not be compatible with them. If wishing to change to Organoil, you should thoroughly wash, then sand down the surface prior to using Organoil.</p>		
<b>FOR BEST RESULTS:</b>	<p>Maximum of 2 coats only. Light even coats and rubbing surface down with cloth after application will provide best results.</p> <p>If accessible, or prior to installation, apply one application of oil to the joists, bearers and underside of decking boards</p> <p>New Decking – hardwoods (particularly Spotted Gum and plantation species) often have high moisture content. Enquire as to the grade and moisture levels of your hardwood. The use of Woodguard is recommended for high moisture hardwood.</p>		





**Organoil Technical Data Sheet**  
Exterior Decking Oil

<b>APPLY WITH:</b>	Brush, lambswool applicator
<b>SURFACE PREPARATION (HOW TO PREPARE):</b>	<ol style="list-style-type: none"> <li>1. Remove all sawdust, nails, metal filings and dust from on or near your timber.</li> <li>2. Wet the deck and surrounds.</li> <li>3. Clean the timber with suitable timber cleaner. We recommend Organoil Wash-A-Way outdoor cleaner. Apply liberally with a still bristle broom.</li> <li>4. Leave for 30 minutes before washing off. For severely weathered timber consider using a water pressure cleaner.</li> <li>5. Allow timber to dry for a minimum of 48 hours</li> </ol>
<b>APPLICATION PROCEDURE (HOW TO APPLY):</b>	<ol style="list-style-type: none"> <li>1. Ensure you have read and understood all the instructions.</li> <li>2. Shake or stir well prior and during use. Do not thin this product.</li> <li>3. Only apply oil to previously washed, dry timber; preferably mid-morning and with consideration to dry weather forecast for next 48 hours (this includes heavy dews.) Ensure good ventilation when applying.</li> <li>4. Using a lambswool applicator apply the oil evenly along the grain of the timber. Apply 2 coats a minimum 24 hours apart. For rejuvenating only apply 1 coat.</li> <li>5. Do NOT over apply oil.</li> <li>6. A brush should be used to coat the end grain and intricate areas ensuring the timber is fully coated.</li> <li>7. Within 30 minutes - 1 hour of each coat it is essential that you dry brush or cloth in excess surface oil. For large decks, consider shuffling over the areas with old towels under foot or wrapped around broom head.</li> <li>8. Wait minimum 24 hours for the oil to be fully absorbed before applying a second coat.</li> </ol>
<b>HOW TO CLEAN UP:</b>	Clean brushes and applicators in hot soapy water or Gum Turpentine. Wash clothes/towels/rags in warm soapy water and hang out to dry. Oil splatters or spillages should be wiped from glass and other surfaces within 12 hours to avoid permanent marking.
<b>HOW TO MAINTAIN:</b>	<p>The horizontal aspect of decking timbers makes for ready collection of air borne pollutants (roadway, airway and particularly gum soots). Light intermittent washing of the timber will reduce build-up of contaminants and the risk of discolouration.</p> <p>General cleaning is conducted by scrubbing down timber with Wash-A-Way or an alkaline salt cleaner (not oxalic acid), and a bristle brush. After leaving cleaned timber to dry for a minimum 48 hour, apply a single coat of Organoil Decking Oil. Repeat this process every 6-18 months.</p> <p>Areas under cover will not require recoating as often as fully exposed timbers. If after washing timber, beading of water on timber occurs, the oil is still present therefor re-oiling is not yet necessary in these areas.</p>
<b>HEALTH &amp; SAFETY:</b>	<p>Keep out of reach of children.</p> <p>This product contains dipentene (pinewood oil) UN2052 and/or Gum Turpentine UN1299. As such it can be irritating to skin. If irritation occurs, wash immediately with plenty of soapy water.</p> <p>If swallowed do not induce vomiting. Contact Poisons Information Centre phone 131126 in Australia, 0800 764 766 in New Zealand or seek medical advice at once.</p>
<b>STORAGE/ DISPOSAL:</b>	<p>Store in cool dry area with lid tightly sealed. Keep out of reach of children</p> <p>Tung oil is exothermic; therefore, to avoid used oily rags self-combusting later, it is essential to rinse them in warm soapy water and hang to dry prior to disposal.</p> <p>Refer to local authority for disposal advise. Do not empty into drains or waterways. Do not reuse container.</p>

If swallowed do NOT induce vomiting. contact the Poisons Information Centre (Phone: 13 11 26 in Australia or 0800 764 766 in New Zealand or seek Medical Advice at once.

Version 1 of Organoil Technical Data Sheet, August 2021. Organoil is a registered ® trademark. The data provided within this document is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.