

VOC Content Test Certificate

Monday, 29th January 2018

Supplier: Soudal Pty Ltd Australia (1 Tollis Place, Seven Hills, NSW 2147).

Sample Description: Fill & Paint Flexible Gap Filler

Date Tested: January 2018 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: Method 304-91 Determination of Volatile Organic Compounds (VOC) in Various

Materials as referenced by South Coast Air Quality Management District (SCAQMD)

Rule 1168.

Test Data:

Specification

Green Building Council of Australia Green Star Design & As Built V1.1 13.1.1 Green Star Interiors V1.1 12.1.1B

Fill & Paint Flexible Gap Filler

General purpose adhesives and sealants: 50 grams per Litre as VOC content per material

24 grams per Litre as VOC content per material

We hereby certify Fill & Paint Flexible Gap Filler is below the VOC Content limits of chosen category specified by Green Star Design, Green Building Council of Australia

Dr. Vyt Garnys

PhD, BSc(Hons) AIMM, ARACI, ISIAQ

ACA, AIRAH, FMA

Managing Director and Principal Consultant

Tuan Duong BE (Chem. Eng.) Consultant Nick Joy BSc (Hons) Consultant

CV171250